


NOTES:

1) RAKE OUT EXISTING SEALANT AT REGLET. ADD NEW LEAD-WEDGES IF NEEDED, AND RECAULK AS REQUIRED.



AS A MANUFACTURER OF CONSTRUCTION PRODUCTS, SIKA CORPORATION PROVIDES GENERIC DETAILS AS A GENERAL GUIDE FOR INFORMATION PURPOSES ONLY. THESE DETAILS ARE NOT INTENDED TO REPLACE SOUND ENGINEERING AND ARCHITECTURAL PRACTICES AND SHOULD NOT BE RELIED UPON FOR THAT PURPOSE. SIKA CORPORATION ASSUMES NO LIABILITY WITH RESPECT TO THE DESIGN OF THE SYSTEM. THE SYSTEM, FOR THE PREPARATION AND APPROVAL OF THE PROJECT GENERAL SHOULD FOR THE PROJECT OF APPLICATION. WHILE SIX PROVIDES GENERAL INSTRUCTIONS FOR THE INSTALLATION OF ITS MATERIALS, THE MEANS AND METHODS USED BY THE CONTRACTOR FOR MATERIAL STORAGE, SUBSTRATE EVALUATION, SURFACE PREPARATION, AND THE INSTALLATION OF BOTH SIKA AND NON-SIKA MATERIALS ARE THE SESPONISIBILITY OF THE CONTRACTOR. THE CONTRACTOR TOR THE MATERIAL SARE THE SAVAILABLE AT WWW. SIKAUSA COM. SIKA PROPATION MAKES NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, AS TO THE CONTENT OF THIS GUIDE DETAIL. SIKA SHALL NOT BE RESPONSIBILE UNDER ANY SUBJECT TO ITS TERMS AND CONDITIONS OF SALE AVAILABLE AT WWW. SIKAUSA COM.