

# Sikafloor® 225N Part A clear

Revision Date 9/27/2016

# 1. Identification

Product name	:	Sikafloor® 225N Part A clear
Supplier	:	Sika Corporation
Address	:	201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Recommended use of the chemical and restrictions on use	:	For further information, refer to the product technical data sheet.

#### 2. Hazards identification

# **GHS Classification** Skin irritation, Category 2 H315: Causes skin irritation. Eye irritation, Category 2A H319: Causes serious eye irritation. Skin sensitization, Category 1 H317: May cause an allergic skin reaction. **GHS Label element** Hazard pictograms Signal Word : Warning Hazard Statements : H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. **Precautionary Statements** : Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear eye protection/ face protection. P280 Wear protective gloves. **Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and



Print Date 9/27/2016

easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

# 3. Composition/information on ingredients

#### **Hazardous ingredients**

Chemical Name	CAS-No.	Concentration (%)
bisphenol A-(epichlorhydrin), homopolymer	25085-99-8	>= 50 - <= 100 %
oxirane, mono[(C12-14- alkyloxy)methyl]derivatives	68609-97-2	>= 5 - <= 10 %
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	17557-23-2	>= 2 - <= 5 %
2-methylpentane-2,4-diol	107-41-5	>= 2 - <= 5 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.


#### 4. First aid measures

If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Immediately flush eye(s) with plenty of water.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.</li> </ul>
Most important symptoms and effects, both acute and delayed	: irritant effects sensitizing effects
	Allergic reactions Excessive lachrymation

®

# Sikafloor® 225N Part A clear

Revision Date 9/27/2016	Print Date 9/27/2016
	Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Protection of first-aiders	: Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
Notes to physician	: Treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific extinguishing methods	<ul> <li>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.</li> <li>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.</li> </ul>
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	: Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
7. Handling and storage	
Advice on safe handling	<ul> <li>Do not breathe vapors or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.</li> </ul>



Conditions for safe storage	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
Materials to avoid	:	no data available

# 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
2-methylpentane-2,4-diol	107-41-5	ACGIH	С	25 ppm
		OSHA P0	С	25 ppm 125 mg/m3

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### \*\*<u>Basis</u>

ACGIH. Threshold Limit Values (TLV) OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values) OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant OSHA P2. Permissible Exposure Limits (PEL), Table Z-2 OSHA Z3. Table Z-3, Mineral Dust

product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.	Engineering measures	nclosures, local exhaust ventilation or other ig controls to keep worker exposure below any
--	----------------------	--

### Personal protective equipment

Respiratory protection :	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.	
	The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.	
Hand protection Remarks :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.	



# Sikafloor® 225N Part A clear

evision Date 9/27/2016	Print Date 9/27/2016
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	<ul> <li>Avoid contact with skin, eyes and clothing.</li> <li>Wash hands before breaks and immediately after handling the product.</li> <li>Remove contaminated clothing and protective equipment before entering eating areas.</li> <li>Wash thoroughly after handling.</li> </ul>

# 9. Physical and chemical properties

Appearance	:	liquid
Color	:	light yellow
Odor	:	characteristic
Odor Threshold	:	no data available
Flash point	:	> 244 °F (> 118 °C)
Ignition temperature	:	not applicable
Decomposition temperature	:	no data available
Lower explosion limit (Vol%)	:	no data available
Upper explosion limit (Vol%)	:	no data available
Flammability (solid, gas)	:	no data available
Oxidizing properties	:	no data available
Autoignition temperature	:	no data available
рН	:	Note: not applicable
Melting point/range / Freezing point	:	no data available
Boiling point/boiling range	:	no data available
Vapor pressure	:	no data available
Density	:	ca.1.13 g/cm3 at 73 °F (23 °C)
Water solubility	:	Note: negligible
Partition coefficient: n- octanol/water	:	no data available
Viscosity, dynamic	:	no data available



Viscosity, kinematic	:	ca.> 20.5 mm2/s at  104 °F (40 °C)
Relative vapor density	:	no data available
Evaporation rate	:	no data available
Burning rate	:	no data available
Volatile organic compounds (VOC) content	:	46 g/l A+B Combined

### 10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: no data available
Incompatible materials	: no data available

#### 11. Toxicological information

# Acute toxicity

Acute oral toxicity	:	no data available
Acute inhalation toxicity	:	no data available
Acute dermal toxicity	:	no data available

#### Skin corrosion/irritation

# **Product**

Causes skin irritation.

# Serious eye damage/eye irritation

### **Product**

Causes serious eye irritation.

# Respiratory or skin sensitization

### Product



May cause an allergic skin reaction.

# Germ cell mutagenicity

# Product

Mutagenicity : no data available

# Carcinogenicity

# Product

Carcinogenicity	: no data available
-----------------	---------------------

IARC	not applicable
NTP	not applicable

# **Reproductive Toxicity/Fertility**

#### Product

Reproductive toxicity : no	data available
----------------------------	----------------

# Reproductive Toxicity/Development/Teratogenicity

# **Product**

Teratogenicity

: no data available

# STOT-single exposure

### Product

Assessment: no data available

# STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

# Product

Assessment: no data available

# Aspiration toxicity

# Product

no data available

# 12. Ecological information

Other information

Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Print Date 9/27/2016

#### 13. Disposal considerations

Disposal methods	
Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

#### 14. Transport information

DOT Not dangerous goods IATA Not dangerous goods IMDG Not dangerous goods

Special precautions for user no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

# 15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

#### EPCRA - Emergency Planning and Community Right-to-Know

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Acute Health Hazard Chronic Health Hazard
SARA 302	:	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Safety Dat	ta Sheet
Sikafloor	® 225N Part A clear
Revision Date 9/27/2016	Print Date 9/27/2016
SARA 313	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Clean Air Act	
Ozone-Depletion Potential	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Air Act Section 12 (40 C This product does not c	ontain any hazardous air pollutants (HAP), as defined by the U.S. Clean CFR 61). ontain any chemicals listed under the U.S. Clean Air Act Section 112(r) for vention (40 CFR 68.130, Subpart F).
California Prop 65	<b>WARNING</b> : Cancer – <u>www.P65Warnings.ca.gov</u>
16. Other information	

**HMIS Classification** 

Health *	2
Flammability	1
Physical Hazard	0
Personal Protection	X

**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



Print Date 9/27/2016

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 9/27/2016

Material number: 411044