

PRODUCT DATA SHEET

Sikacryl® Pourable Crack Repair Sealant

Fiber reinforced, easy squeeze concrete crack repair sealant

PRODUCT DESCRIPTION

Sikacryl® Pourable Crack Repair Sealant is an easy-to-use, pre-mixed material that is designed to fill and repair narrow cracks on any horizontal concrete surface. This fiber reinforced pourable sealant cures to a semi-textured gray finish that naturally blends with the surface of concrete, and provides a durable, weather resistant seal that can accommodate for minor concrete settlement and movement.

USES

- Driveways
- Sidewalks
- Patios
- Steps
- Garage / Basement Floors
- Concrete Decks / Slabs

CHARACTERISTICS / ADVANTAGES

- Packaged in an "Easy Squeeze" bottle
 - No special tools or mixing required
- Just shake, pour, and let cure!
- Fiber Reinforced - forms strong, durable bond after cure
- Repairs narrow cracks up to 1/2" wide & 1/4" deep
- Resists cracking, shrinking, & water penetration
- Weather-resistant seal
- Natural concrete finish
- Quick set time (light foot traffic in under 1 hr)
- Super adhesion to cementitious building materials
- Interior/exterior applications

PRODUCT INFORMATION

Packaging	32 fl. oz bottle, 6/case
Color	Gray
Shelf Life	12 months in original, unopened container
Storage Conditions	Store product in original container at 40°F(4°C) to 80°F(26°C) and protect from freezing.
pH-Value	8 to 9
Viscosity	30,000 cps

TECHNICAL INFORMATION

Shore Hardness	85	ASTM D2240
----------------	----	------------

Tensile Strength	8 lbs.	
Elongation at Break	50%	(ASTM D-412)
Tensile Adhesion Strength	Dry Application Adhesion Strength Wet Application Adhesion Strength	16 lbs. 5.5 lbs.
Service Temperature	-30°F to 150°F (-34°C to 65°C)	
APPLICATION INFORMATION		
Coverage	38 linear feet @ 1/2" wide x 1/4" deep	
Ambient Air Temperature	45°F to 100°F (7°C to 37°C)	
Cure Time	Full Cure: 24 hours Rain Ready Time: 24 hours	
Tack Free Time	50 minutes	

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

- Apply when temperatures are above 45°F (7°C)
- **DO NOT APPLY** if rain is expected within 24 hours of application.
- **DO NOT APPLY** in cracks wider than 1/2" (12 mm).
- **DO NOT APPLY** in dynamically moving cracks.
- Ensure the application surface is clean and dry.
- **DO NOT APPLY** to concrete that has cured for less than 7 days.
- Store product in original container at 40°F(4°C) to 80°F(26°C) and protect from freezing.
- Full cure of the product is dependent on temperature, humidity, and depth of repair. Cooler temperatures, higher humidity, and greater application depth of repair will delay curing process.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Remove all loose dirt and debris, oil, greese, and other foreign materials that may interfere with adhesion and/or performance. Make sure the application area is completely clean, dry, and structurally sound.

APPLICATION

For cracks deeper than 1/4" (6 mm), use backer rod to fill the crack up to 1/4" (6 mm) below the surface.

Shake the bottle thoroughly before each use to ensure a consistent mixture. Remove the cap and cut the nozzle tip to 1/4" (6 mm) opening for narrower applications and 3/8" (9 mm) opening for wider applications.

Squeeze the Sikacryl® Pourable Crack Repair Sealant directly into the crack, filling the crack up to or just above the surface. Smooth or tool the surface as needed for a uniform, level finish.

Protect newly repaired surfaces from heavy traffic and rain for 24 hours after application.

CLEANING OF TOOLS

Clean up excess wet material with a damp rag or sponge. Remove uncured material from skin and tools with soap and water immediately after use. Dried material must be mechanically removed.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 201-933-8300.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikacryl® Pourable Crack Repair Sealant
February 2026, Version 01.01
0218403000247289