Sikafloor-100 HD Pronto Formerly MTop SRS 100HD



Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

SECTION 1. IDENTIFICATION

Product name : Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Product code : 00000000059102317

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Curing chemical

Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Organic peroxides : Type D

Eye irritation : Category 2A

Skin sensitization : Category 1

Reproductive toxicity : Category 1B

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 3

Combustible dust : Combustible Dust (1)

GHS label elements

Hazard pictograms :





Signal Word : Danger





Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Hazard Statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H360D May damage the unborn child.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects. May form combustible dust concentrations in air.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ combustible materials.

P234 Keep only in original container.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

P337 + P313 If eye irritation persists: Get medical advice/ attention

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to tempera-

tures exceeding 40 °C/ 104 °F.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Sikafloor-100 HD Pronto Formerly MTop SRS 100HD



Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Chemical nature : Organic Peroxides, Solid

Components

Chemical name	CAS-No.	Concentration (% w/w)
dicyclohexyl phthalate	84-61-7	>= 50 - < 70
dibenzoyl peroxide	94-36-0	>= 50 - < 70

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : After inhalation of dust.

Keep patient calm, remove to fresh air, seek medical atten-

tion.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

Keep eye wide open while rinsing. Remove contact lenses, if present.

Seek medical advice.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention. Do NOT induce vomiting.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye irritation. May damage the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod: :

ucts

harmful vapours nitrogen oxides fumes/smoke





Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

> carbon black carbon oxides

Further information For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for fire-fighters

Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Remove all sources of ignition.

Contain contaminated water/firefighting water. **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for

disposal according to local regulations (see section 13).

Avoid dust formation.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Keep away from sources of ignition - No smoking. Dust can form an explosive mixture with air.

Avoid formation of respirable particles. Advice on safe handling

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Sikafloor-100 HD Pronto Formerly MTop SRS 100HD



Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Conditions for safe storage : Store in cool place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep container tightly closed and dry; store in a cool place.

Materials to avoid : Keep away from reducing agents (e.g. amines), acids, alkalis,

heavy metal compounds (e.g. accelerators, driers, metal

soaps).

Segregate from combustible materials.

Recommended storage tem-

perature

< 104 °F / < 40 °C

Further information on stor-

age stability

Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
111 1 1 1	04.00.0			A C C II ITI \ /
dibenzoyl peroxide	94-36-0	TWA value	5 mg/m3	ACGIHTLV
		REL value	5 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR
				1910.1000
				(Table Z-1)
		TWA value	5 mg/m3	29 CFR
				1910.1000
				(Table Z-1-A)
		TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0

Engineering measures : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Sikafloor-100 HD Pronto Formerly MTop SRS 100HD



Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Remarks : Chemical resistant protective gloves Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Avoid inhalation of dusts.

Wearing of closed work clothing is required additionally to the

stated personal protection equipment.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white

Odor : faint, aldehyde-like

Odor Threshold : not determined

pH : insoluble

Melting point : $> 104 \, ^{\circ}\text{F} \, / > 40 \, ^{\circ}\text{C}$

Boiling point : No data available

Flash point : Not applicable

Evaporation rate : The product is a non-volatile solid.

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : Not applicable





Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Relative vapor density : Not applicable

Relative density : 1.23 (68 °F / 20 °C)

Density : 1.23 g/cm3 (68 °F / 20 °C)

Bulk density : 640 kg/m3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : > 716 °F / > 380 °C

Decomposition temperature : $>= 131 \, ^{\circ}\text{F} / >= 55 \, ^{\circ}\text{C}$

Violent decomposition and deflagration takes place above the

indicated temperature or under local heating.

Risk of exothermic self-accelerating decomposition above the

indicated temperature.

Self-Accelerating decomposi-

tion temperature (SADT)

131 °F / 55 °C

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Self-heating substances : No data available

Sublimation point : No data available

Molecular weight : No data available

Peroxide content : 49 - 51 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

Risk of hazardous polymerization under certain conditions

(e.g. elevated temperatures, low inhibitor and oxygen concen-

tration).

The product is stable if stored and handled as pre-



Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

scribed/indicated.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids and bases

Iron Copper

Reducing agents Heavy metals

Rust

Combustible material

Hazardous decomposition

products

Benzoic acid Benzene Carbon oxides Biphenyls nitrogen oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Sikafloor-100 HD Pronto Formerly MTop SRS 100HD



Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

dibenzoyl peroxide:

M-Factor (Acute aquatic tox- :

icity)

10

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.



Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not permitted for transport

IATA-DGR

UN/ID No. : UN 3106

Proper shipping name : ORGANIC PEROXIDE TYPE D, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo

aircraft)

Packing instruction (passen- : 570

ger aircraft)

IMDG-Code

UN number : UN 3106

Proper shipping name : ORGANIC PEROXIDE TYPE D, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3106

Proper shipping name : ORGANIC PEROXIDE TYPE D, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 145 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.





BUILDING TRUST

Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

dibenzoyl perox- 94-36-0 >= 50 - < 70 %

ide

US State Regulations

Pennsylvania Right To Know

dicyclohexyl phthalate 84-61-7 dibenzoyl peroxide 94-36-0

New Jersey Right To Know

dibenzoyl peroxide 94-36-0

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Flammability Health 2 2 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)



Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;



Sikafloor-100 HD Pronto Formerly MTop SRS 100HD

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/17/2021 000000260462 Date of first issue: 05/17/2021

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/17/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN