

PRODUCT DATA SHEET

Sarnatherm® Roof Board A-III

Sarnatherm Roof Board A-III is a high-density polyisocyanurate roof board

PRODUCT DESCRIPTION

Sarnatherm® Roof Board A-III is a lightweight, high-density polyisocyanurate roof board with coated glass facers. Sarnatherm® Roof Board A-III is suitable for use in new construction and recover roof applications with Sarnafil® or Sikaplan® roof membranes. The coated glass facers provide strong, smooth surfaces suitable for mechanically attached or adhered applications.

USES

Used as a lightweight roof board in conventional roof assemblies

AREAS OF APPLICATION

- New Roofs
- Recover Roofs
- Mechanically Attached Systems
- Adhered Systems

CHARACTERISTICS / ADVANTAGES

- Lightweight for easy hoisting, staging and maneuvering
- High impact and flexural strength
- Easy scoring, cutting and snapping
- Improved coverage rates in adhered systems
- Manufactured using CFC-, HCFC- and HFC-free foam blowing technology
- Virtually no Global Warming Potential (GWP)
- Zero Ozone Depletion Potential (ODP)
- Recognized as resistant or highly resistant to mold growth

APPROVALS / STANDARDS

- ASTM C1289, Type II, Class 4, Grade 1
- FM 4450 / 4470
- FM 4473 hail rating SH-1
- UL Classified 790
- UL Certified for Canada

PRODUCT INFORMATION

Chemical Base	Polyisocyanurate foam core with coated glass facers
Recycled Content	7.4% Pre-consumer
Packaging	<ul style="list-style-type: none">▪ 4 ft x 4 ft (1.2 m x 1.2 m), 8 lbs (3.6 kg)▪ 4 ft x 8 ft (1.2 m x 2.4 m), 16 lbs (7.2 kg)▪ 0.5" (12.7 mm) thickness, 42 boards per pallet
Color	Off-white core with off white/light tan facers
Shelf Life	N/A
Storage Conditions	Factory-applied packaging is intended only for protection during transit. When stored outdoors or on the job site, the insulation should be stacked on pallets at least 4" (102 mm) above ground level and completely covered with a weatherproof covering such as a tarpaulin. The temporary factory-applied packaging should be slit or removed to prevent accumulation of condensation. Refer to PIMA Technical Bulletin #109: Storage and Handling Recommendations for Polyiso Roof Insulation.

TECHNICAL INFORMATION

Compressive Strength	80 psi (551 kPa) minimum	(ASTM D-1621)
Flexural Strength	> 2000 psf (> 95 kPa)	(ASTM D-1623)
Dimensional Stability	< 0.5%	(ASTM D-2126)
Reaction to Fire	Flame Spread ¹ : 40 – 60* Smoke Development ¹ : 50 – 170* <small>*Numerical ratings are not intended to reflect performance under actual fire conditions. Flame spread index of ≤75 and smoke development ≤450 meet code requirements for foam plastic roof insulation. Codes exempt foam plastic insulation when used in FM 4450 or UL 1256.</small>	(ASTM E-84)
Thermal resistance	2.5	(ASTM C-518)
Permeability to Water Vapor	1.5 perm (85 ng/(pa s m))	(ASTM E-96)
Water Absorption	<3%	(ASTM C-209)
Microbiological Resistance	Resistant	(UL 2824)
Service Temperature	-100 – 250°F (-73 – 121°C)	

APPLICATION INSTRUCTIONS

Sarnatherm® Roof Board A-III is installed by a Sika Authorized Applicator. Sarnatherm® Roof Board A-III may be installed by mechanical attachment to the roof deck with approved fasteners and insulation plates or by attachment with Sarnacol board adhesive depending on project requirements and specifications. Roof boards that have become wet or damaged should be removed and replaced with solid, dry roof boards. Contact Sika Corporation – Roofing Technical Department regarding alternative methods of attachment.

MAINTENANCE

Standard maintenance of Sika Sarnafil systems should include inspections of flashings, drains, and terminations sealants at least twice a year and after each storm.

AVAILABILITY/WARRANTY

AVAILABILITY

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

WARRANTY

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide

a warranty to the Building Owner via the Sika Authorized Applicator.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Sarnafil

100 Dan Road
Canton, MA 02021
Phone: +1 800-451-2504
Fax: +1 781-828-5365
usa.sika.com/sarnafil
webmaster.sarnafil@us.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

Sarnatherm® Roof Board A-III
August 2020, Version 04.01
020935013000005012

SarnathermRoofBoardA-III-en-US-(08-2020)-4-1.pdf

