



## PRODUCT DATA SHEET

# Sikafloor®-100 HD Pronto

(formerly MasterTop® SRS 100HD)

### METHYL METHACRYLATE INITIATOR

#### PRODUCT DESCRIPTION

Sikafloor®-100 HD Pronto is a white, free-flowing, granular powder consisting of dibenzoyl peroxide, phthalate ester plasticizer. This peroxide is used as a cure initiator for Sikafloor® Pronto acrylic resins in both elevated temperature cure and ambient temperature cure processes. Sikafloor®-100 HD Pronto is easy to disperse and dissolves fast in Sikafloor® Pronto acrylic resins.

#### USES

- Activates Sikafloor® Pronto MMA resin when properly dispersed in mixing container prior to transport to the project area
- Initiates curing of residual material in empty pails and drums prior to disposal

#### CHARACTERISTICS / ADVANTAGES

- Able to adjust quantity (oz) used per mix based on floor, air, and resin temperatures

#### PRODUCT INFORMATION

<b>Packaging</b>	50 lb box 0.5 gallon bottle
<b>Shelf Life</b>	12 months for the 50 lb box 24 months for the 0.5 gallon bottle
<b>Storage Conditions</b>	Store in original container away from flammables and all sources of heat, sparks, or flames; out of direct sunlight; and away from cobalt naphthenate, anilines, other promoters, accelerators, oxidizing or reducing agents and strong acids or bases.
<b>Appearance / Color</b>	White, free-flowing powder

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTEL at +1(800) 255-3924 or if outside the US or Canada, +1(813) 248-0585.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



Product Data Sheet  
Sikafloor®-100 HD Pronto  
May 2024, Version 01.01  
020816220010000032

Sikafloor-100HDPronto-en-US-(05-2024)-1-1.pdf

