

PRODUCT DATA SHEET

SikaWall®-9000 SRT Mesh

Glass fiber mesh for use with stucco.

PRODUCT DESCRIPTION

A woven fiberglass mesh with high mechanical strength and dimensional stability.

USES

For Sika Facades stucco and stucco resurfacing systems and conventional stucco for improved crack resistance when used with Sika Facades SRT Mesh

Note: For stucco systems only. Not for use with Sika Facades EIFS or Cement Board Stucco (CBS) systems.

CHARACTERISTICS / ADVANTAGES

- Alkali resistant, compatible with all Sika Facades base coats; high tensile strength and flexibility for long-term durability.
- Increased flexural & tensile strength at ultimate load compared to stucco without SikaWall SRT Mesh/ base coat.

PRODUCT INFORMATION

| | |
|---------------------------|---|
| Packaging | <ul style="list-style-type: none"> ▪ Sold by the pallet. 33 rolls per pallet. ▪ Roll Size: 39.4" x 164' (100 cm x 50 m) |
| Shelf Life | Two (2) years, when properly stored in original container. |
| Storage Conditions | Store products in a cool, dry place protected from exposure to moisture. |
| Weight | 4.3 oz/yd ² (145 g/m ²) |
| Coverage | 538 ft ² (50 m ²) per roll. |

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

SURFACE PREPARATION

- Substrates must be clean, dry, sound and free of loose material, paint, efflorescence, contaminants and other coatings.

- Stucco: allow to cure a minimum of 6 days prior to application of Sika Facades base coat or SikaWall-525 Stucco Surface Leveler and SikaWall SRT Mesh.

APPLICATION

- Apply mixed Sika Facades base coat to the entire surface of the stucco with a stainless steel trowel. Immediately place SikaWall SRT Mesh against the wet base coat and embed mesh into the base coat by troweling from the center to the edges.
- Lap SikaWall SRT Mesh a minimum of 2 ½" (64mm) at edges. Ensure mesh is continuous, void of wrinkles and

embedded in base coat so that no mesh or pattern is visible.

- If required, apply a second layer of base coat to achieve a total nominal base coat / SikaWall SRT Mesh thickness of 1/16" (1.6 mm).
- Allow base coat with embedded mesh to dry hard (normally 8 to 10 hours) prior to finish coat application.

Consult Sika Facades Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications.

ENVIRONMENTAL, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

SikaWall®-9000 SRT Mesh
November 2024, Version 01.01
021830901000000068

SikaWall-9000SRTMesh-en-US-(11-2024)-1-1.pdf

