		WARM PIPE-METAL SL	eeve req'd. @ ^	50°F OR GREATER	
8" INCHES MIN.		SIKAFLEX®	SEALANT (SEE N HOOD W/ STAIN —METAL SLEEVE —SIKALASTIC FL —SIKALASTIC FL	OTE) ILESS STEEL HOSE CLAI ASHING MEMBRANE, FING ASHING MEMBRANE, TUR	GER CUT WRAP TLENECK MBRANE PRIMER
METAL SLEEVE FASTENED 4 IN. O.C. STAGGERED USING 1-INCH GALVANIZED ANNULAR RING NAILS INTO WOOD NAILER, OR FASTENED 6 IN. O.C. STAGGERED USING ROOFING SCREWS OR MASHROOM-HEAD ANCHORS APPROPRIATE FOR SUBSTRATE. NOTES: 1) SEALANT IS A MAINTENANCE ITEM NOT COVERED UNDER WARRANTY. 2) REMOVE ANY EXISTING ROOFING AND METAL EDGE MATERIALS DOWN TO EXISTING WOOD BLOCKING. ADD ADDITIONAL WOOD NAILER AS REQUIRED TO MATCH HEIGHT OF EXISTING ROOF.					
		JOB NAME:			
Jika ®		HOT STACK FLASHING			
	1-800-933-SIKA (7452) www.sikausa.com	SCALE: DATE: DATE:	10/13	FILE NO.:	DRW. NO.: DS.4.03
ENGINEERING AND ARCHITECTURAL PRACTI CONSULTANT AND/OR ENGINEER OR DESIGI SPECIFICATIONS, DETAILS AND SHOP DRAW MATERIALS, THE MEANS AND METHODS USE RESPONSIBILITY OF THE CONTRACTOR. THI AVAILABLE AT WWW.SIKAUSA.COM. SIKA CC	ICES AND SHOULD NOT BE RELIED UP/ N PROFESSIONAL FOR A PARTICULAR NINGS, AND FOR DETERMINING THEIRS ED BY THE CONTRACTOR FOR MATERI/ E CONTRACTOR MUST AL WAYS READ J DRPORATION MAKES NO WARRANTY O NAY DIRECT OR CONSEQUENTIAL DAM	DES GENERIC DETAILS AS A GENERAL GUIDE FC N FOR THAT PURPOSE. SIKA CORPORATION AS ROJECT BEARS THE SOLE RESPONSIBILITY FO JITABILITY FOR A PARTICULAR PROJECT OR AP L STORAGE, SUBSTRATE EVALUATION, SURFAC NO FOLLOW THE WARNINGS AND INSTRUCTION F ANY KIND, EITHER EXPRESS OR IMPLIED, AS T AGES OF ANY KIND ARISING FROM THE USE OF COM.	SUMES NO LIABILITY WIT R THE DESIGN OF THE SY PLICATION. WHILE SIKA F E PREPARATION, AND TH S ON SIKA PRODUCT LAB FO THE CONTENT OF THIS	H RESPECT TO THE DESIGN OF THI STEM, FOR THE PREPARATION AND ROVIDES GENERAL INSTRUCTIONS E INSTALLATION OF BOTH SIKA ANI ELS, TECHNICAL DATA SHEETS, AN GUIDE DETAIL. SIKA SHALL NOT	E SYSTEM. THE ARCHITECT,) APPROVAL OF THE PROJECT 5 FOR THE INSTALLATION OF ITS) NON-SIKA MATERIALS ARE THE D MATERIAL SAFETY DATA SHEETS BE RESPONSIBLE UNDER ANY