



Sika® Level-525 Rapid

FAST SETTING, SELF-LEVELING UNDERLAYMENT

- Job site with fast floor-covering installation requirement
- Exceptional fluid leveler designed for thin applications
- Ideal for heavy traffic loads
- Install most floor covering in 90 minutes

Available in
55 lb. Bag



BUILDING TRUST



Sika® Level-525 Rapid

FAST SETTING, SELF-LEVELING UNDERLAYMENT

WHERE TO USE

- Interior use only
- Levels, flattens and smooths substrates before application of resilient floor
- Suitable on concrete, ceramic and quarry tile, OSB/Plywood, and well bonded LVT
- Residential, commercial and industrial applications with heavy traffic

FEATURES AND BENEFITS

- Pumpable self-leveling
- Install most floor covering in 90 minutes
- Feather edge applications
- High flow and high strengths
- Acceptable for castor wheel and forklift traffic
- Compatible with subfloor heating systems
- Suitable for use with the Sika® Secure System

NOTE: Always refer to current PDS and SDS for detailed performance specifications prior to use.

TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)

Color	Concrete Gray
Application Thickness	1/16" up to 1/2" (1.6 mm up to 13 mm) Can be extended with aggregate to 1" (26 mm)
Density (ASTM C185)	118 lbs/cu.ft.
Working Time	Approx. 25 minutes
Ready for Foot Traffic	1 - 1.5 hours
Flexural Strength (ASTM C348)	1,600 psi (11 MPa) at 28 days
Compressive Strength (ASTM C109)	7,600 psi (52.4 MPa) at 28 days
VOC (EPA METHODE 24)	0 g/l

Sika® Classification Table

Strength					
Flow					
Depth					
Speed					



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikasecure.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

