

Revision Date 12/04/2019

# **SECTION 1. IDENTIFICATION**

Product name : SikaBiresin® AP861-1 Part B

Company name : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

# **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1B

Serious eye damage : Category 1

Skin sensitization : Category 1

Specific target organ toxicity

- repeated exposure (Oral)

Category 2

**GHS** label elements

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or re-

peated exposure if swallowed.



Revision Date 12/04/2019 Print Date 12/04/2019

**Precautionary Statements** 

#### Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

## Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

# Mixtures

# Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
benzyl alcohol	100-51-6	Acute Tox. 4; H302 Acute Tox. 4; H332	>= 20 - < 30



Revision Date 12/04/2019 Print Date 12/04/2019

		Eye Irrit. 2A; H319	
Methyleneoxide, polymer with ben-	135108-88-2	Acute Tox. 4; H302	>= 20 - < 30
zenamine, hydrogenated		Skin Corr. 1C; H314	
		Eye Dam. 1; H318	
		Skin Sens. 1; H317	
		STOT RE 2; H373	
Fatty acids, tall-oil, reaction products	68953-36-6	Skin Irrit. 2; H315	>= 10 - < 20
with tetraethylenepentamine		Eye Irrit. 2A; H319	
		Skin Sens. 1; H317	
		STOT SE 3; H335	
Fatty acids, C18-unsatd., dimers,	68082-29-1	Eye Dam. 1; H318	>= 5 - < 10
oligomeric reaction products with			
tall-oil fatty acids and triethylenetet-			
ramine			
3,6,9-	112-57-2	Acute Tox. 4; H302	>= 1 - < 5
triazaundecamethylenediamine		Acute Tox. 4; H312	
		Skin Corr. 1B; H314	
		Eye Dam. 1; H318	
		Skin Sens. 1; H317	
4,4'-methylenebis(cyclohexylamine)	1761-71-3	Acute Tox. 4; H302	>= 1 - < 5
		Skin Corr. 1B; H314	
		Eye Dam. 1; H318	
		Skin Sens. 1B; H317	
		STOT RE 2; H373	
triethylenetetramine	112-24-3	Acute Tox. 4; H302	>= 1 - < 5
-		Acute Tox. 4; H312	
		Skin Corr. 1B; H314	
		Eye Dam. 1; H318	
		Skin Sens. 1; H317	

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.



Revision Date 12/04/2019 Print Date 12/04/2019

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

Health injuries may be delayed.

corrosive effects sensitizing effects

Gastrointestinal discomfort

Allergic reactions

Dermatitis

Harmful if swallowed.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated

exposure if swallowed. Causes severe burns.

Notes to physician Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.



Revision Date 12/04/2019 Print Date 12/04/2019

#### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Store in original container.

Keep container tightly closed in a dry and well-ventilated

Observe label precautions.

Store in accordance with local regulations.

Materials to avoid **Explosives** 

> Oxidizing agents Poisonous gases Dangerous when wet Flammable solids Organic peroxides Poisonous liquids

Spontaneously Combustible Substances

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** Use of adequate ventilation should be sufficient to control

> worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.



Revision Date 12/04/2019 Print Date 12/04/2019

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : brown

Odor : amine-like

Odor Threshold : No data available

pH : Not applicable

Melting point/range : 387 °F / 197 °C

Boiling point/boiling range : No data available

Flash point : 338 °F / 170 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available



Revision Date 12/04/2019

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 0.07 hpa

Relative vapor density : No data available

Density : ca. 0.9 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : 815 °F / 435 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

9 g/l

A+B Combined

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

Carbon dioxide (CO2)

Carbon monoxide



Revision Date 12/04/2019

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Harmful if swallowed.

#### Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

# 3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,716.2 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1,260 mg/kg

#### 4,4'-methylenebis(cyclohexylamine):

Acute oral toxicity : LD50 Oral (Rat): 380 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 2,110 mg/kg

# triethylenetetramine:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

#### Skin corrosion/irritation

Causes severe burns.

#### Serious eye damage/eye irritation

Causes serious eye damage.

# Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

# Respiratory sensitization

Not classified based on available information.

#### Components:

# 4,4'-methylenebis(cyclohexylamine):

Test Type : Buehler Test

Assessment : The product is a skin sensitizer, sub-category 1B. Result : The product is a skin sensitizer, sub-category 1B.



Revision Date 12/04/2019

Print Date 12/04/2019

## Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

**IARC** Not applicable

**OSHA** Not applicable

**NTP** Not applicable

#### Reproductive toxicity

Not classified based on available information.

# STOT-single exposure

Not classified based on available information.

# STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

### **Components:**

#### benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

#### 4,4'-methylenebis(cyclohexylamine):

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

plants

EC50 (Daphnia magna (Water flea)): 6.84 mg/l

EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

Exposure time: 48 h

# triethylenetetramine:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

100 mg/l

Exposure time: 72 h



Revision Date 12/04/2019

Persistence and degradability

No data available

**Bioaccumulative potential** 

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION** 

**International Regulations** 

**IATA-DGR** 

UN/ID No. : UN 2735

Proper shipping name : Amines, liquid, corrosive, n.o.s.

(Methyleneoxide, polymer with benzenamine, hydrogenated)

Class : 8 Packing group : III

Labels : Corrosive

Packing instruction (cargo

aircraft)

856

Packing instruction (passen: :

852

ger aircraft)

**IMDG-Code** 

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.

(Methyleneoxide, polymer with benzenamine, hydrogenated)

Class : 8
Packing group : III
Labels : 8



Revision Date 12/04/2019

EmS Code : F-A, S-B Marine pollutant : no

**Domestic regulation** 

**49 CFR** 

UN/ID/NA number : UN 2735

Proper shipping name : Amines, liquid, corrosive, n.o.s.

(Methyleneoxide, polymer with benzenamine, hydrogenated)

Class : 8 Packing group : III

Labels : CORROSIVE

ERG Code : 153 Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

# **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop 65 WARNING: Cancer – www.P65Warnings.ca.gov



Revision Date 12/04/2019

Print Date 12/04/2019

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

US WEEL / TWA : 8-hr TWA

#### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 12/04/2019

100000027713

US / Z8