

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

---

### SECTION 1. IDENTIFICATION

Product name : Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA

Product code : 000000000058408257

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Floor coating

Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Inhalation) : Category 4

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure

#### GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black silhouette of a person with a starburst on their chest, representing Health Hazard. The second is a red diamond with a black exclamation mark, representing a general hazard.

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

Precautionary Statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.  
P285 In case of inadequate ventilation wear respiratory protection.

**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P363 Wash contaminated clothing before reuse.

**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**  
None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : isocyanate

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Hexane, 1,6-diisocyanato-, homopolymer	28182-81-2	>= 90 - <= 100
1,6-hexamethylene diisocyanate	822-06-0	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

---

- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Hazardous combustion products : fumes/smoke  
harmful vapours  
Carbon oxides  
nitrogen oxides  
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water.  
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wear eye/face protection.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
-

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Pick up with suitable appliance and dispose of.  
Dispose of absorbed material in accordance with regulations.  
Do not rinse off with water or aqueous cleaning agents.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Sealed containers should be protected against heat as this results in pressure build-up.  
Risk of explosion if heated under confinement.
- Advice on safe handling : Avoid inhalation of dusts/mists/vapours.  
Avoid skin contact.  
Ensure adequate ventilation.  
No special measures necessary provided product is used correctly.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Keep container tightly closed.  
Protect from direct sunlight.
- Recommended storage temperature : 39 - 90 °F / 4 - 32 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,6-hexamethylene diisocyanate	822-06-0	TWA value	0.005 ppm	ACGIHTLV
		Ceil_Time	0.020 ppm 0.140 mg/m3	NIOSH
		REL value	0.005 ppm 0.035 mg/m3	NIOSH
		TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.035 mg/m3	NIOSH REL
		C	0.02 ppm 0.14 mg/m3	NIOSH REL

- Engineering measures : Ensure adequate ventilation, especially in confined areas.

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

---

### Personal protective equipment

- Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.  
Wear a NIOSH-certified (or equivalent) respirator as necessary.
- Hand protection
- Remarks : Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene. Manufacturer's directions for use should be observed because of great diversity of types.
- Eye protection : Safety glasses with side-shields.  
Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.
- Skin and body protection : Body protection must be chosen based on level of activity and exposure.
- Protective measures : Do not inhale dust/fumes/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.
- Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).  
Wash soiled clothing immediately.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : clear, colorless
- Odor : odorless
- Odor Threshold : Not relevant
- pH : No data available

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0	Revision Date: 05/26/2021	SDS Number: 960000010885	Date of last issue: - Date of first issue: 05/26/2021
----------------	------------------------------	-----------------------------	--

---

Melting point	:	No data available
Boiling point/boiling range	:	> 255 °F / > 124 °C
Flash point	:	334 °F / 168 °C
Evaporation rate	:	No data available
Flammability (liquids)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.050 mmHg
Relative vapor density	:	Heavier than air.
Relative density	:	1.16
Density	:	9.63 lb/USg
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available
Molecular weight	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0	Revision Date: 05/26/2021	SDS Number: 960000010885	Date of last issue: - Date of first issue: 05/26/2021
----------------	------------------------------	-----------------------------	--

---

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Oxidizing agents Strong bases Water Amines Alcohols Copper
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if inhaled.

#### Product:

Acute inhalation toxicity	:	Acute toxicity estimate: 11.02 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
---------------------------	---	---

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

##### Skin sensitization

May cause an allergic skin reaction.

##### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

---

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

### Further information

#### Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : No data available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available.  
Discharge into the environment must be avoided.

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---



# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.  
Do not contaminate ponds, waterways or ditches with chemical or used container.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
- 

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

---

### SECTION 15. REGULATORY INFORMATION

#### US State Regulations

##### Pennsylvania Right To Know

Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2

##### New Jersey Right To Know

Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2

#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA




Version 1.0      Revision Date: 05/26/2021      SDS Number: 960000010885      Date of last issue: -  
Date of first issue: 05/26/2021


### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / Ceil\_Time : Ceiling Limit Value and Time Period (if specified):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / C : Ceiling value not be exceeded at any time.

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -

# SAFETY DATA SHEET

## Sikafloor TC 421 UHW Part A Formerly MTop TC 421 UHW PTA



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/26/2021	960000010885	Date of first issue: 05/26/2021

---

Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/26/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN