

Sikalastic® 320 NS/SL/SG System Guidelines

March 2021

BUILDING TRUST



Application	System	Option	Sikalastic® 320 Build	Primer	Protection Course	Drainage Mat
Foundation Wall ¹	5 years		60 mils		GreenGuard® PB4	
	10 years		90 mils			Sika® Drainage Mat 420
	20 years		90 mils		GreenGuard® PB4	Sika® Drainage Mat 420/GRS
Split Slab, Pavers ²	5 years	1	60 mils		GreenGuard® PB4	
	5 years	2	60 mils			Sika® Drainage Mat 1000/720
	10 years		90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 1000/720
	20 years		120 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 1000
Plaza Decks ³	5 years		60 mils			Sika® Drainage Mat 420/GRS
	10 years		90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS
	20 years		120 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS
Planter ⁴			Floor/Wall			
	5 years		60/60 mils			Sika® Drainage Mat 420/GRS
	10 years		90/90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS
	20 years		120/90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS

1. Some Building Codes may require Drainage Mats depending on the height of the foundation
2. Mortar beds supporting pavers must be at least 2 inches thick
3. For Plaza Decks with vegetation/overburden please contact Sika Technical Service
4. Use root barrier where applicable

Note: Consult Sika for prior approval for all warranties

Sika Corporation
www.usa.sika.com
 201 Polito Avenue
 Lyndhurst, NJ 07071
 Phone: 201-933-8800