

PRODUCT DATA SHEET

Sarnadisc RhinoBond

Sarnadisc Rhinobond is a polymer coated plate

PRODUCT DESCRIPTION

Sarnadisc RhinoBond is a specially designed polymer coated plate used with Sarnafasteners or Sikaplan Fasteners to attach Sarnatherm® insulation, Sarnatherm® roof boards, gypsum roof boards, or other Sika approved boards directly to the roof deck or structural purlins prior to the installation of Sarnafil® S 327 membrane or Sikaplan® Fastened membrane. The membrane is field welded to the Sarnadisc RhinoBond by induction welding.

USES

Used with Sarnafasteners or Sikaplan fasteners when attaching Sarnafil® S 327 or Sikaplan® Fastened membrane direct to the roof deck.

Ares of Application

- New Roof Applications
- Reroof Applications
- Recover Applications

CHARACTERISTICS / ADVANTAGES

- Recessed center to provide protection to the membrane underside from abrasion by the fastener head
- Zero penetrations of the roof cover.

APPROVALS / STANDARDS

- Factory Mutual 4470
- ICC Code Compliance ESR 1157
- Miami-Dade County

PRODUCT INFORMATION

Chemical Base	Metal plate with a polymer coating
Packaging	500 per pail, 54 lb (24 kg) per pail
Appearance / Color	Black Topside
Shelf Life	N/A
Storage Conditions	N/A
Dimensions	Diameter: 3" (75 mm)

Product Data Sheet

Sarnadisc RhinoBond September 2019, Version 03.01 020945012150005000

APPLICATION INSTRUCTIONS

APPLICATION

Sarnadisc® RhinoBond is positioned on the surface of the insulation board. A Sarnafastener® is set through the center of the disc and set into the roof deck or purlin. The Sarnadisc® RhinoBond holds the insulation in place.

MAINTENANCE

Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

AVAILABILITY/WARRANTY

Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

Warrantv

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized **Applicator**

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: +1-800-933-7452 Fax: +1-201-933-6225 usa.sika.com

Sika Sarnafil

100 Dan Road Canton. MA 02021 Phone: +1 800-451-2504 Fax: +1 781-828-5365 usa.sika.com/sarnafil webmaster.sarnafil@us.sika.com

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY

FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/group/SikaCorp/termsandconditions.html or by calling 1-800-933-7452.

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5 Fracc. Industrial Balvanera Corregidora, Queretaro C.P. 76920

Phone: 52 442 2385800 Fax: 52 442 2250537



Sarnadisc RhinoBond September 2019, Version 03.01 020945012150005000



SarnadiscRhinoBond-en-US-(09-2019)-3-1.pdf