Revision Dat

1. Identifica

use

sion Date 03/27/2018			Print Date 03/2
dentification			
Product name	:	BMI Natural Base Marble	
Supplier	:	Sika Corporation	
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com	
Telephone	:	(201) 933-8800	
Telefax	:	(201) 804-1076	
E-mail address	:	ehs@sika-corp.com	
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887	
Recommended use of the chemical and restrictions on	:	For further information, refer to product data shee	ət.

2. Hazards identification

GHS Classification

Skin corrosion, Category 1C Serious eye damage, Category 1 Skin sensitization, Category 1 Carcinogenicity, Category 1A (Inhalation) Specific target organ systemic toxicity single exposure, Category 3, Respiratory system

Specific target organ systemic toxicity repeated exposure, Category 1, Lungs

H314: Causes severe skin burns and eve damage. H318: Causes serious eye damage. H317: May cause an allergic skin reaction. H350i: May cause cancer by inhalation. H335: May cause respiratory irritation.

H372: Causes damage to organs through prolonged or repeated exposure.

GHS label elements

Hazard pictograms



Signal Word

Hazard Statements

: H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350i May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.



Revision Date 03/27/2018



	Precautionary Statements	 Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P281 Use personal protective equipment as required. Response: P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P310 Immediately call a POISON CENTER/doctor. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before reuse. Storage: P405 Store locked up. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.
--	--------------------------	---

See Section 11 for more detailed information on health effects and symptoms. There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

3. Composition/information on ingredients

Hazardous ingredients

Calcium hydroxide	1305-62-0	>= 10 - < 20 %
Portland cement	65997-15-1	>= 10 - < 20 %
Quartz (SiO2)	14808-60-7	>= 1 - < 2 %

4. First aid measures

If inhaled

: Move to fresh air.

Consult a physician after significant exposure.

Revision Date 03/27/2018



In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Prolonged exposure can cause silicosis.
		Health injuries may be delayed. corrosive effects irritant effects sensitizing effects carcinogenic effects
		Cough Respiratory disorder Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms.
		May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure. Causes severe burns.
Protection of first-aiders	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
Notes to physician	:	Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Revision Date 03/27/2018



Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.
6. Accidental release measures	

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling	 Avoid formation of respirable particles. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	 Prevent unauthorized access. Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Materials to avoid	: No data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
-----------	---------	----------	-------	--

Revision Date 03/27/2018



on Date 00/21/2010				T fint Date 00/
Calcium hydroxide	1305-62-0	ACGIH	TWA	5 mg/m3
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA P0	TWA	5 mg/m3
		NIOSH REL	TWA	5 mg/m3
		CAL PEL	PEL	5 mg/m3
Portland cement	65997-15-1	ACGIH	TWA	1 mg/m3 Respirable fraction
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA Z-3	TWA	50 Million particles per cubic foot Dust
		OSHA P0	TWA	10 mg/m3 Total dust
		OSHA P0	TWA	5 mg/m3 respirable dust fraction
Quartz (SiO2)	14808-60-7	OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m3 Respirable dust

Revision Date 03/27/2018



*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**<u>Basis</u>

ACGIH. Threshold Limit Values (TLV) OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values) OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant OSHA P2. Permissible Exposure Limits (PEL), Table Z-2 OSHA Z3. Table Z-3, Mineral Dust

Engineering measures	:	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
		The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling. Avoid breathing dust.

Revision Date 03/27/2018



Appearance	:	granularpowder
Color	:	tan off-white
Odor	:	slight
Odor Threshold	:	No data available
Flash point	:	Note: Not applicable
Ignition temperature	:	No data available
Decomposition temperature	:	No data available
Lower explosion limit (Vol%)	:	No data available
Upper explosion limit (Vol%)	:	No data available
Flammability (solid, gas)	:	No data available
Oxidizing properties	:	No data available
рН	:	Note: Not applicable
Melting point/range /	:	No data available
Freezing point Boiling point/boiling range	:	No data available
Vapor pressure	:	No data available
Density	:	ca.2.3 g/cm3 at 68 °F (20 °C)
Water solubility	:	Note: insoluble
Partition coefficient: n-	:	No data available
octanol/water Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Note: Not applicable
Relative vapor density	:	No data available
Evaporation rate	:	No data available
Burning rate	:	No data available
Volatile organic compounds (VOC) content	:	Not applicable

10. Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.

Revision Date 03/27/2018



Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available

11. Toxicological information

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction. Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Prolonged exposure can cause silicosis.

Aspiration toxicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation. IARC Group 1: Carcinogenic to humans

NTP	Quartz (SiO2) Known to be human carcinoge	14808-60-7 en
	Quartz (SiO2)	14808-60-7

12. Ecological information

Other information Do not empty into drains; dispose of this material and its container in a safe way.

Revision Date 03/27/2018



13. Disposal considerations

Disposal methods

Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT Not dangerous goods IATA Not dangerous goods IMDG Not dangerous goods

Special precautions for user No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Chronic Health Hazard
	Skin corrosion or irritation
	Serious eye damage or eye irritation
	Respiratory or skin sensitization
	Carcinogenicity
	Specific target organ toxicity (single or repeated exposure)

Revision Date 03/27/2018



This material does not contain any components with a section 302 EHS TPQ.
This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
any hazardous air pollutants (HAP), as defined by the U.S. Clean I). any chemicals listed under the U.S. Clean Air Act Section 112(r) for (40 CFR 68.130, Subpart F).
MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

16. Other information

* 3	Health •
0	Flammability
ard o	Physical Hazard
otection x	Personal Protection

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER

Print Date 03/27/2018

Revision Date 03/27/2018

ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/27/2018

Material number: 506698