

Sikalastic® 320 NS/SL

SINGLE COMPONENT, BITUMEN MODIFIED WATERPROOFING MEMBRANE

- Available in Self-leveling and Non-sag consistencies
- Application on green or damp concrete
- Low VOC content (<48 g/L)
- Alkali Resistant
- Catalyzed by water
- Can be applied around pool areas
- Solvent Free

Available in

5 gallons









Sikalastic® 320 NS/SL

SINGLE COMPONENT, BITUMEN MODIFIED WATERPROOFING MEMBRANE

APPLICATIONS

- **Planters**
- Plazas
- Between Slabs
- Foundation Walls
- Bridges
- **Shower Pans**
- Tunnels

LITERATURE

- Product Data Sheet
- Safety Data Sheet
- Architectural Details
- Specification Component
- *Always refer to Current Product Data Sheet and SDS for detailed performance specifications prior to use.

BENEFITS

- Available in Self-leveling and Non-sag consistencies
- Low VOC content (<48 g/L)
- Alkali Resistant
- Can be applied around pool areas
- Catalyzed by water
 - Faster cure
 - Applied horizontally up to 120 mils
- Application on green concrete
 - Horizontal: 48 hours after pour or walkable
 - Vertical: 24 hours after forms removed
- Detailed cracks can be coated with Sikalastic® 320 in one hour with:

Sikaflex® 11FC - Existing Concrete Sikaflex® 1a+ - Green Concrete

COVERAGE	DRY FILM THICKNESS	SYSTEM TYPE
50 FT ² /GAL	30 ± MILS DFT	
25 FT ² /GAL	60 ± MILS DFT	5 YEAR SYSTEM
18 FT ² /GAL	90 ± MILS DFT	10 YEAR SYSTEM
13 FT ² /GAL	120 ± MILS DFT	20 YEAR SYSTEM

GOING ON GREEN?

TRY Sikaflex® 1a+ OR Sikaflex® 1c SL WHEN SEALING GREEN CONCRETE.





Note: 1) Advice on specific applications is available from the Technical Service Department of Sika Construction Products Division. 2) See Product Data Sheet and Warranty Guidelines for more information.

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikausa.com

Sika Corporation 201 Polito Avenue

Lyndhurst, NJ 07071 Phone: 201-933-8800 Fax: 201-933-6225







