TEXTURE COL CLEAR



Version **Revision Date:** SDS Number: Date of last issue: -

10/14/2020 000000260215 Date of first issue: 10/14/2020 1.0

SECTION 1. IDENTIFICATION

Product name : TEXTURE COL CLEAR

Product code 000000000050002521

Manufacturer or supplier's details

Company name of supplier Sika MBCC US LLC

Address 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use Product for construction chemicals

Restrictions on use Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Specific target organ toxicity : Category 2 (Kidney)

- repeated exposure

GHS label elements

Hazard pictograms



Signal Word Warning

Hazard Statements H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

Precautionary Statements Prevention:

P260 Do not breathe dust or mist.

Response:

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

No data available.

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--------------------|------------|-----------------------|
| crystalline silica | 14808-60-7 | >= 50 - < 75 |
| Limestone | 1317-65-3 | >= 5 - < 15 |
| ethyleneglycol | 107-21-1 | >= 0.3 - < 3 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry powder

Unsuitable extinguishing : High volume water jet

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

media

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black

carbon oxides

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards.

TEXTURE COL CLEAR



Version **Revision Date:** SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid No applicable information available.

Recommended storage tem: :

perature

32 °F / 0 °C

Further information on stor-

age stability

Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------|-----------|---|--|--------------------------------------|
| ethyleneglycol | 107-21-1 | TWA value (Vapor frac- tion) | 25 ppm | ACGIHTLV |
| | | STEL value (Vapor frac- tion) | 50 ppm | ACGIHTLV |
| | | STEL value (Aerosol, inhalable.) | 10 mg/m3 | ACGIHTLV |
| | | TWA (Vapor) | 25 ppm | ACGIH |
| | | STEL (Va- por) | 50 ppm | ACGIH |
| | | STEL (Inhalable fraction, Aerosol only) | 10 mg/m3 | ACGIH |
| | | С | 50 ppm 125 mg/m3 | OSHA P0 |
| Limestone | 1317-65-3 | REL value (Respirable) | 5 mg/m3 | NIOSH |
| | | REL value (Total) | 10 mg/m3 | NIOSH |
| | | PEL (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA value (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
|--------------------|------------|--|--------------------------------------|------------------------------|
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 | OSHA P0 |
| | | TWA (respir- able dust fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA (Respirable) | 5 mg/m3 (Calcium car- bonate) | NIOSH REL |
| | | TWA (total) | 10 mg/m3 (Calcium car- bonate) | NIOSH REL |
| crystalline silica | 14808-60-7 | TWA value (Respirable fraction) | 0.025 mg/m3 | ACGIHTLV |
| | | REL value (Respirable dust) | 0.05 mg/m3 | NIOSH |
| | | TWA value | 0.05 mg/m3 (Respirable dust) | 29 CFR 1910.1001- 1050 |
| | | OSHA Action level | 0.025 mg/m3 (Respirable dust) | 29 CFR 1910.1001- 1050 |
| | | TWA (Respirable dust) | 0.05 mg/m3 | OSHA Z-1 |
| | | TWA (respirable) | 10 mg/m3 / %SiO2+2 | OSHA Z-3 |
| | | TWA (respirable) | 250 mppcf / %SiO2+5 | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 0.1 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| | | PEL (respir- able) | 0.05 mg/m3 | OSHA CARC |
| | | TWA (Respirable dust) | 0.05 mg/m3 (Silica) | NIOSH REL |

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : pigmented

Odor : ammonia-like, slight odour

Odor Threshold : No data available

pH : slightly alkaline

Melting point : No applicable information available.

Freezing point No applicable information available.

Boiling point : No applicable information available.

Flash point : 200.01 °F / 93.34 °C

200 °F / 93 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

Method: derived from flash point

Relative vapor density : Heavier than air.

Relative density : 1.90 - 2.25 (68 °F / 20 °C)

Density : 15.8 - 18.7 lb/USg (68.00 °F / 20.00 °C)

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

Solubility(ies)

Water solubility : soluble

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, kinematic : No applicable information available.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

crystalline silica:

Partition coefficient: n-

octanol/water

Remarks: not applicable

ethyleneglycol:

Partition coefficient: n-

octanol/water

log Pow: approx. -1.36 (73 °F / 23 °C) Method: Calculation Hansch/Leo

GLP: no data

Remarks: Information taken from reference works and the

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

literature.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

TEXTURE COL CLEAR



| | Version 1.0 | Revision Date: 10/14/2020 | SDS Number: 000000260215 | Date of last issue: - Date of first issue: 10/14/2020 | |
|---|----------------|---------------------------|--------------------------|--|--|
| ethyleneglycol Limestone crystalline silica | | | | 107-21-1 1317-65-3 14808-60-7 | |
| | New | Jersey Right To Know | , | | |
| othylonoglycol | | | | 107 21 1 | |

 ethyleneglycol
 107-21-1

 Limestone
 1317-65-3

 crystalline silica
 14808-60-7

 talc
 14807-96-6

California Prop. 65

WARNING: This product can expose you to chemicals including acrylamide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1001-1050

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

: OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response: EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substanc-

TEXTURE COL CLEAR



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/14/2020 000000260215 Date of first issue: 10/14/2020

es; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/14/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN