CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

SECTION 1. IDENTIFICATION

Product name : CLASSIC COL DARK

Product code : 00000000050002399

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity :

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution based on:

inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 50 - < 70
Limestone	1317-65-3	>= 10 - < 20
Titanium dioxide	13463-67-7	>= 1 - < 5
Silicon dioxide	7631-86-9	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

CLASSIC COL DARK



Version Revision Date: SDS Number: Date of last issue: 10/22/2020 2.0 04/14/2021 000000260573 Date of first issue: 10/22/2020

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment :

for fire-fighters

Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

atelv.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact.

Avoid contact with eyes.

Conditions for safe storage : Keep contain

Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem-

perature

> 32 °F / > 0 °C

Further information on stor-

age stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respir-	10 mg/m3 /	OSHA Z-3

CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

1	1	1	Lavaraa	1
		able)	%SiO2+2	00114.7.2
		TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respir- able)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWÁ (Total dust)	10 mg/m3	OSHA P0
		TWÁ	10 mg/m3 (Titanium dioxide)	ACGIH
Silicon dioxide	7631-86-9	REL value	6 mg/m3	NIOSH
		TWA value	6 mg/m3	29 CFR 1910.1000

CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

		(Table Z-1-A)
TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
TWA	6 mg/m3 (Silica)	NIOSH REL

Engineering measures : Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

CLASSIC COL DARK



Version Revision Date: SDS Number: Date of last issue: 10/22/2020 2.0 04/14/2021 000000260573 Date of first issue: 10/22/2020

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : various colours

Odor : slight odour, ammonia-like

Odor Threshold : not determined

pH : 9.0 - 9.5

Melting point : No data available

Boiling point : 212 °F / 100 °C

Flash point : Not applicable

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 1.85

Density : approx. 1.0 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

CLASSIC COL DARK



Version Revision Date: SDS Number: Date of last issue: 10/22/2020 2.0 04/14/2021 000000260573 Date of first issue: 10/22/2020

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

CLASSIC COL DARK



Version Revision Date: SDS Number: Date of last issue: 10/22/2020 2.0 04/14/2021 000000260573 Date of first issue: 10/22/2020

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHA OSHA specifically regulated carcinogen

Quartz (SiO2) 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Residues should be disposed of in the same manner as the

substance/product.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

Packs that cannot be cleaned should be disposed of in the

same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

CLASSIC COL DARK



14808-60-7

Version 2.0	Revision Date: 04/14/2021	SDS Number: 000000260573	Date of last issue: 10/22/2020 Date of first issue: 10/22/2020
	Titanium dioxide Quartz (SiO2)		13463-67-7 14808-60-7
New	Limestone Jersey Right To Kno	w	1317-65-3
Titanium dioxide Limestone			13463-67-7 1317-65-3

California Prop. 65

Quartz (SiO2)

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as


active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1000 (Table Z- : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

CLASSIC COL DARK



Version **Revision Date:** SDS Number: Date of last issue: 10/22/2020 04/14/2021 000000260573 Date of first issue: 10/22/2020 2.0

OSHA - Specifically Regulated Substances (29 CFR 29 CFR 1910.1001-1050

1910.1001-1050)

USA. ACGIH Threshold Limit Values (TLV) **ACGIH**

ACGIHTLV American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH NIOSH REL USA. NIOSH Recommended Exposure Limits

OSHA Specifically Regulated Chemicals/Carcinogens OSHA CARC USA. OSHA - TABLE Z-1 Limits for Air Contaminants -OSHA P0

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value

Time Weighted Average (TWA):

Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : 3) / TWA value

29 CFR 1910.1001-1050 /

OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / Time Weighted Average (TWA):

TWA value

ACGIH / TWA 8-hour, time-weighted average ACGIHTLV / TWA value Time Weighted Average (TWA): NIOSH / REL value Recommended exposure limit (REL):

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

Permissible exposure limit (PEL) OSHA CARC / PEL OSHA P0 / TWA 8-hour time weighted average OSHA Z-1 / TWA 8-hour time weighted average OSHA Z-3 / TWA 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New

CLASSIC COL DARK



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/22/2020

 2.0
 04/14/2021
 000000260573
 Date of first issue: 10/22/2020

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/14/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN