

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

### 1 Identification

- **Product identifier**
- **Trade name:** SikaBiresin AP861-1 (861 Hardener)
- **Article number:** I861089-1
- **Application of the substance / the mixture** Epoxy curing agent
- **Details of the supplier of the safety data sheet**  
Sika Advanced Resins, US  
EHS Department
- **Manufacturer/Supplier:**  
Supplier's Name: Sika Advanced Resins, US  
Headquarters:  
30800 Stephenson Hwy  
Madison Heights, MI 48071  
USA  
  
advancedresins.ehs@us.sika.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (248) 588-2270  
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 1)

· **Hazard pictograms**



GHS05    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Benzyl alcohol*

*Tofa, reaction products with TEPA*

*Methyleneoxide, polymer with benzenamine, hydrogenated*

*Polymer of C-18 unsat'd fatty acid dimers w/TETA & TOFA*

*tetraethylenepentamine*

*3,6-diazaoctanethylenediamin*

· **Hazard statements**

*Harmful if swallowed.*

*Causes severe skin burns and eye damage.*

*May cause an allergic skin reaction.*

*May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Do not breathe dusts or mists.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If swallowed: Call a poison center/doctor if you feel unwell.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Immediately call a poison center/doctor.*

*Specific treatment (see on this label).*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



*Health = 3*

*Fire = 1*

*Reactivity = 0*

· **HMIS-ratings (scale 0 - 4)**



*Health = \*3*

*Fire = 1*

*Reactivity = 0*

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol	20-50%
CAS: 135108-88-2	Methyleneoxide, polymer with benzenamine, hydrogenated	20-50%
CAS: 68953-36-6	Tofa, reaction products with TEPA	10-20%
	Polymer of C-18 unsat'd fatty acid dimers w/TETA & TOFA	5-10%
CAS: 67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	5-10%
CAS: 112-57-2 EINECS: 203-986-2	tetraethylenepentamine	≥1-<5%
	Organic acid - Proprietary	≥1-<3%
CAS: 1761-71-3 EINECS: 217-168-8	4,4'-methylenebis(cyclohexylamine)	≥1-<3%
CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin	≥1-<5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Immediately call a doctor.  
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 3)

· **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

100-51-6	Benzyl alcohol	30 ppm
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	120 mg/m <sup>3</sup>
112-57-2	tetraethylenepentamine	15 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	3 ppm

· **PAC-2:**

100-51-6	Benzyl alcohol	52 ppm
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	1,300 mg/m <sup>3</sup>

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 4)

112-57-2	tetraethylenepentamine	130 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
<b>· PAC-3:</b>		
100-51-6	Benzyl alcohol	740 ppm
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	7,900 mg/m <sup>3</sup>
112-57-2	tetraethylenepentamine	790 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	83 ppm

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

<b>100-51-6 Benzyl alcohol</b>	
WEEL	Long-term value: 10 ppm
<b>112-57-2 tetraethylenepentamine</b>	
WEEL	Long-term value: 5 mg/m <sup>3</sup> Skin; DSEN
<b>112-24-3 3,6-diazaoctanethylenediamin</b>	
WEEL	Long-term value: 6 mg/m <sup>3</sup> , 1 ppm Skin

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 5)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.
- **Breathing equipment:**  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Pasty
<b>Color:</b>	Brown
<b>Odor:</b>	Amine-like
<b>Odor threshold:</b>	Not determined.

(Contd. on page 7)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 6)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	197 °C (386.6 °F)
· <b>Flash point:</b>	170 °C (338 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	435 °C (815 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.3 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	0.1 hPa
· <b>Density at 20 °C (68 °F):</b>	0.9 g/cm <sup>3</sup> (7.51 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	27.4 %
<b>VOC content:</b>	27.44 %
	247.0 g/l / 2.06 lb/gal
<b>Solids content:</b>	28.8 %
· <b>Other information</b>	No further relevant information available.

### \* 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 7)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 100-51-6 Benzyl alcohol

Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

#### 112-57-2 tetraethylenepentamine

Oral	LD50	2,140 mg/kg (rat)
Dermal	LD50	660 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

7631-86-9	silicon dioxide, chemically prepared	3
	Red Iron Oxide	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

Trade name: SikaBiresin AP861-1 (861 Hardener)

(Contd. of page 8)

**12 Ecological information**

**· Toxicity**

**· Aquatic toxicity:**

**100-51-6 Benzyl alcohol**

96 hr LC50	460 mg/l (Fathead minnow)
	10 mg/l (Fish)

**· Persistence and degradability** No further relevant information available.

**· Behavior in environmental systems:**

**· Bioaccumulative potential** No further relevant information available.

**· Mobility in soil** No further relevant information available.

**· Additional ecological information:**

**· General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

**· Results of PBT and vPvB assessment**

**· PBT:** Not applicable.

**· vPvB:** Not applicable.

**· Other adverse effects** No further relevant information available.

**13 Disposal considerations**

**· Waste treatment methods**

**· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packagings:**

**· Recommendation:** Disposal must be made according to official regulations.

**· Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

**· UN-Number**

**· DOT**

NA2735

**· IMDG, IATA**

UN2735

**· UN proper shipping name**

**· DOT**

Amines, liquid, corrosive, n.o.s. (Polymer of C-18 unsat'd fatty acid dimers w/TETA & TOFA, Tofa, reaction products with TEPA)

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 9)

· **IMDG, IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (Amidoamine Resin, Tofa, reaction products with TEPA)

· **Transport hazard class(es)**

· **DOT**



· **Class** 8 Corrosive substances  
 · **Label** 8

· **IMDG, IATA**



· **Class** 8 Corrosive substances  
 · **Label** 8

· **Packing group**  
 · **DOT, IMDG, IATA** III

· **Environmental hazards:**  
 · **Marine pollutant:** No

· **Special precautions for user** Warning: Corrosive substances  
 · **Hazard identification number (Kemler code):** 80  
 · **EMS Number:** F-A,S-B  
 · **Segregation groups** Alkalis

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
 · **Quantity limitations** On passenger aircraft/rail: 5 L  
 On cargo aircraft only: 60 L

· **IMDG**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 10)

· **UN "Model Regulation":** UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (AMIDOAMINE RESIN, TOFA, REACTION PRODUCTS WITH TEPA), 8, III

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7 Quartz (SiO<sub>2</sub>)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Listed in CWC Regulations**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 11)

· **Hazard pictograms**



GHS05    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Benzyl alcohol*  
*Tofa, reaction products with TEPA*  
*Methyleneoxide, polymer with benzenamine, hydrogenated*  
*Polymer of C-18 unsat'd fatty acid dimers w/TETA & TOFA*  
*tetraethylenepentamine*  
*3,6-diazaoctanethylenediamin*

· **Hazard statements**

*Harmful if swallowed.*  
*Causes severe skin burns and eye damage.*  
*May cause an allergic skin reaction.*  
*May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

*Do not breathe dusts or mists.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*If swallowed: Call a poison center/doctor if you feel unwell.*  
*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*  
*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*  
*Continue rinsing.*  
*Immediately call a poison center/doctor.*  
*Specific treatment (see on this label).*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Date of preparation / last revision** 05/19/2020 / 8

· **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods*  
*DOT: US Department of Transportation*  
*IATA: International Air Transport Association*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

(Contd. on page 13)

US

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 05/19/2020

Reviewed on 05/19/2020

**Trade name: SikaBiresin AP861-1 (861 Hardener)**

(Contd. of page 12)

NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
· **\* Data compared to the previous version altered.**

US