Revision Date 11/08/2017 Print Date 11/08/2017

### 1. Identification

Product name Sikaflex®-124

Supplier Sika Corporation

> 201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

E-mail address ehs@sika-corp.com

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

Recommended use of the

chemical and restrictions on

use

: For further information, refer to product data sheet.

### 2. Hazards identification

### **GHS Classification**

Respiratory sensitization, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitization, Category 1

H317: May cause an allergic skin reaction. Carcinogenicity, Category 1A (Inhalation) H350i: May cause cancer by inhalation.

### **GHS** label elements

Hazard pictograms



Signal Word

Hazard Statements H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H350i May cause cancer by inhalation.

**Precautionary Statements** Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P272 Contaminated work clothing must not be allowed out of

the workplace.



Revision Date 11/08/2017 Print Date 11/08/2017

P280 Wear protective gloves.

P281 Use personal protective equipment as required. P285 In case of inadequate ventilation wear respiratory protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

### 3. Composition/information on ingredients

### **Hazardous ingredients**

Chemical name	CAS-No.	Concentration (%)
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 0.1 - < 1 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %
Quartz (SiO2) <5µm	14808-60-7	>= 0.1 - < 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.



Revision Date 11/08/2017 Print Date 11/08/2017

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and delayed

: sensitizing effects carcinogenic effects

Asthmatic appearance Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

May cause cancer by inhalation.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

### 5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Sika®

Revision Date 11/08/2017 Print Date 11/08/2017

### 7. Handling and storage

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Prevent unauthorized access.

Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : No data available

### 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
4,4'-methylenediphenyl diisocyanate	101-68-8	ACGIH	TWA	0.005 ppm
		OSHA Z-1	С	0.02 ppm 0.2 mg/m3
		OSHA P0	С	0.02 ppm 0.2 mg/m3
ethylbenzene	100-41-4	ACGIH	TWA	20 ppm
		ACGIH	STEL	125 ppm
		OSHA Z-1	TWA	100 ppm 435 mg/m3
		OSHA P0	TWA	100 ppm 435 mg/m3
		OSHA P0	STEL	125 ppm 545 mg/m3
Quartz (SiO2) <5µm	14808-60-7	OSHA Z-3	TWA	10 mg/m3 /



Revision Date 11/08/2017

		%SiO2+2 respirable
OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
OSHA P0	TWA	0.1 mg/m3 Respirable fraction
ACGIH	TWA	0.025 mg/m3 Respirable fraction
OSHA Z-1	TWA	0.05 mg/m3 Respirable dust

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### \*\*Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

### **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

: Safety eyewear complying with an approved standard should Eye protection

be used when a risk assessment indicates this is necessary.

# Print Data 11/08/2017

Revision Date 11/08/2017 Print Date 11/08/2017

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

### 9. Physical and chemical properties

Appearance : paste Color : gray

Odor : odorless

Odor Threshold : No data available

Flash point :  $> 199.99 \, ^{\circ}\text{F} \, (> 93.33 \, ^{\circ}\text{C})$ 

Ignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

pH : No data available

Melting point/range /

Freezing point

: No data available

Boiling point/boiling range : No data available

Vapor pressure : 0.01 mmHg (0.01 hpa)

Density : 1.31 g/cm3

at 68 °F (20 °C)

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s

at 104 °F (40 °C)

## Revision Date 11/08/2017 Print Date 11/08/2017

Relative vapor density : No data available

Evaporation rate : No data available

Burning rate : No data available

Volatile organic compounds

(VOC) content

15 g/l

### 10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

### 11. Toxicological information

### **Acute toxicity**

Not classified based on available information.

### **Ingredients:**

### 4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Test atmosphere: dust/mist Method: Expert judgment

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified based on available information.



Revision Date 11/08/2017

Not classified based on available information.

### STOT-single exposure

Reproductive toxicity

Not classified based on available information.

### STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### **Aspiration toxicity**

Not classified based on available information.

### Carcinogenicity

May cause cancer by inhalation.

**IARC** Group 1: Carcinogenic to humans

> Quartz (SiO2) <5µm 14808-60-7 Group 2B: Possibly carcinogenic to humans

> titanium dioxide 13463-67-7 ethylbenzene 100-41-4

**NTP** Known to be human carcinogen

> Quartz (SiO2) <5µm 14808-60-7

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have seen shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory aninals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that cause lung cancer. Epidemiology studies do no suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

### 12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

### 13. Disposal considerations

### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should



Revision Date 11/08/2017 Print Date 11/08/2017

protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

### 14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

**IMDG** 

Not dangerous goods

### Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### 15. Regulatory information

**TSCA list** : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

### **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### **SARA304** Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard

Respiratory or skin sensitization

Carcinogenicity

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

ethylbenzene 100-41-4 0.21 %

Clean Air Act

Revision Date 11/08/2017 Print Date 11/08/2017



Ozone-Depletion **Potential** 

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65

MARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

### 16. Other information

**HMIS Classification** 



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 11/08/2017

# Safety Data Sheet

# Sikaflex®-124

Revision Date 11/08/2017



Material number: 535259