

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0	Revision Date: 07/29/2020	SDS Number: 000000467347	Date of last issue: 07/29/2020 Date of first issue: 07/29/2020
----------------	------------------------------	-----------------------------	---

SECTION 1. IDENTIFICATION

Product name : SikaWall-6230 Chroma M1.5 Finish Custom

Product code : 000000000050002379

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1 (Lungs)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H350i May cause cancer by inhalation.
H372 Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0	Revision Date: 07/29/2020	SDS Number: 000000467347	Date of last issue: 07/29/2020 Date of first issue: 07/29/2020
----------------	------------------------------	-----------------------------	---

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P202 Do not handle until all safety precautions have been read and understood.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 50 - < 75
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	25265-77-4	>= 0.3 - < 3

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0	Revision Date: 07/29/2020	SDS Number: 000000467347	Date of last issue: 07/29/2020 Date of first issue: 07/29/2020
----------------	------------------------------	-----------------------------	---

- If irritation develops, seek medical attention.
- In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes damage to organs through prolonged or repeated exposure if inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0 Revision Date: 07/29/2020 SDS Number: 000000467347 Date of last issue: 07/29/2020
Date of first issue: 07/29/2020

- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Spilled product should be disposed in accordance with all applicable government regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid aerosol formation.
Avoid inhalation of mists/vapours.
Avoid skin contact.
Avoid contact with eyes.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : No applicable information available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m ³	ACGIHTLV
		TWA value	0.05 mg/m ³ (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m ³	NIOSH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable par-	0.025 mg/m ³ (Silica)	ACGIH

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0 Revision Date: 07/29/2020 SDS Number: 000000467347 Date of last issue: 07/29/2020
Date of first issue: 07/29/2020

		ticulate matter)		
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : off-white to light tan

Odor : mild, earthy

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0	Revision Date: 07/29/2020	SDS Number: 000000467347	Date of last issue: 07/29/2020 Date of first issue: 07/29/2020
----------------	------------------------------	-----------------------------	---

pH	:	9 - 10 (77 °F / 25 °C)
Melting point	:	No applicable information available.
Boiling point	:	not applicable
Flash point	:	> 200 °F / > 93 °C
		Method: Standard Method of Test for Flash Point by Setaflash Closed Tester
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not determined
Upper explosion limit / Upper flammability limit	:	No applicable information available.
Lower explosion limit / Lower flammability limit	:	No applicable information available.
Vapor pressure	:	No applicable information available.
Relative vapor density	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	14.8 lb/USg (77 °F / 25 °C)
Bulk density	:	not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	not applicable
Autoignition temperature	:	not applicable
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Based on the chemical structure there is no indication of explosive properties.
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version	Revision Date:	SDS Number:	Date of last issue: 07/29/2020
2.0	07/29/2020	000000467347	Date of first issue: 07/29/2020

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials :
Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0	Revision Date: 07/29/2020	SDS Number: 000000467347	Date of last issue: 07/29/2020 Date of first issue: 07/29/2020
----------------	------------------------------	-----------------------------	---

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Quartz (SiO₂):

Partition coefficient: n-octanol/water : Remarks: not applicable

Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol:

Partition coefficient: n-octanol/water : log Pow: 3.2 (77 °F / 25 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), HPLC method.
GLP: no

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version	Revision Date:	SDS Number:	Date of last issue: 07/29/2020
2.0	07/29/2020	000000467347	Date of first issue: 07/29/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Quartz (SiO ₂)	14808-60-7
----------------------------	------------

New Jersey Right To Know

Quartz (SiO ₂)	14808-60-7
----------------------------	------------

California Prop. 65

WARNING: This product can expose you to chemicals including benzophenone, which is/are known to the State of California to cause cancer, and ethyleneglycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

- TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version 2.0 Revision Date: 07/29/2020 SDS Number: 000000467347 Date of last issue: 07/29/2020
Date of first issue: 07/29/2020


TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		M
FLAMMABILITY		M
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level:
29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):
ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version	Revision Date:	SDS Number:	Date of last issue: 07/29/2020
2.0	07/29/2020	000000467347	Date of first issue: 07/29/2020

OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/29/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO

SAFETY DATA SHEET

SikaWall-6230 Chroma M1.5 Finish Custom



Version	Revision Date:	SDS Number:	Date of last issue: 07/29/2020
2.0	07/29/2020	000000467347	Date of first issue: 07/29/2020

DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN