

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

### SECTION 1. IDENTIFICATION

Product name : Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone  
Product code : 000000000050452546

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Sealant  
Restrictions on use : Reserved for industrial and professional use.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4  
Eye irritation : Category 2A  
Respiratory sensitization : Category 1  
Skin sensitization : Category 1  
Carcinogenicity : Category 2  
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal Word : Danger  
Hazard Statements : H227 Combustible liquid.  
H317 May cause an allergic skin reaction.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

### Precautionary Statements :

#### **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P285 In case of inadequate ventilation wear respiratory protection.

#### **Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version 2.0      Revision Date: 04/08/2024      SDS Number: 000000700857      Date of last issue: 01/06/2021  
Date of first issue: 04/28/2020

### Other hazards

Contains isocyanates. Inhalation of isocyanate mists or vapors may cause respiratory irritation, breathlessness, chest discomfort and reduced pulmonary function. Overexposure well above the PEL may result in bronchitis, bronchial spasms and pulmonary edema. Animal tests indicate that skin contact may play a role in causing respiratory sensitization.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Sealant

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	$\geq 30 - < 50$
Titanium dioxide	13463-67-7	$\geq 1 - < 5$
Stoddard solvent	8052-41-3	$\geq 1 - < 5$
calcium oxide	1305-78-8	$\geq 1 - < 5$
Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate	59719-67-4	$\geq 1 - < 5$
p-Toluenesulphonyl isocyanate	4083-64-1	$\geq 0.1 - < 1$
toluene-2,6-diisocyanate	91-08-7	$\geq 0.1 - < 1$
3-Oxazolidineethanol, 2-(1-methylethyl)-, 3,3'-carbonate	145899-78-1	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.
- In case of skin contact : Wash thoroughly with soap and water
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

Causes damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : water jet

Hazardous combustion products : fumes/smoke  
harmful vapours  
Carbon oxides  
nitrogen oxides  
carbon black

Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water.  
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.

Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version 2.0      Revision Date: 04/08/2024      SDS Number: 000000700857      Date of last issue: 01/06/2021  
Date of first issue: 04/28/2020

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable par-	0.2 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version 2.0      Revision Date: 04/08/2024      SDS Number: 000000700857      Date of last issue: 01/06/2021  
Date of first issue: 04/28/2020

		ticulate matter)		
		TWA (Respirable particulate matter)	2.5 mg/m3 (Titanium dioxide)	ACGIH
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
calcium oxide	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
toluene-2,6-diisocyanate	91-08-7	C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0

**Engineering measures** : Provide adequate exhaust ventilation to control work place concentrations.

### Personal protective equipment

**Respiratory protection** : Wear appropriate certified respirator when exposure limits may be exceeded.  
Use NIOSH approved respiratory protection.

**Hand protection**

**Remarks** : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Wear safety glasses with side shields or goggles.

**Skin and body protection** : Body protection must be chosen based on level of activity and exposure.

**Protective measures** : Do not inhale dust/fumes/aerosols.  
Avoid contact with the skin, eyes and clothing.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Color	: light gray
Odor	: mild
Odor Threshold	: not determined
pH	: neutral
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: 185 °F / 85 °C Method: closed cup
Evaporation rate	: No data available
Flammability (liquids)	: Combustible liquid.
Self-ignition	: not self-igniting
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

---

Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	11.3 lb/USg (77 °F / 25 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Sublimation point	:	No data available
Molecular weight	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Suspected of causing cancer.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans toluene-2,6-diisocyanate (toluene diisocyanates)	91-08-7
<b>NTP</b>	Reasonably anticipated to be a human carcinogen toluene-2,6-diisocyanate	91-08-7

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

#### Aspiration toxicity

Not classified based on available information.

#### Further information

#### Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version 2.0	Revision Date: 04/08/2024	SDS Number: 000000700857	Date of last issue: 01/06/2021 Date of first issue: 04/28/2020
----------------	------------------------------	-----------------------------	---

---

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version 2.0      Revision Date: 04/08/2024      SDS Number: 000000700857      Date of last issue: 01/06/2021  
Date of first issue: 04/28/2020

### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene-2,6-diisocyanate	91-08-7	100	31575

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate	91-08-7	>= 0.1 - < 1 %
--------------------------	---------	----------------

### US State Regulations

#### Pennsylvania Right To Know

Limestone	1317-65-3
Titanium dioxide	13463-67-7
Di-isononylphthalate	28553-12-0
Stoddard solvent	8052-41-3
calcium oxide	1305-78-8
toluene-2,6-diisocyanate	91-08-7

#### New Jersey Right To Know

Limestone	1317-65-3
Titanium dioxide	13463-67-7
Stoddard solvent	8052-41-3
calcium oxide	1305-78-8
toluene-2,6-diisocyanate	91-08-7

#### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version 2.0      Revision Date: 04/08/2024      SDS Number: 000000700857      Date of last issue: 01/06/2021  
Date of first issue: 04/28/2020

DSL : This product contains one or more components listed on the Canadian NDSL. All other components are on the Canadian DSL.

### TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

toluene-2,6-diisocyanate      91-08-7      See 40 CFR § 721.10789; Proposed Rule

4-methyl-m-phenylene diisocyanate      584-84-9      See 40 CFR § 721.10789; Proposed Rule


The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

toluene-2,6-diisocyanate      91-08-7

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits  
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikaflex SL 1 limestone Formerly MSeal SL 1 limestone

Version	Revision Date:	SDS Number:	Date of last issue: 01/06/2021
2.0	04/08/2024	000000700857	Date of first issue: 04/28/2020

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
NIOSH REL / C : Ceiling value not be exceeded at any time.  
OSHA P0 / TWA : 8-hour time weighted average  
OSHA P0 / STEL : Short-term exposure limit  
OSHA Z-1 / TWA : 8-hour time weighted average  
OSHA Z-1 / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/08/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN