

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

SECTION 1. IDENTIFICATION

Product name : Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B
Product code : 000000000050519488

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Waterproof coating
Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Inhalation) : Category 4
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Short-term (acute) aquatic hazard : Category 3
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black exclamation mark inside. The second is a red diamond with a black silhouette of a person and a flame over their head, indicating a health hazard.

Signal Word : Danger

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

Hazard Statements : H332 Harmful if inhaled.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dust or mist.
P273 Avoid release to the environment.
P284 In case of inadequate ventilation wear respiratory protection.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Disposal:
P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : polyurethane component

Components

Chemical name	CAS-No.	Concentration (% w/w)
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Not Assigned	$\geq 1 - < 3$
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8	$\geq 0.3 - < 1$
Titanium dioxide	13463-67-7	$\geq 1 - < 5$

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : Harmful if inhaled.
Causes serious eye irritation.
Causes skin irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

- Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Dike spillage.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors or spray mist.
-

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 00000834448 Date of last issue: 12/04/2020
 Date of first issue: 12/04/2020

Avoid contact with skin and eyes.
 Provide suitable exhaust ventilation at the processing machines.
 Ensure thorough ventilation of stores and work areas.
 When handling heated product, vapours of the product should be ventilated, and respiratory protection used.
 Wear respiratory protection when spraying.
 Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Protect against moisture.
 Danger of bursting when sealed gastight.
 If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
 Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA value	0.005 ppm	ACGIHTLV
		TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.045 mg/m ³	NIOSH REL
		ST	0.02 ppm 0.18 mg/m ³	NIOSH REL
		TWA	0.005 ppm	OSHA P0
		STEL	0.02 ppm	OSHA P0
Titanium dioxide	13463-67-7	TWA value	10 mg/m ³	ACGIHTLV
		PEL (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total	15 mg/m ³	OSHA Z-1

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
 Date of first issue: 12/04/2020

		dust)		
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection

Remarks : Chemical resistant protective gloves should be worn to prevent all skin contact. Manufacturer's directions for use should be observed because of great diversity of types. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) fluoroelastomer (Viton) butyl rubber

Eye protection : Tightly fitting safety goggles (chemical goggles).
 Wear face shield if splashing hazard exists.

Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.
 Suitable materials may include saran-coated material depending upon conditions of use.

Protective measures : Do not inhale gases/vapours/aerosols.
 Avoid contact with the skin, eyes and clothing.
 Avoid exposure - obtain special instructions before use.
 Handle in accordance with good building materials hygiene and safety practice.
 Wearing of closed work clothing is recommended.
 Wear protective clothing as necessary to prevent contact.
 Eye wash fountains and safety showers must be easily accessible.
 Observe the appropriate PEL or TLV value.

Hygiene measures : When using, do not eat, drink or smoke.

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber

Odor : mild

Odor Threshold : No data available

pH : Not applicable

Melting point : No applicable information available.

Boiling range : 221.00 - 316.00 °F / 105.00 - 157.78 °C

Flash point : 321.01 °F / 160.56 °C

Evaporation rate : No applicable information available.

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 8.7 lb/USg (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)
Water solubility : insoluble

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

 Viscosity, dynamic : No applicable information available.

 Viscosity, kinematic : No applicable information available.

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Remarks: No applicable information available.

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

Acute inhalation toxicity : ATE: 1.03 mg/l
Remarks: Determined for mist

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1	Revision Date: 02/01/2021	SDS Number: 000000834448	Date of last issue: 12/04/2020 Date of first issue: 12/04/2020
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Partition coefficient: n-octanol/water : log Pow: approx. 4.75 (77 °F / 25 °C)
pH: 7
Method: other (calculated)
Remarks: Study scientifically not justified.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version 1.1 Revision Date: 02/01/2021 SDS Number: 000000834448 Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

3- 4098-71-9
isocyanatome-
thyl-3,5,5-
trimethylcyclo-
hexyl isocyanate

US State Regulations

Pennsylvania Right To Know

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9
Titanium dioxide	13463-67-7

New Jersey Right To Know

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9
Titanium dioxide	13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains the following components listed on the Canadian NDSL. All other components are on the Canadian DSL.

Fatty acids, C14-18 and C16-18-unsatd., maleated

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B




Version
1.1

Revision Date:
02/01/2021

SDS Number:
000000834448

Date of last issue: 12/04/2020
Date of first issue: 12/04/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	:	OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
ACGIH / TWA	:	8-hour, time-weighted average
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
1.1	02/01/2021	00000834448	Date of first issue: 12/04/2020

Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/01/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND

SAFETY DATA SHEET

Sikalastic M 270 NP Part B Formerly MSeal M 270NP Part B



Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
1.1	02/01/2021	00000834448	Date of first issue: 12/04/2020

INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN