



Version 2.0

Revision Date: 03/28/2022

SDS Number: 000000261101

Date of last issue: 08/04/2020 Date of first issue: 08/04/2020

SECTION 1. IDENTIFICATION

Product name : Sikalnject-1380 Part B Formerly MInject 1380 PTB

Product code : 00000000055352711

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 3

Skin corrosion : Category 1A

Serious eye damage : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 1B

Specific target organ toxicity

- repeated exposure

Category 2

Specific target organ toxicity

- single exposure

Category 3

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements



Sikalnject-1380 Part B Formerly MInject 1380 PTB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/04/2020

 2.0
 03/28/2022
 000000261101
 Date of first issue: 08/04/2020

Hazard pictograms











Signal Word : Danger

Hazard Statements : H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H360F May damage fertility.

H373 May cause damage to organs through prolonged or re-

peated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON

CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

Sikalnject-1380 Part B Formerly Minject 1380 PTB



Version 2.0

Revision Date: 03/28/2022

SDS Number: 000000261101

Date of last issue: 08/04/2020 Date of first issue: 08/04/2020

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Amines

Components

Chemical name	CAS-No.	Concentration (% w/w)
2-sec-Butylphenol	89-72-5	>= 20 - < 30
trimethylhexane-1,6-diamine	25620-58-0	>= 20 - < 30
diethylmethylbenzenediamine	68479-98-1	>= 10 - < 20
2,4,6-	90-72-2	>= 10 - < 20
tris(dimethylaminomethyl)phenol		
2,2'-iminodi(ethylamine)	111-40-0	>= 5 - < 20
bisphenol A	80-05-7	>= 5 - < 20
Bis[(dimethylamino)methyl]phenol	71074-89-0	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Immediately flush eyes for at least 15 minutes. Get medical

attention.

Remove contact lenses.

Keep eye wide open while rinsing.

Protect unharmed eye.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,



Sikalnject-1380 Part B Formerly Minject 1380 PTB

Version Revision Date: SDS Number: Date of last issue: 08/04/2020 2.0 03/28/2022 000000261101 Date of first issue: 08/04/2020

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms

and effects, both acute and

delayed

Toxic if inhaled.

Causes severe skin burns and eye damage.

Harmful if swallowed.

May cause an allergic skin reaction. May cause respiratory irritation.

May damage fertility.

May cause damage to organs through prolonged or repeated

exposure.

Treat symptomatically. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod: :

ucts

nitrogen oxides Carbon oxides fumes/smoke carbon black

corrosive gases/vapours

Further information The degree of risk is governed by the burning substance and

the fire conditions.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment:

for fire-fighters

Firefighters should be equipped with self-contained breathing

apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective clothing.

Do not breathe vapour/aerosol/spray mists.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.



Sikalnject-1380 Part B Formerly Minject 1380 PTB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/04/2020

 2.0
 03/28/2022
 000000261101
 Date of first issue: 08/04/2020

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Handle and open container with care.

Wear personal protective equipment. Avoid contact with skin and eyes.

Avoid aerosol formation. Keep container tightly sealed.

Keep away from sources of ignition - No smoking.

Conditions for safe storage : Prevent unauthorized access.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight. Store protected against freezing.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-sec-Butylphenol	89-72-5	TWA value	5 ppm	ACGIHTLV
		REL value	5 ppm 30 mg/m3	NIOSH
		TWA value	5 ppm 30 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	5 ppm	ACGIH
		TWA	5 ppm 30 mg/m3	NIOSH REL
		TWA	5 ppm 30 mg/m3	OSHA P0
2,2'-iminodi(ethylamine)	111-40-0	TWA	1 ppm	ACGIH
		TWA	1 ppm 4 mg/m3	NIOSH REL
		TWA	1 ppm 4 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation.

Sikalnject-1380 Part B Formerly MInject 1380 PTB



Version 2.0

Revision Date: 03/28/2022

SDS Number: 000000261101

Date of last issue: 08/04/2020 Date of first issue: 08/04/2020

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles) and face

shield.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : black-brown

Odor : of phenol

Odor Threshold : not determined

pH : alkaline

Melting point : No data available

Boiling point/boiling range : $> 392 \, ^{\circ}\text{F} / > 200 \, ^{\circ}\text{C}$

Sikalnject-1380 Part B Formerly Minject 1380 PTB



Version Revision Date: SDS Number: Date of last issue: 08/04/2020 2.0 03/28/2022 000000261101 Date of first issue: 08/04/2020

Flash point : $> 212 \,^{\circ}\text{F} / > 100 \,^{\circ}\text{C}$

Evaporation rate : No data available

Flammability (liquids) : not highly flammable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : approx. 0.98 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : insoluble (68 °F / 20 °C)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : approx. 1,900 mPa.s (approx. 77 °F / 25 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.





Version Revision Date: SDS Number: Date of last issue: 08/04/2020 2.0 03/28/2022 000000261101 Date of first issue: 08/04/2020

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Oxidizing agents

strong alkalies

Acids

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed. Toxic if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 771.55 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 6.58 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility.

Sikalnject-1380 Part B Formerly MInject 1380 PTB



Version 2.0

Revision Date: 03/28/2022

SDS Number: 000000261101

Date of last issue: 08/04/2020 Date of first issue: 08/04/2020

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicolo-

gy have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements.

Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible



Sikalnject-1380 Part B Formerly Minject 1380 PTB

Version Revision Date: SDS Number: Date of last issue: 08/04/2020 2.0 03/28/2022 000000261101 Date of first issue: 08/04/2020

and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1760

Proper shipping name : CORROSIVE LIQUID, N.O.S.

(2-SEC-BUTYLPHENOL, TRIMETHYLHEXANE-1,6-

DIAMINE)

Class : 8
Packing group : II
Labels : 8

IATA-DGR

UN/ID No. : UN 1760

Proper shipping name : Corrosive liquid, n.o.s.

(2-SEC-BUTYLPHENOL, TRIMETHYLHEXANE-1,6-

DIAMINE)

Class : 8 Packing group : II

Labels : Corrosive Packing instruction (cargo : 855

aircraft)

Packing instruction (passen-

ger aircraft)

851

IMDG-Code

UN number : UN 1760

Proper shipping name : CORROSIVE LIQUID, N.O.S.

(2-SEC-BUTYLPHENOL, TRIMETHYLHEXANE-1,6-

DIAMINE)

Class : 8
Packing group : II
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1760

Proper shipping name : Corrosive liquids, n.o.s.

(2-SEC-BUTYLPHENOL, TRIMETHYLHEXANE-1,6-

DIAMINE)

Class : 8 Packing group : II

Labels : CORROSIVE

ERG Code : 154



Sikalnject-1380 Part B Formerly MInject 1380 PTB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/04/2020

 2.0
 03/28/2022
 000000261101
 Date of first issue: 08/04/2020

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

bisphenol A 80-05-7 >= 5 - < 10 %

US State Regulations

Pennsylvania Right To Know

2-sec-Butylphenol 89-72-5 bisphenol A 80-05-7 2,2'-iminodi(ethylamine) 111-40-0

New Jersey Right To Know

2-sec-Butylphenol 89-72-5 trimethylhexane-1,6-diamine 25620-58-0 bisphenol A 80-05-7 2,2'-iminodi(ethylamine) 111-40-0

California Prop. 65

WARNING: This product can expose you to chemicals including bisphenol A, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information




Sikalnject-1380 Part B Formerly Minject 1380 PTB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/04/2020

 2.0
 03/28/2022
 000000261101
 Date of first issue: 08/04/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

Time Weighted Average (TWA):

values)

29 CFR 1910.1000 (Table Z-

1-A) / TWA value

ACGIH / TWA : 8-hour, time-weighted average ACGIHTLV / TWA value : Time Weighted Average (TWA):

NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Indus-



Sikalnject-1380 Part B Formerly Minject 1380 PTB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/04/2020

 2.0
 03/28/2022
 000000261101
 Date of first issue: 08/04/2020

trial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/28/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN