La Habra®





Pebbletex Classic PB Wall System

Class PB Exterior Insulation and Finish System providing a primary moisture barrier and optional secondary air/weather barrier

DESCRIPTION

Pebbletex Classic PB is an Exterior Insulation and Finish System (EIFS) that provides a durable weather-resistant primary barrier. The system offers design flexibility, aesthetic appeal and energy savings. Integrated system components include adhesive, EPS insulation board, reinforced base coat and 100% acrylic polymer finish. Pebbletex Classic PB complies with ASTM E 2568 and has passed rigorous tests including Full-Scale Fire, Wind-Load, Wind-Driven Rain, and Large and Small Missiles.

USES


For new or retrofit commercial and institutional construction such as hotels, hospitals, retail, schools, multi-family apartments and condominiums, and government facilities. Pebbletex Classic PB can be panelized to expedite year-round construction. Use over mass walls where drainage is not required.

ACCEPTABLE SUBSTRATES

PermaBase® Cement Board and other cement boards conforming with ASTM C1325 (Type A - exterior); poured concrete/unit masonry; ASTM C1177 type sheathings, including Weather Defense™ Platinum sheathing, GreenGlass® sheathing, e2XP™ sheathing, GlasRoc® sheathing, Securock™ glass-mat sheathing, and DensGlass® exterior sheathing; gypsum sheathing (ASTM C79/C1396); Exposure I or exterior plywood (Grade C/D or better); or Exposure I OSB.

ADVANTAGES

- · Cost-effective.
- Ability to achieve any architectural style with unlimited design options.
- Economical architectural detailing.
- Seamless exterior blanket of insulation provides high R values, lowers heating and cooling costs.
- Multiple options for impact resistance improve functional design, ease of maintenance.
- Plaster trims/accessories are not required for installation.
- Wide selection of standard colors, custom colors, and finish textures.



- 1. Concrete / Masonry*
- 2. LaHabra Adhesive
- 3. Approved EPS Insulation Board*
- 4. LaHabra Base Coat
- **5.** LaHabra Reinforcing Mesh
- **6.** LaHabra Base Coat
- 7. SikaWall® Tinted Primer (optional)
- 8. LaHabra Finish Coat
- *By Others

DESIGN CONSIDER ATIONS

- The design wind-load shall not exceed the system's allowable windload as stated in applicable code reports.
- System is not designed for horizontal applications.
- Use high impact mesh for ground floor applications in high traffic areas
- Consult the framing and sheathing manufacturer for design and application considerations.
- Limit the use of dark colors. Heat build up behind dark colors can adversely affect the performance of EPS insulation. Use of colors with a light reflectance value of less than 20% require the approval of the Sika Facades Technical Department.
- Do not use below grade; system must terminate a minimum of 203 mm (8") inches above grade.
- Maximum substrate design deflection is L/240.

Pebbletex Classic PB Wall System

WARRANTY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com/lahabra or by calling SIKA Facades' Technical Service Department at 1-800-589-1336. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at usa.sika.com.

