

PRODUCT DATA SHEET

Yellow Spaghetti®

Roof Walkway Pads and Rolls

PRODUCT DESCRIPTION

Yellow Spaghetti® is a heat and pressure bonded, nonwoven pad, made of spaghetti-like strands of flexible plastic.

USES

Protect membranes and surfacing materials in high traffic areas of commercial and industrial roofing systems.

CHARACTERISTICS / ADVANTAGES

- Lightweight
- Easy to install and maintain
- Porous, to prevent damming or ponding
- Allows even moisture evaporation from beneath the walkway system to retard algae growth
- Resistant to wind uplift
- UV stabilized and resistant to environmental and chemical degradation
- Does not leach plasticizer
- Highly visible; yellow in color
- Not affected by asphalt or coal tar pitch
- Suitable for use with built-up roof (BUR) and granular surface membranes

PRODUCT INFORMATION

Packaging

Pads

- 3 ft. x 4 ft. pads
- 150 pads per skid (600 lineal ft., 1800 sq. ft.)
- shipping weight is approximately 1350 lbs. per skid

Rolls

- 3 ft. x 25 ft. rolls
- 16 rolls per skid (500 lineal ft., 1200 sq. ft.)
- shipping weight is approximately 1100 lbs. per skid

Appearance / Color

Yellow or Grey

Shelf Life

n/a

Storage Conditions

n/a

Length

Pads: 4ft
Rolls: 25ft

Width

3ft

Thickness

5/16" nominal thickness

Product Data Sheet

Yellow Spaghetti®

June 2019, Version 01.01

020703830100000002

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

- The substrate must be free of all dirt, dust, talc and any form of moisture such as dew, rainwater, ice or snow.
- All surface preparation cleaning solvents must be allowed to flash off completely prior to installation.
- Household cleaners and detergents are not recommended for substrate preparation. Use solvent-based cleaners as approved by the membrane manufacturer (i.e. mineral spirits).

APPLICATION METHOD / TOOLS

- Install Yellow Spaghetti® on BUR in a thin layer of hot asphalt or coal tar pitch so the hot-mopped material does not bleed through the open pores of the pad or roll (i.e. sprinkle mop).
- Install Yellow Spaghetti® on single-ply roof membrane using a 100% silicone, neutral-cure, and vinyl-compatible sealant. Care must be taken to properly prepare the substrate as previously described for installation of pads.
- Use Eternabond™ 2" Doublestick Tape in 12" lengths, intermittently spaced around the pad or roll. Both surfaces must be clean and dry. Use a steel roller to apply pressure over the pad or roll for proper adhesion to the membrane.
- The approved caulking pattern is two rows of caulk, 1/2" wide by 12" long, applied to the outer edges of each roll with intermittent spacing not to exceed 12 inches.
- A space of no less than 2" and no more than 6" should be left between each roll.

AVAILABILITY/WARRANTY

Yellow Spaghetti® does not require any maintenance. Proper surface preparation and installation will ensure a maintenance-free area. Dirt and debris may be flushed from the pad or roll using a power spray or water hose.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of Sika products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

Yellow Spaghetti®
June 2019, Version 01.01
020703830100000002

YellowSpaghetti-en-US-(06-2019)-1-1.pdf

