

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

SECTION 1. IDENTIFICATION

Product name : SikaTop-500 Seal grey Formerly MSeal 500 gry

Product code : 000000000051710498

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 1

Specific target organ toxicity - single exposure : Category 3 (respiratory tract irritation)

Carcinogenicity (Inhalation) : Category 1A (Lungs)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.
H315 Causes skin irritation.

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

H335 May cause respiratory irritation.
H350i May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Precautionary Statements

:

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dust or mist.
P202 Do not handle until all safety precautions have been read and understood.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/ doctor/
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : modified cement mortar

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Cement, portland, chemicals | 65997-15-1 | >= 50 - < 75 |
| crystalline silica | 14808-60-7 | >= 25 - <= 50 |
| sodium carbonate | 497-19-8 | >= 7 - < 15 |
| Iron oxide | 1309-37-1 | >= 0 - < 10 |

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

| | | |
|-----------------------|------------|-------------|
| Tartaric acid | 87-69-4 | >= 1 - < 3 |
| Limestone | 1317-65-3 | >= 1 - <= 7 |
| Gypsum (Ca(SO4).2H2O) | 13397-24-5 | >= 1 - <= 3 |
| Titanium dioxide | 13463-67-7 | >= 1 - <= 3 |

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : After inhalation of dust.
Keep patient calm, remove to fresh air.
If difficulties occur:
Seek medical attention.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

Carbon dioxide (CO₂)
Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralize with acid.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
 Date of first issue: 04/29/2020

Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.
 Segregate from acids and bases.
 Segregate from oxidants.
 Segregate from foods and animal feeds.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---------------|-----------|-------------------------------------|--|--------------------------------|
| calcium oxide | 1305-78-8 | TWA value | 2 mg/m ³ | ACGIHTLV |
| | | REL value | 2 mg/m ³ | NIOSH |
| | | PEL | 5 mg/m ³ | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value | 5 mg/m ³ | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA | 2 mg/m ³ | ACGIH |
| | | TWA | 2 mg/m ³ | NIOSH REL |
| | | TWA | 5 mg/m ³ | OSHA Z-1 |
| Iron oxide | 1309-37-1 | TWA value (Respirable fraction) | 5 mg/m ³ | ACGIHTLV |
| | | REL value (Dust and fume) | 5 mg/m ³ (iron (Fe)) | NIOSH |
| | | PEL (fumes/smoke) | 10 mg/m ³ | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (fumes/smoke) | 10 mg/m ³ | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA (Respirable particulate matter) | 5 mg/m ³ | ACGIH |
| | | TWA (dust and fume) | 5 mg/m ³ (Iron) | NIOSH REL |
| | | TWA | 10 mg/m ³ | OSHA Z-1 |

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
 Date of first issue: 04/29/2020

| | | | | |
|-----------------------|------------|---------------------------------|------------------------------|--------------------------------|
| | | (Fumes) | | |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Fumes) | 10 mg/m3 | OSHA P0 |
| Limestone | 1317-65-3 | REL value (Respirable) | 5 mg/m3 | NIOSH |
| | | REL value (Total) | 10 mg/m3 | NIOSH |
| | | PEL (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA value (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA (Respirable) | 5 mg/m3 (Calcium carbonate) | NIOSH REL |
| | | TWA (total) | 10 mg/m3 (Calcium carbonate) | NIOSH REL |
| Gypsum (Ca(SO4).2H2O) | 13397-24-5 | TWA value (Inhalable fraction) | 10 mg/m3 | ACGIHTLV |
| | | REL value (Respirable) | 5 mg/m3 | NIOSH |
| | | REL value (Total) | 10 mg/m3 | NIOSH |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | PEL (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
 Date of first issue: 04/29/2020

| | | | | |
|------------------|------------|------------------------------------|-------------------------------|--------------------------------|
| | | TWA value (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA (Respirable) | 5 mg/m3 | NIOSH REL |
| | | TWA (total) | 10 mg/m3 | NIOSH REL |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA (Inhalable particulate matter) | 10 mg/m3 (Calcium) | ACGIH |
| Titanium dioxide | 13463-67-7 | TWA value | 10 mg/m3 | ACGIHTLV |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Total dust) | 10 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 10 mg/m3 | OSHA P0 |
| | | TWA | 10 mg/m3 (Titanium dioxide) | ACGIH |
| Quartz (SiO2) | 14808-60-7 | TWA value (Respirable fraction) | 0.025 mg/m3 | ACGIHTLV |
| | | TWA value (Respirable dust) | 0.05 mg/m3 | 29 CFR 1910.1001-1050 |
| | | OSHA Action level | 0.025 mg/m3 (Respirable dust) | 29 CFR 1910.1001-1050 |
| | | REL value (Respirable dust) | 0.05 mg/m3 | NIOSH |
| | | TWA (Respirable dust) | 0.05 mg/m3 | OSHA Z-1 |
| | | TWA (respirable) | 10 mg/m3 / %SiO2+2 | OSHA Z-3 |
| | | TWA (respirable) | 250 mppcf / %SiO2+5 | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 0.1 mg/m3 | OSHA P0 |
| | | TWA (Respirable par- | 0.025 mg/m3 (Silica) | ACGIH |

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
 Date of first issue: 04/29/2020

| | | | | |
|-----------------------------|------------|-------------------------------------|--|--------------------------------|
| | | ticulate matter) | | |
| | | PEL (respirable) | 0.05 mg/m3 | OSHA CARC |
| | | TWA (Respirable dust) | 0.05 mg/m3 (Silica) | NIOSH REL |
| Cement, portland, chemicals | 65997-15-1 | TWA value (Respirable fraction) | 1 mg/m3 | ACGIHTLV |
| | | REL value (Total) | 10 mg/m3 | NIOSH |
| | | REL value (Respirable) | 5 mg/m3 | NIOSH |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | PEL (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Total dust) | 10 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA value (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA value | 50 millions of particles per cubic foot of air | 29 CFR 1910.1000 (Table Z-3) |
| | | TWA (Respirable particulate matter) | 1 mg/m3 | ACGIH |
| | | TWA (Respirable) | 5 mg/m3 | NIOSH REL |
| | | TWA (total) | 10 mg/m3 | NIOSH REL |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 10 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA (Dust) | 50 Million particles per cubic foot | OSHA Z-3 |

Engineering measures : Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection : Breathing protection if dusts are formed.
 Wear a NIOSH-certified (or equivalent) particulate respirator.

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.
Avoid inhalation of dusts.
In order to prevent contamination while handling, closed working clothes and working gloves should be used.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : gray

Odor : earthy

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : approx. 12 - 13
(as aqueous suspension)

Melting temperature : > 1,832 °F / > 1,000 °C

boiling temperature : Not applicable

Flash point : does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not flammable

Upper explosion limit / Upper flammability limit : As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

- Lower explosion limit / Lower flammability limit : As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
- Vapor pressure : No applicable information available.
- Relative vapor density : No applicable information available.
- Relative density : No applicable information available.
- Bulk density : approx. 1,800 - 2,400 kg/m³
- Solubility(ies)
Water solubility : dispersible (68 °F / 20 °C)
Solubility in other solvents : No applicable information available.
- Partition coefficient: n-octanol/water : Not applicable
- Autoignition temperature : No applicable information available.
- Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.
- Viscosity
Viscosity, dynamic : Not applicable
Viscosity, kinematic : Not applicable
- Explosive properties : Not explosive
Not explosive
- Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.
- Self-heating substances : No data available
- Sublimation temperature : No applicable information available.
- Molecular weight : No data available.

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.
- Chemical stability : The product is stable if stored and handled as prescribed/indicated.
- Possibility of hazardous reac- : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

tions

- Conditions to avoid : See SDS section 7 - Handling and storage.
- Incompatible materials : Strong bases
Strong acids
- Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.
-

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicolo-

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

gy have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable for inorganic substances.

Components:

sodium carbonate:

Biodegradability : Remarks: Not applicable

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to its consistency and insolubility in water.

Components:

sodium carbonate:

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

Mobility in soil

Product:

Distribution among environmental compartments : Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.
The substance will not evaporate into the atmosphere from the water surface.

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.
The product has not been tested. The statements on ecotoxi-

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

ology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

| | |
|---|------------|
| Limestone | 1317-65-3 |
| Gypsum (Ca(SO ₄).2H ₂ O) | 13397-24-5 |
| Titanium dioxide | 13463-67-7 |
| Cement, portland, chemicals | 65997-15-1 |
| crystalline silica | 14808-60-7 |

New Jersey Right To Know

| | |
|-----------------------------|------------|
| Limestone | 1317-65-3 |
| Titanium dioxide | 13463-67-7 |
| Cement, portland, chemicals | 65997-15-1 |
| crystalline silica | 14808-60-7 |

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|-----------------|--|--|
| HEALTH | | |
| FLAMMABILITY | | |
| PHYSICAL HAZARD | | |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- 29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



Version 1.1 Revision Date: 01/05/2021 SDS Number: 000000260230 Date of last issue: 04/29/2020
Date of first issue: 04/29/2020

| | |
|--|---|
| OSHA Z-1 | : 1910.1000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3 | : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| 29 CFR 1910.1000 (Table Z-1-A) / TWA value | : Time Weighted Average (TWA): |
| 29 CFR 1910.1000 (Table Z-1) / PEL | : Permissible exposure limit |
| 29 CFR 1910.1000 (Table Z-3) / TWA value | : Time Weighted Average (TWA): |
| 29 CFR 1910.1001-1050 / OSHA Action level | : OSHA Action level: |
| 29 CFR 1910.1001-1050 / TWA value | : Time Weighted Average (TWA): |
| ACGIH / TWA | : 8-hour, time-weighted average |
| ACGIHTLV / TWA value | : Time Weighted Average (TWA): |
| NIOSH / REL value | : Recommended exposure limit (REL): |
| NIOSH REL / TWA | : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA CARC / PEL | : Permissible exposure limit (PEL) |
| OSHA P0 / TWA | : 8-hour time weighted average |
| OSHA Z-1 / TWA | : 8-hour time weighted average |
| OSHA Z-3 / TWA | : 8-hour time weighted average |

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;

SAFETY DATA SHEET

SikaTop-500 Seal grey Formerly MSeal 500 gry



| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/29/2020 |
| 1.1 | 01/05/2021 | 000000260230 | Date of first issue: 04/29/2020 |

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/05/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN