

PRODUCT DATA SHEET

Sarnacol®-2175 Cleaner

Canister adhesive cleaner

PRODUCT DESCRIPTION

Sarnacol®-2175 Cleaner is a canister adhesive cleaner

USES

Used to flush and clean the Sarnacol 2175 spray hose, spray gun and spray tip.

CHARACTERISTICS / ADVANTAGES

- Specially formulated for use with Sarnacol 2175 membrane adhesive
- Packaged in a canister with a compatible outlet to connect to the Sarnacol 2175 spray hose
- Fast drying

PRODUCT INFORMATION

Chemical Base	Liquid
Packaging	Canister in carton, 15 lbs (6.8 kg), 90 cartons per pallet
Appearance / Color	Clear
Shelf Life	12 months if stored properly in original unopened, sealed, and undamaged packaging.
Storage Conditions	Store canisters on pallets away from outside walls and off concrete floors between 50°F (10°C) and 90°F (38°C). Do not store in direct sunlight. Contents are extremely flammable. Store in accordance with local, state, and federal regulations.
Volatile organic compound (VOC) content	0 g/L*
	* The U.S. EPA, SCAQMD and others consider the solvent in Sarnacol 2175 Cleaner as "exempt", and therefore the product's VOC content can be considered "0 g/L" and used in all jurisdictions operating under these guidelines.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

AVAILABILITY/WARRANTY

AVAILABILITY

From Authorized Applicators when used within Sarnafil or Sikaplan roofing and waterproofing systems.

LIMITATIONS

Precautions should be taken to prevent odors and/or vapors from entering the building/structure, including but not limited to turning off and sealing air intake vents or other means of ingress for odors and/or vapors into the building/structure during product application and cure. Avoid ignition source.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

- Close the Sarnacol 2175 canister valve by turning the valve clockwise.
- 2. Press the spray gun trigger to dispense the residual adhesive into a suitable waste container and relieve pressure from the spray hose.
- 3. Slowly disconnect the spray hose from the Sarnacol 2175 canister using an adjustable wrench. Allow any remaining pressure to vent before removing the spray hose. Wipe any residual wet adhesive with shop towels before it dries.
- 4. Remove the protective cap from the Sarnacol 2175 Cleaner canister outlet and immediately connect the spray hose to the outlet to prevent the adhesive from drying in the spray hose. Tighten the connection with an adjustable wrench. Use caution not to strip threads or overtighten the connection.
- 5. Make sure the adjustment wheel behind the spray gun trigger is closed to prevent accidental spray.
- 6. Slowly turn the Sarnacol 2175 Cleaner valve counterclockwise to open. Check for any leaks.
- 7. Turn the adjustment wheel behind the spray gun trigger to the open position and spray the cleaner into a designated solvent containment vessel or waste bin. Press the spray gun trigger repeatedly if the spray gun trigger is sticking.
- 8. Run the cleaner through the hose and spray gun until the cleaner runs clear.
- If necessary, allow the spray gun and spray hose to remain under pressure to dissolve any remaining adhesive buildup or particulates.
- Spray tips can be soaked separately in Sarnacol 2175
 Cleaner, MEK Substitute, or acetone. Use a small gauge wire or torch tip cleaning tool to remove clogs.
- 11. The spray gun, spray hose and spray tips are ready for future use.



DISPOSAL OF EMPTY CANISTER

- Close the Sarnacol 2175 Cleaner canister valve completely by turning the valve clockwise.
- Press the spray gun trigger to dispense residual cleaner into a suitable solvent containment vessel or waste bin and to relieve pressure from the hose.
- 3. Slowly disconnect the spray hose from the Sarnacol 2175 Cleaner outlet turning clockwise with an adjustable wrench. Allow any remaining pressure to vent before removing the spray hose.
- 4. Set the canister in a vertical position. Open the valve for 24 hours to allow any residual vapor to vent.
- 5. Punch out the pressure relief disc located under the canister collar with a non-sparking brass punch.
- 6. Dispose or recycle the canister in accordance with all applicable local, state, and federal regulations.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/group/SikaCorp/termsandconditions.html or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: +1-800-933-7452 Fax: +1-201-933-6225 usa.sika.com



Product Data Sheet Sarnacol®-2175 Cleaner June 2021, Version 01.01 020945072050000012

Sika Sarnafil

100 Dan Road Canton, MA 02021 Phone: +1 800-451-2504 Fax: +1 781-828-5365 usa.sika.com/sarnafil webmaster.sarnafil@us.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5 Fracc. Industrial Balvanera Corregidora, Queretaro C.P. 76920 Phone: 57 442 2385800

Phone: 52 442 2385800 Fax: 52 442 2250537

Sarnacol-2175Cleaner-en-US-(06-2021)-1-1.pdf

