according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

SECTION 1. IDENTIFICATION

Product name : 888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Product code : 00000000056435448

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agents, pigments

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 1B

Specific target organ toxicity:

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure (Oral)

Category 2 (Kidney)

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H335 May cause respiratory irritation.

H350 May cause cancer.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure if swallowed.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution

Components

CAS-No.	Concentration (% w/w)
107-21-1	>= 15 - < 40
68412-54-4	>= 3 - < 7
111-46-6	>= 3 - < 7
13463-67-7	>= 0.5 - < 1.5
64741-88-4	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air.

If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

If irritation develops, seek medical attention.

In case of eye contact Contact lenses should be removed. Hold eyelids open and

flush with copious amounts of clean, fresh water or a special

eyewash solution and seek medical advice.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms

and effects, both acute and

delayed

May cause respiratory irritation.

May cause cancer.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod-

ucts

fumes/smoke harmful vapours Carbon oxides nitrogen oxides carbon black

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

Personal precautions, protec-:

tive equipment and emergency procedures

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wear eye/face protection.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Pick up with suitable appliance and dispose of.

Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

The product is neither self-ignitable, nor an explosion hazard,

nor does it promote fires.

Advice on safe handling : Avoid inhalation of dusts/mists/vapours.

Avoid skin contact.

Ensure adequate ventilation.

No special measures necessary provided product is used

correctly.

Conditions for safe storage : Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		С	50 ppm 125 mg/m3	OSHA P0
Diethylene glycol	111-46-6	TWA	10 mg/m3	US WEEL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Res- pirable par-	0.2 mg/m3 (Titanium dioxide)	ACGIH

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

		ticulate mat- ter)		
		TWA (Respirable particulate matter)	2.5 mg/m3 (Titanium dioxide)	ACGIH
Distillates (petroleum), solvent- refined heavy paraffinic	64741-88-4	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : yellow

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

Odor : of glycol

Odor Threshold : not determined

pH : approx. 8.5

Melting point/freezing point : No data available

Boiling point : $> 212 \, ^{\circ}\text{F} \, / > 100 \, ^{\circ}\text{C}$

Flash point : 239 °F / 115 °C

Method: estimate

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.8

Density : 1.8 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac- :

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

Carcinogenicity

May cause cancer.

IARC Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several

ingredients, the product is estimated not to be readily biode-

gradable according to OECD classification.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available.

Discharge into the environment must be avoided.

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxi-

cology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ethylene glycol	107-21-1	5000	25601

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethylene glycol 107-21-1 >= 15 - < 40 %

Nonylphenol, 68412-54-4 >= 3 - < 7 %

branched, ethox-

ylated

US State Regulations

Pennsylvania Right To Know

ethylene glycol 107-21-1 Diethylene glycol 111-46-6 Titanium dioxide 13463-67-7

New Jersey Right To Know

ethylene glycol 107-21-1
Titanium dioxide 13463-67-7
Distillates (petroleum), solvent-refined heavy paraffinic 64741-88-4
Distillates (petroleum), solvent-refined light paraffinic 64741-89-5

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and

ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit : 8-hour time weighted average

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-

according to the OSHA Hazard Communication Standard



888-1810C YELLOW OXIDE YELLOW OXIDE 8881810C

Version Revision Date: SDS Number: Date of last issue: 09/21/2020 2.0 07/03/2024 000000268957 Date of first issue: 09/21/2020

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/03/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN