

# SYSTEM DATA SHEET

# PAREX® Armourwall CI Stucco

### Continously Insulated Stucco System

#### PRODUCT DESCRIPTION


PAREX® Armourwall CI Stucco is a portland cement plaster system that incorporates continuous rigid insulation, helping designers meet today's code requirements and provides a durable exterior stucco façade with unique, refined aesthetic appeal.

#### **USES**

For exterior walls in new and retrofit commercial, institutional and residential construction when a continuous high effective R-value is needed to meet energy or eco-efficiency standards, and/or when a rainscreen is desired or required to satisfy code issues related to drainage.

## **CHARACTERISTICS / ADVANTAGES**

- For use on non-combustible construction types
- For use with fire resistance rated walls
- Continuous insulation



System Data Sheet
PAREX® Armourwall CI Stucco
June 2025, Version 01.01
021830950000242577

#### SYSTEM INFORMATION

Compatibility	Material substitution will adversely affect system performance and will void all warranty coverage unless approved in writing by Sika Facades Technical
	Service Team.

#### APPLICATION INFORMATION

Substrates	Acceptable Substrates:	
	Glass mat gypsum Sheathing	
	Gypsum sheathing	
	Exposure 1 OSB	
	Cement Boatrd Sheathing	
	Pured Concrete & Concrete Masonry	
	Exposre 1 Exterior Plywood	

#### **BASIS OF PRODUCT DATA**

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

#### **LIMITATIONS**

- Users must read the most current Product Data Sheets for each system component before using any products and follow all application instructions.
- Refer to Parex Technical Bulletin Key Detail Considerations for Insulated Stucco Systems for allowable continous insulation thicknessses.
- Contact SIKA Facades' Technical Service Department at 1-800-226-2424 for additional information.

#### **ENVIRONMENTAL, HEALTH AND SAFETY**

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

#### LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at

usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/group/SikaCorp/termsandconditions.html or by calling 1-800-933-7452.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

**System Data Sheet** 

PAREX® Armourwall CI Stucco
June 2025, Version 01.01
021830950000242577



PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at usa.sika.com.

#### Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: +1-800-933-7452 Fax: +1-201-933-6225 usa.sika.com



System Data Sheet
PAREX® Armourwall CI Stucco
June 2025, Version 01.01
021830950000242577

PAREXArmourwallCIStucco-en-US-(06-2025)-1-1.pdf

