

Revision Date 06/23/2023

### **SECTION 1. IDENTIFICATION**

Product name : Sikafloor® Marine-570 Part A

Company name : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on

use

: For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Mixtures**

#### Components

Chemical name	CAS-No.	Classification	Concentra-
			tion (% w/w)
barium sulfate	7727-43-7		>= 10 - < 20
Talc	14807-96-6		>= 5 - < 10

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**



Revision Date 06/23/2023 Print Date 06/23/20

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

No information available.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

No known significant effects or hazards.

Never give anything by mouth to an unconscious person.

Most important symptoms

delayed

Notes to physician Treat symptomatically.

and effects, both acute and

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Local authorities should be advised if significant spillages **Environmental precautions** 

cannot be contained.

Methods and materials for

containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products.



Revision Date 06/23/2023 Print Date 06/23/2023

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

Materials to avoid : No special restrictions on storage with other products.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
barium sulfate	7727-43-7	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
Talc	14807-96-6	TWA (Dust)	20 Million parti- cles per cubic foot	OSHA Z-3
		TWA (respir- able dust fraction)	2 mg/m3	OSHA P0
		TWA (Res- pirable par- ticulate mat- ter)	2 mg/m3	ACGIH
		PEL (respir- able)	0.05 mg/m3	OSHA CARC

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.



Revision Date 06/23/2023

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : various

Odor : characteristic

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : ca.  $212 \,^{\circ}\text{F} / 100 \,^{\circ}\text{C}$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available



Revision Date 06/23/2023

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.32 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : 2 g/l

(VOC) content A+B Combined

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.



Revision Date 06/23/2023

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

OSHA specifically regulated carcinogen

Talc (Mg3H2(SiO3)4) 14807-96-6

(crystalline silica)

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.



Revision Date 06/23/2023

Print Date 06/23/2023

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

**IATA-DGR** 

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

**Domestic regulation** 

**49 CFR** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

TSCA list : All chemical substances in this product are either listed as ac-

tive on the TSCA Inventory or are in compliance with a TSCA

Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **CERCLA Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards



Revision Date 06/23/2023 Print Date 06/23/2023

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### California Prop. 65

⚠

**WARNING:** This product can expose you to chemicals including Talc, which is known to the State of California to cause cancer, and benzene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average OSHA CARC / PEL : Permissible exposure limit (PEL) OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

#### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 06/23/2023

# Safety Data Sheet

# Sikafloor® Marine-570 Part A



Revision Date 06/23/2023

100000017945 US / Z8