## Sikagard-300 KNS SB Formerly MKure CC 300SB



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

#### **SECTION 1. IDENTIFICATION**

Product name : Sikagard-300 KNS SB Formerly MKure CC 300SB

Product code : 00000000051678751

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

FLAMMABLE LIQUIDS : 3

Skin corrosion/irritation : 2

Serious eye damage/eye

irritation

Category 2A

Carcinogenicity : 2

Reproductive toxicity : 1B

Specific target organ toxicity

- single exposure

3 (Respiratory system)

Long-term (chronic) aquatic

hazard

: 2

**GHS label elements** 

Hazard pictograms







Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation. H351 Suspected of causing cancer. H360D May damage the unborn child.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements**

#### Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust or mist.

P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.

P264 Wash face, hands and any exposed skin thoroughly after handling.

P242 Use only non-sparking tools.

P240 Ground and bond container and receiving equipment.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

P362 + P364 Take off contaminated clothing and wash it before reuse

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P233 Keep container tightly closed.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

## Sikagard-300 KNS SB Formerly MKure CC 300SB



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
solvent naphtha	64742-95-6	>= 25 - < 50
1,2,4-trimethylbenzene	95-63-6	>= 25 - < 50
mesitylene	108-67-8	>= 5 - < 7
cumene	98-82-8	>= 1 - < 3
xylene	1330-20-7	>= 1 - < 3
Diethylbenzene	25340-17-4	>= 1 - < 3
,	71888-89-6	>= 1 - < 3
8-branched alkylesters, C7-rich		
ethylbenzene	100-41-4	>= 0.3 - < 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Immediately wash thoroughly with soap and water, seek med-

ical attention.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.
May damage the unborn child.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapors accumulating to form explosive concentra-





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

tions. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : no smoking

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

Keep away from heat.

Avoid all sources of ignition: heat, sparks, open flame.

Materials to avoid : Segregate from foods and animal feeds.

Further information on stor-

age stability

No decomposition if stored and applied as directed.



# Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,2,4-trimethylbenzene	95-63-6	TWA value	25 ppm	ACGIHTLV
1,2,4-uimeuryiberizerie	33 03 0	REL value	25 ppm	NIOSH
			125 mg/m3	
		TWA value	25 ppm	29 CFR
			125 mg/m3	1910.1000
				(Table Z-1-A)
		TWA	25 ppm	NIOSH REL
			125 mg/m3	
		TWA	25 ppm	ACGIH
		TWA	25 ppm	OSHA P0
			125 mg/m3	
cumene	98-82-8	TWA value	50 ppm	ACGIHTLV
		REL value	50 ppm	NIOSH
			245 mg/m3	
		PEL	50 ppm	29 CFR
			245 mg/m3	1910.1000
				(Table Z-1)
		TWA value	50 ppm	29 CFR
			245 mg/m3	1910.1000
				(Table Z-1-A)
		TWA	50 ppm	ACGIH
		TWA	50 ppm	NIOSH REL
			245 mg/m3	
		TWA	50 ppm	OSHA Z-1
			245 mg/m3	
		TWA	50 ppm	OSHA P0
			245 mg/m3	
mesitylene	108-67-8	TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm	NIOSH
			125 mg/m3	
		TWA value	25 ppm	29 CFR
			125 mg/m3	1910.1000
				(Table Z-1-A)
		TWA	25 ppm	NIOSH REL
			125 mg/m3	
		TWA	25 ppm	ACGIH
		TWA	25 ppm	OSHA P0
			125 mg/m3	
xylene	1330-20-7	TWA value	100 ppm	ACGIHTLV
		STEL value	150 ppm	ACGIHTLV
		PEL	100 ppm	29 CFR
			435 mg/m3	1910.1000
				(Table Z-1)
		TWA value	100 ppm	29 CFR
			435 mg/m3	1910.1000





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

		(Table Z-1-A)
STEL value	150 ppm	29 CFR
	655 mg/m3	1910.1000
		(Table Z-1-A)
REL value	100 ppm	NIOSH
	435 mg/m3	
STEL value	150 ppm	NIOSH
	655 mg/m3	
TWA	100 ppm	OSHA Z-1
	435 mg/m3	
TWA	100 ppm	ACGIH
STEL	150 ppm	ACGIH
STEL	150 ppm	OSHA P0
	655 mg/m3	
TWA	100 ppm	OSHA P0
	435 mg/m3	

**Engineering measures** : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Avoid inhalation of dusts/mists/vapours.

Avoid contact with the skin, eyes and clothing.

Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid



## Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

Color : clear

pH : not applicable

Boiling point : No applicable information available.

Flash point : 100.00 °F / 37.78 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 0.91

Density : 0.91 g/cm3 (68 °F / 20 °C)

Bulk density : not applicable

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No data available.

Autoignition temperature : No data available

Decomposition temperature : Vapors may form explosive mixture with air.

No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available.

Viscosity, kinematic : 71 mm2/s (104 °F / 40 °C)

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

## Sikagard-300 KNS SB Formerly MKure CC 300SB



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available.

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified based on available information.

## Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

# Sikagard-300 KNS SB Formerly MKure CC 300SB



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

May damage the unborn child.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

#### **Product:**

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

The product has not been tested. The statement has been derived from the properties of the individual components.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Product:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## Persistence and degradability

No data available

#### Bioaccumulative potential

#### Components:

#### solvent naphtha:

Partition coefficient: n- : log Pow: 3.17

octanol/water Method: other (calculated)

GLP: no

#### 1,2,4-trimethylbenzene:

Partition coefficient: n- : log Pow: 3.63 (77 °F / 25 °C) octanol/water : Method: other (calculated)

## mesitylene:



## Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

Partition coefficient: nlog Pow: 3.42

Method: other (measured) octanol/water

cumene:

Partition coefficient: nlog Pow: 3.55 (73 °F / 23 °C)

Method: Partition coefficient (n-octanol/water), Shake-flask octanol/water

method

xylene:

Partition coefficient: nlog Pow: 3.12 - 3.20 (77 °F / 25 °C)

octanol/water Method: other (calculated)

GLP: no

Remarks: Information taken from reference works and the

literature.

1,2-benzenedicarboxylic acid; di-C6-8-branched alkylesters, C7-rich:

Partition coefficient: n-

octanol/water

Remarks: No data available.

ethylbenzene:

Pow: 4,170 (68 °F / 20 °C) Partition coefficient: noctanol/water log Pow: 3.6 (68 °F / 20 °C)

pH: 7.8

Method: Partition coefficient

GLP: yes

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.



## Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

**UNRTDG** 

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

**IATA-DGR** 

UN/ID No. : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III

Labels : Flammable Liquids

366

Packing instruction (cargo

aircraft)

Packing instruction (passen: 355

ger aircraft)

**IMDG-Code** 

UN number : UN 1263 Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 1263

Proper shipping name : PAINT, COMBUSTIBLE LIQUID

Class : C Packing group : III

Labels : Combustible Liquid

ERG Code : 128 Marine pollutant : no

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**



## Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

1,2,4- 95-63-6

trimethylbenzene

cumene 98-82-8

xylene 1330-20-7

ethylbenzene 100-41-4

### **US State Regulations**

## Pennsylvania Right To Know

 1,2,4-trimethylbenzene
 95-63-6

 cumene
 98-82-8

 mesitylene
 108-67-8

 xylene
 1330-20-7

 bis(2-propylheptyl) phthalate
 53306-54-0

 Solvent naphtha (petroleum), light arom.
 64742-95-6

#### **New Jersey Right To Know**

 1,2,4-trimethylbenzene
 95-63-6

 xylene
 1330-20-7

 Diethylbenzene
 25340-17-4

 Solvent naphtha (petroleum), light arom.
 64742-95-6

 ethylbenzene
 100-41-4

 styrene
 100-42-5

 cumene
 98-82-8

### California Prop. 65

WARNING: This product can expose you to chemicals including cumene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

### **SECTION 16. OTHER INFORMATION**

#### **Further information**




## Sikagard-300 KNS SB Formerly MKure CC 300SB



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

#### NFPA 704:



Special hazard

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

1)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV** 

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH NIOSH REL USA. NIOSH Recommended Exposure Limits

OSHA P0 USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Short Term Exposure Limit (STEL):

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit

ACGIHTLV / STEL value Short Term Exposure Limit (STEL): Time Weighted Average (TWA): ACGIHTLV / TWA value NIOSH / REL value Recommended exposure limit (REL): NIOSH / STEL value Short Term Exposure Limit (STEL):

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA 8-hour time weighted average OSHA P0 / STEL Short-term exposure limit OSHA Z-1 / TWA 8-hour time weighted average



## Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 07/15/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE



## Sikagard-300 KNS SB Formerly MKure CC 300SB

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261384 Date of first issue: 07/15/2020

MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN