

- 1) WOOD NAILERS OR WOOD BLOCKING FOR PENETRATIONS, CURBS, OR SNOW PROTECTION SYSTEMS SHALL BE INSTALLED PRIOR TO THE INSTALLATION OF THE ROOF MEMBRANE WHENEVER POSSIBLE.
- 2) VAPOR RETARDER SHALL BE SEALED AT EDGES.
- CONTINUOUS CLEAT IS REQUIRED IF FACE DIMENSION OF FASCIA EXCEEDS 3".
- 4) FACE DIMENSION OF FASCIA SHALL BE A MINIMUM OF 3" OR AS OTHERWISE REQUIRED TO EXTEND A MINIMUM OF 1-1/2" BELOW BOTTOM OF WOOD NAILER.
- 5) THE HORIZONTAL FLANGE OF FASCIA SHALL BE A MINIMUM OF 4" WIDE.
- 6) FASCIA MY BE FORMED WITH A OPTIONAL WATER DAM/GRAVEL STOP.
- 7) NAILS USED TO ATTACH EITHER THE CONTINUOUS CLEAT OR FASCIA SHALL PENETRATE THE NAILER A MINIMUM OF 1-1/2". SCREWS SHALL PENETRATE A MINIMUM OF 1".

<u>SIKAPLAN SARNACLAD</u> METAL EDGE

