Revision Date 03/10/2021



SECTION 1. IDENTIFICATION

Product name	:	Sikafloor [®] NA PurCem [®] Part B	
Company name	:	Sika Corporation	
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com	
Telephone	:	(201) 933-8800	
Telefax	:	(201) 804-1076	
E-mail address	:	ehs@sika-corp.com	
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887	
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.	

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

:	Category 4
:	Category 2
:	Category 2B
:	Category 1
:	Category 1
:	Category 3 (Respiratory system)
:	Category 2
:	
	::



Revision Date 03/10/2021	Print Date 03/1
Signal Word :	Danger
Hazard Statements :	 H315 + H320 Causes skin and eye irritation. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary Statements :	Prevention: P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves. P284 Wear respiratory protection.
	 Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. P362 + P364 Take off contaminated clothing and wash it before reuse.
	Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
	Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

Revision Date 03/10/2021



SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 50 - < 70
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 30 - < 50
o-(p-isocyanatobenzyl)phenyl isocy- anate	5873-54-1	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.	
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.	
3/12			

Revision Date 03/10/2021



	Obtain medical attention.
Most important symptoms and effects, both acute and delayed	irritant effects sensitizing effects Asthmatic appearance Cough Respiratory disorder Allergic reactions Headache Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician :	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Revision Date 03/10/2021



Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Advice on safe handling	:	 Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products. 	
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.005 ppm	ACGIH
		С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Revision Date 03/10/2021



Personal protective equipmen	t
Respiratory protection :	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection :	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures :	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	amber
Odor	:	musty
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	424 °F / 218 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available

Revision Date 03/10/2021



Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapor pressure	:	0.01 hpa	
Relative vapor density	:	No data available	
Density	:	1.2 g/cm3	
Solubility(ies) Water solubility	:	soluble	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Autoignition temperature	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	> 20.5 mm2/s (104 °F / 40 °C)	
Explosive properties	:	No data available	
Oxidizing properties	:	No data available	
Volatile organic compounds (VOC) content	:	5 g/l Sikafloor® NA PurCem® Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-19 NA PurCem® Part C Combined.	
		5 g/l Sikafloor®-19-31 NA PurCem® FS Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-19 NA PurCem® Part C Com- bined.	
		5 g/l Sikafloor® NA PurCem® Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-22 NA PurCem® Part C Combined.	
		5 g/l Sikafloor®-19-31 NA PurCem® FS Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-22 NA PurCem® Part C Com- bined.	
		5 g/l Sikafloor® NA PurCem® Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-24 NA PurCem® Part C Combined.	

Revision Date 03/10/2021



5 g/l Sikafloor®-19-31 NA PurCem® FS Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-24 NA PurCem® Part C Combined. 5 g/l Sikafloor® NA PurCem® Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-29 NA PurCem® Part C Combined. 5 a/l Sikafloor®-19-31 NA PurCem® FS Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-29 NA PurCem® Part C Combined. 13 g/l Sikafloor® NA PurCem® Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-31 NA PurCem® Part C Combined. 13 g/l Sikafloor®-19-31 NA PurCem® FS Part A + Sikafloor® NA PurCem® Part B + Sikafloor®-31 NA PurCem® Part C Combined.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): > 4,700 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1.5 mg/l Exposure time: 4 h

Revision Date 03/10/2021



Test atmosphere: dust/mist Method: Expert judgment

	-	, isomeres and homologues:			
Acute oral toxicit	ty :	LD50 Oral (Rat): > 10,000 mg/kg			
Acute inhalation	toxicity :	LC50: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Assessment: The component/mixture is moderately toxic after short term inhalation.			
Acute dermal to	xicity :	LD50 Dermal (Rabbit): > 9,400 mg/kg			
Skin corrosion/	<i>'irritation</i>				
Causes skin irrit	ation.				
Serious eye damage/eye irritation Causes eye irritation.					
Respiratory or	Respiratory or skin sensitization				
Skin sensitization					
May cause an al	May cause an allergic skin reaction.				
Respiratory sensitization					
May cause allergy or asthma symptoms or breathing difficulties if inhaled.					
Germ cell mutagenicity					
Not classified based on available information.					
Carcinogenicity					
Not classified based on available information. IARC Not applicable					
OSHA	Not applicable				
NTP	Not applicable				
Reproductive to	oxicity				
Not classified based on available information.					
STOT-single ex	posure				
May cause respiratory irritation.					
STOT-repeated exposure					
May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.					

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

Revision Date 03/10/2021



SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity					
Components:					
Diphenylmethanediisocyanate	, isomeres and homologues:				
Toxicity to fish :	LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l Exposure time: 96 h				
Toxicity to algae/aquatic : plants	EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l				
Persistence and degradability No data available					
Bioaccumulative potential No data available					
Mobility in soil No data available					
Other adverse effects					
Product: Additional ecological infor- : mation	Do not empty into drains; dispose of this material and its con- tainer in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.				

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Revision Date 03/10/2021



Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

```
TSCA list
```

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	Respiratory or sk Specific target or Skin corrosion or	gan toxicity (single or	repeated exposure)
SARA 313	The following components are subject to reporting levels es- tablished by SARA Title III, Section 313:		
	4,4'- methylenediphe- nyl diisocyanate	101-68-8	>= 50 - < 70 %
	Diphenylme- thanediisocya- nate, isomeres and homologues	9016-87-9	>= 30 - < 50 %
Clean Air Act			
The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61): 4,4'-methylenediphenyl 101-68-8 >= 50 - < 70 % diisocyanate			
California Prop 65 :			icals known to the State ny other reproductive

SECTION 16. OTHER INFORMATION

Full text of other abbreviati	ons	
ACGIH	:	USA. ACGIH Threshold Limit Values

(TLV)

Revision Date 03/10/2021



OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA OSHA P0 / C OSHA Z-1 / C	:	8-hour, time-weighted average Ceiling limit Ceiling

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/10/2021

10000003529 US / Z8