

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

Version 2.0 Revision Date: 06/13/2024 SDS Number: 000000298893 Date of last issue: 07/22/2020
Date of first issue: 07/22/2020

SECTION 1. IDENTIFICATION

Product name : Sikalastic-310 Formerly MSeal 610

Product code : 00000000056434070

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION


GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity
- repeated exposure (Inhalation) : Category 1 (Lungs)

Specific target organ toxicity
- repeated exposure (Inhalation) : Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

Version 2.0 Revision Date: 06/13/2024 SDS Number: 000000298893 Date of last issue: 07/22/2020
Date of first issue: 07/22/2020

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|----------------------------|------------|-----------------------|
| Asphalt | 8052-42-4 | >= 35 - < 45 |
| Quartz (SiO ₂) | 14808-60-7 | >= 1 - < 5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Remove contact lenses, if present.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do NOT induce vomiting.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

Most important symptoms and effects, both acute and delayed : May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure if inhaled. Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides

Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

Version 2.0 Revision Date: 06/13/2024 SDS Number: 000000298893 Date of last issue: 07/22/2020
Date of first issue: 07/22/2020

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Spilled product should be disposed in accordance with all applicable government regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid aerosol formation.
Avoid inhalation of mists/vapours.
Avoid skin contact.
Avoid contact with eyes.

Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Recommended storage temperature : 50 - 109 °F / 10 - 43 °C

Further information on storage stability : PROTECT FROM FREEZING.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------------|------------|--------------------------------|---|-----------|
| Asphalt | 8052-42-4 | TWA (Fume, inhalable fraction) | 0.5 mg/m ³ (benzene soluble aerosol) | ACGIH |
| | | C (Fumes) | 5 mg/m ³ | NIOSH REL |
| Quartz (SiO ₂) | 14808-60-7 | TWA (Respirable dust) | 0.05 mg/m ³ | OSHA Z-1 |
| | | TWA (respirable) | 10 mg/m ³ / %SiO ₂ +2 | OSHA Z-3 |
| | | TWA (respirable) | 250 mppcf / %SiO ₂ +5 | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 0.1 mg/m ³ | OSHA P0 |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

Version 2.0 Revision Date: 06/13/2024 SDS Number: 000000298893 Date of last issue: 07/22/2020
Date of first issue: 07/22/2020

| | | | | |
|--|--|-------------------------------------|----------------------|-----------|
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| | | TWA (Respirable dust) | 0.05 mg/m3 (Silica) | NIOSH REL |
| | | PEL (respirable) | 0.05 mg/m3 | OSHA CARC |

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : brown

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

Odor : mild, of petroleum

Odor Threshold : not determined

pH : 6 - 9

Melting point/freezing point : No data available

Boiling point/boiling range : 212 °F / 100 °C

Flash point : > 212 °F / > 100 °C

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : approx. 60 mmHg (100 °F / 38 °C)

Relative vapor density : No data available

Relative density : 1 - 1.2

Density : 9.2 lb/USg

Solubility(ies)
Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : > 400 °F / > 204 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : 100,000 cps (77 °F / 25 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

| | | |
|----------------------|---|--|
| Oxidizing properties | : | Based on its structural properties the product is not classified as oxidizing. |
| Sublimation point | : | No data available |
| Molecular weight | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|---|
| Reactivity | : | No hazardous reactions if stored and handled as prescribed/indicated. |
| Chemical stability | : | The product is stable if stored and handled as prescribed/indicated. |
| Possibility of hazardous reactions | : | The product is stable if stored and handled as prescribed/indicated. |
| Conditions to avoid | : | Avoid extreme heat. |
| Incompatible materials | : | Strong oxidizing agents |
| Hazardous decomposition products | : | Sulfur oxides Carbon monoxide Carbon dioxide (CO ₂) Hydrocarbons |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

| | | |
|-------------|---|------------|
| IARC | Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline) | 14808-60-7 |
| | Group 2B: Possibly carcinogenic to humans Asphalt (Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving) | 8052-42-4 |
| OSHA | OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica) | 14808-60-7 |
| NTP | Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size)) | 14808-60-7 |

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.
The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

Version 2.0 Revision Date: 06/13/2024 SDS Number: 000000298893 Date of last issue: 07/22/2020
Date of first issue: 07/22/2020

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|---------|--------------------|-----------------------------|
|------------|---------|--------------------|-----------------------------|

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

| | | | |
|---------|-----------|-----|-----|
| Asphalt | 8052-42-4 | 100 | 250 |
|---------|-----------|-----|-----|

US State Regulations

Pennsylvania Right To Know

| | |
|----------------------------|------------|
| Asphalt | 8052-42-4 |
| Quartz (SiO ₂) | 14808-60-7 |

New Jersey Right To Know

| | |
|----------------------------|------------|
| Asphalt | 8052-42-4 |
| Quartz (SiO ₂) | 14808-60-7 |

California Prop. 65

WARNING: This product can expose you to chemicals including Asphalt, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:


TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|-----------------|--|--|
| HEALTH | | |
| FLAMMABILITY | | |
| PHYSICAL HAZARD | | |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

| | |
|-----------|--|
| ACGIH | : USA. ACGIH Threshold Limit Values (TLV) |
| NIOSH REL | : USA. NIOSH Recommended Exposure Limits |
| OSHA CARC | : OSHA Specifically Regulated Chemicals/Carcinogens |
| OSHA P0 | : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/13/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic-310 Formerly MSeal 610

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07/22/2020 |
| 2.0 | 06/13/2024 | 000000298893 | Date of first issue: 07/22/2020 |

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN