



Page 1/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

#### 1 Identification

· Product identifier

· Trade name: EC433-2 Hardener

· Article number: 1433289

· Application of the substance / the mixture Epoxy resin

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Supplier's Name: Sika Advanced Resins, US

*Headquarters:* 

30800 Stephenson Hwy Madison Heights, MI 48071

USA

ehs-us@axson.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

(Contd. on page 2)



Page 2/12

### Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/16/2019 Printing date 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 1)

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS05

GHS06

GHS09 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

*4,4'-methylenebis(cyclohexylamine)* 

diethylmethylbenzenediamine

· Hazard statements

Toxic if swallowed.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

*If swallowed: Immediately call a poison center/doctor.* 

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*3

Fire = 1

(Contd. on page 3)



Page 3/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1761-71-3 EINECS: 217-168-8	4,4'-methylenebis(cyclohexylamine)	20-50%
CAS: 68479-98-1 EINECS: 270-877-4	diethylmethylbenzenediamine	≥25-≤50%

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Page 4/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 3)

- Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· *PAC-1*:

None of the ingredients is listed.

· PAC-2:

None of the ingredients is listed.

· PAC-3:

None of the ingredients is listed.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 5)

Page 5/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

9 Physical and chemical p	pro	perties
---------------------------	-----	---------

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Amber colored
Odor: Amine-like
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.

• Flash point: 141 °C (285.8 °F)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 420 °C (788 °F)

• Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapor pressure: Not determined.

• **Density at 20 °C (68 °F):** 0.98 g/cm³ (8.18 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 7)



Page 7/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

	(Contd. of	f page (
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC3	LD/LC50 values that are relevant for classification:	
Oral	LD50	625 mg/kg (rat)
Dermal	LD50	2,100 mg/kg (rabbit)

### 68479-98-1 diethylmethylbenzenediamine Oral LD50 | 738 mg/kg (rat)

Dermal | LD50 | >2,000 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Corrosive

(Contd. on page 8)



Page 8/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 7)

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

96 hr LC50 46-100 mg/l (Fish)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)





Page 9/12

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/16/2019 Printing date 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 8)

- · Uncleaned packagings: · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN2922
UN proper shipping name	
DOT IMDG	Corrosive liquids, toxic, n.o.s. (Cycloaliphatic Amine) CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amin
IATA	diethylmethylbenzenediamine), MARINE POLLUTANT CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine)
Transport hazard class(es)	
DOT	
CORROSIVE TOXIC	
Class	8 Corrosive substances
Label	8, 6.1
IMDG	
Class	8 Corrosive substances
Label	8/6.1
IATA  Solve of the second of t	
Class	8 Corrosive substances
Label	8 (6.1)
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substance diethylmethylbenzenediamine

(Contd. on page 10)



Sika ®

Page 10/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

	(Contd. of page
Marine pollutant:	Yes
•	Symbol (fish and tree)
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	86
EMS Number:	F-A,S-B
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L
Remarks:	Special marking with the symbol (fish and tree).
<i>IMDG</i>	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
1 1	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.
	(CYCLOALIPHATIC AMINE), 8 (6.1), II, ENVIRONMENTALI
	HAZARDOUS

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 10)

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS09

GHS05

GHS06

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

*4,4'-methylenebis(cyclohexylamine)* diethylmethylbenzenediamine

· Hazard statements

Toxic if swallowed.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dusts or mists.

(Contd. on page 12)



**Sika**®

Page 12/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/16/2019 Reviewed on 10/16/2019

Trade name: EC433-2 Hardener

(Contd. of page 11)

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 10/16/2019 / 3
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

\* Data some and to the annuious named and the

\* Data compared to the previous version altered.

HC