

Page 1/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

1 Identification

· Product identifier

· Trade name: EC433-4 Hardener

· Article number: 1433489

· Application of the substance / the mixture Epoxy resin

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Supplier's Name: Sika Advanced Resins, US

Headquarters:

30800 Stephenson Hwy Madison Heights, MI 48071

USA

ehs-us@axson.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard


STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



(Contd. on page 2)



Page 2/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 1)

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms











GHS05

GHS06

GHS07

GHS08

GHS09

· Signal word Danger

· Hazard-determining components of labeling:

2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

diethylmethylbenzenediamine

4,4'-methylenebis(cyclohexylamine)

1-methylimidazole

Methyleneoxide, polymer with benzenamine, hydrogenated

· Hazard statements

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

(Contd. on page 3)



Page 3/13

Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/12/2019 Printing date 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 2)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 68479-98-1 EINECS: 270-877-4	diethylmethylbenzenediamine t	≥25-≤50%	
CAS: 6864-37-5 EINECS: 229-962-1	2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	≥25-≤50%	
CAS: 1761-71-3 EINECS: 217-168-8	4,4'-methylenebis(cyclohexylamine)	5-10%	
CAS: 616-47-7 EINECS: 210-484-7	1-methylimidazole	≥1-<5%	
CAS: 135108-88-2	Methyleneoxide, polymer with benzenamine, hydrogenated	≥1-<3%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

(Contd. on page 4)

Sika®

Page 4/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 3)

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 5)



Page 5/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

· Protective Action Criteria for Chemicals	(Contd. of page 4
• PAC-1:	
6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	0.28 mg/m^3
616-47-7 1-methylimidazole	2.3 mg/m^3
· PAC-2:	<u> </u>
6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	3.1 mg/m ³
616-47-7 1-methylimidazole	25 mg/m ³
PAC-3:	
6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	19 mg/m³
616-47-7 1-methylimidazole	150 mg/m ²

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 6)





Page 6/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 5)

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Amber colored
Odor: Amine-like
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 197 °C (386.6 °F)

(Contd. on page 7)





Page 7/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

	(Contd. of pag
Flash point:	109 °C (228.2 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	275 °C (527 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.5 Vol %	
Upper:	2.8 Vol %	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	0.99 g/cm³ (8.26 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	$0.0\mathrm{g/l}/0.00\mathrm{lb/gal}$	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- $\cdot \textit{Hazardous decomposition products:} \ \textit{Carbon monoxide and carbon dioxide}$

US ·



Page 8/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 7)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:				
68479-98-1 diethylmethylbenzenediamine				
Oral	LD50	738 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rat)		
6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)				
Oral	LD50	320-460 mg/kg (rat)		
Dermal	LD50	200-400 mg/kg (rabbit)		
Inhalative	LC50/4 h	0.42 mg/l (rat) (Test Guideline 402)		

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

US





Page 9/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 8)

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

48 hr EC50 15.2 mg/l (daphnia)

96 hr LC50 | 45 mg/l (Fish)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- **DOT, IMDG, IATA** UN2922

· UN proper shipping name

• **DOT** Corrosive liquids, toxic, n.o.s. (Cycloaliphatic Amine)

(Contd. on page 10)

110





Page 10/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 9) CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine, diethylmethylbenzenediamine), MARINE POLLUTANT CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine)

· Transport hazard class(es)

 $\cdot DOT$

 \cdot IMDG

 \cdot IATA







8 Corrosive substances · Class · Label 8. 6.1

 \cdot IMDG







· Class 8 Corrosive substances · Label 8/6.1

· IATA





· Class 8 Corrosive substances · Label 8 (6.1)

· Packing group

· DOT, ĬMDG, IATA II

Product contains environmentally hazardous substances: · Environmental hazards:

diethylmethylbenzenediamine, Cycloaliphatic Amine

· Marine pollutant:

Symbol (fish and tree)

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler): 886 · EMS Number: F-A,S-B· Stowage Category В

· Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 11)



UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S.

(CYCLOALIPHATIC AMINE), 8 (6.1), II, ENVIRONMENTALLY

Page 11/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 10)

· Transport/Additional information:	
DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· Remarks:	Special marking with the symbol (fish and tree).
· IMDG	
Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

15 Regulatory information

· UN "Model Regulation":

· Safety, health and environmental regulations/legislation specific for the substance or mixture

HAZARDOUS

- ·Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 12)



Page 12/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 11)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms











GHS05 GHS06 GHS07 GHS08 GHS

· Signal word Danger

· Hazard-determining components of labeling:

2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

diethylmethylbenzenediamine

4,4'-methylenebis(cyclohexylamine)

1-methylimidazole

Methyleneoxide, polymer with benzenamine, hydrogenated

· Hazard statements

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

(Contd. on page 13)

Page 13/13

Safety Data Sheet acc. to OSHA HCS

Printing date 10/12/2019 Reviewed on 10/12/2019

Trade name: EC433-4 Hardener

(Contd. of page 12)

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 10/12/2019 / 6
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

 $Aquatic\ Acute\ 1:\ Hazardous\ to\ the\ aquatic\ environment\ -\ acute\ aquatic\ hazard\ -\ Category\ 1$

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

US ·