

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

### 1 Identification

- **Product identifier**
- **Trade name:** EC439 Resin
- **Article number:** 1439088
- **Application of the substance / the mixture** Resin
- **Details of the supplier of the safety data sheet**  
Sika Advanced Resins, US  
EHS Department
- **Manufacturer/Supplier:**  
Supplier's Name: Sika Advanced Resins, US  
Headquarters:  
30800 Stephenson Hwy  
Madison Heights, MI 48071  
USA  
  
ehs-us@axson.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (248) 588-2270  
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Repr. 1B                      H360 May damage fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1C                H314 Causes severe skin burns and eye damage.

Eye Dam. 1                 H318 Causes serious eye damage.



GHS09 Environment

Aquatic Acute 1            H400 Very toxic to aquatic life.

Aquatic Chronic 1        H410 Very toxic to aquatic life with long lasting effects.



GHS07

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

Trade name: EC439 Resin

(Contd. of page 1)

*Skin Sens. 1 H317 May cause an allergic skin reaction.*

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Trimethylol propane triglycidyl ether copolymer  
1,4-bis(2,3-epoxypropoxy)butane*

· **Hazard statements**

*Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May damage fertility or the unborn child.  
Very toxic to aquatic life.  
Very toxic to aquatic life with long lasting effects.*

· **Precautionary statements**

*Avoid breathing dust/fume/gas/mist/vapors/spray  
Do not breathe dusts or mists.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
Wash contaminated clothing before reuse.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

**Trade name:** EC439 Resin

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	50-100%
CAS: 30499-70-8	Trimethylol propane triglycidyl ether copolymer	5-10%
CAS: 2425-79-8 EINECS: 219-371-7	1,4-bis(2,3-epoxypropoxy)butane	≥5-<10%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

Trade name: EC439 Resin

(Contd. of page 3)

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	30 mg/m <sup>3</sup>
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	16 mg/m <sup>3</sup>

· **PAC-2:**

28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	330 mg/m <sup>3</sup>
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	170 mg/m <sup>3</sup>

· **PAC-3:**

28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	2,000 mg/m <sup>3</sup>
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	220 mg/m <sup>3</sup>

### 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

Trade name: EC439 Resin

(Contd. of page 4)

- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

**Trade name: EC439 Resin**

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Liquid

· **Color:** Amber colored

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/Melting range:** Undetermined.

· **Boiling point/Boiling range:** >200 °C (>392 °F)

· **Flash point:** 94 °C (201.2 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· **Lower:** Not determined.

· **Upper:** Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 1.18 g/cm<sup>3</sup> (9.85 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

Trade name: EC439 Resin

(Contd. of page 6)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - VOC content:** 10.00 %  
118.0 g/l / 0.98 lb/gal
- **Solids content:** 0.0 %
- **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**30499-70-8 Trimethylol propane triglycidyl ether copolymer**

Oral	LD50	3,398 mg/kg (rat)
Dermal	LD50	3,170 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

**Trade name: EC439 Resin**

(Contd. of page 7)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.  
 Danger to drinking water if even small quantities leak into the ground.  
 Also poisonous for fish and plankton in water bodies.  
 Very toxic for aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT** not regulated

(Contd. on page 9)



## Safety Data Sheet


acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

Trade name: EC439 Resin

(Contd. of page 8)

· <b>IMDG, IATA</b>	UN3082
· <b>UN proper shipping name</b> · <b>DOT</b> · <b>IMDG</b> · <b>IATA</b>	not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin)
· <b>Transport hazard class(es)</b> · <b>DOT</b> · <b>Class</b>	not regulated
· <b>IMDG, IATA</b> 	
· <b>Class</b> · <b>Label</b>	9 Miscellaneous dangerous substances and articles 9
· <b>Packing group</b> · <b>DOT</b> · <b>IMDG, IATA</b>	not regulated III
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b> · <b>Special marking (IATA):</b>	Product contains environmentally hazardous substances: Epoxy phenol novolac resin Yes Symbol (fish and tree) Symbol (fish and tree)
· <b>Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Stowage Category</b>	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
· <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

**Trade name: EC439 Resin**

(Contd. of page 9)

· **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN), 9, III

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

**Trade name: EC439 Resin**

(Contd. of page 10)

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05   GHS07   GHS08   GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Trimethylol propane triglycidyl ether copolymer  
1,4-bis(2,3-epoxypropoxy)butane*

· **Hazard statements**

*Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May damage fertility or the unborn child.  
Very toxic to aquatic life.  
Very toxic to aquatic life with long lasting effects.*

· **Precautionary statements**

*Do not breathe dusts or mists.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
Wash contaminated clothing before reuse.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Date of preparation / last revision** 10/12/2019 / 1

· **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances*

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/12/2019

Reviewed on 10/12/2019

**Trade name: EC439 Resin**

(Contd. of page 11)

*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMIS: Hazardous Materials Identification System (USA)*  
*VOC: Volatile Organic Compounds (USA, EU)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*NIOSH: National Institute for Occupational Safety*  
*OSHA: Occupational Safety & Health*  
*TLV: Threshold Limit Value*  
*PEL: Permissible Exposure Limit*  
*REL: Recommended Exposure Limit*  
*Skin Corr. 1C: Skin corrosion/irritation – Category 1C*  
*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*Repr. 1B: Reproductive toxicity – Category 1B*  
*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*  
*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

· **\* Data compared to the previous version altered.**

US