

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

1 Identification

· Product identifier

· Trade name: <u>EC440 Resin</u> · Article number: 1440088

· Application of the substance / the mixture Resin

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Supplier's Name: Sika Advanced Resins, US

Headquarters:

30800 Stephenson Hwy Madison Heights, MI 48071

USA

ehs-us@axson.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

-)



Page 2/12

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Reviewed on 04/03/2019 Printing date 04/03/2019

Trade name: EC440 Resin

· Hazard pictograms





GHS07

GHS09

- · Signal word Warning
- · Hazard-determining components of labeling:

1,4-bis(2,3-epoxypropoxy)butane

Reaction Product of Bisphenol A and Epichlorohydrin

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Avoid breathing dust/fume/gas/mist/vapors/spray

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)



Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	50-100%
CAS: 2425-79-8 EINECS: 219-371-7	1,4-bis(2,3-epoxypropoxy)butane	≥5-<10%
CAS: 25068-38-6 NLP: 500-033-5	Reaction Product of Bisphenol A and Epichlorohydrin	≥1-<2.5%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

US





Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 3)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

<i>PAC-1</i> :		
28064-14-4	Epoxy phenol novolac resin	30 mg/m ⁻
	Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	16 mg/m
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	90 mg/m
<i>PAC-2:</i>		
28064-14-4	Epoxy phenol novolac resin	330 mg/m
	Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	170 mg/m
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	990 mg/m
<i>PAC-3:</i>		
28064-14-4	Epoxy phenol novolac resin	2,000 mg/m
	Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	220 mg/m³
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	5,900 mg/m

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

(Contd. on page 5)



Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

α \mathbf{n}_1		7			1		. •
у Ри	บราคม	and	C	remical	nro	$n \rho v_1$	705
	youtur	with	$-\omega_{L}$	temitui.	יייייייייייייייייייייייייייייייייייייי	$per \iota$	والحال

- · Information on basic physical and chemical properties
- General Information
- · Appearance:

Form: Liquid

Color: Amber colored
Odor: Characteristic
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: >200 °C (>392 °F)

• Flash point: 94 °C (201.2 °F)

· Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.
 Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapor pressure: Not determined.

• **Density at 20 °C (68 °F):** 1.18 g/cm³ (9.85 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 7)



Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

	(Contd. of p	age 6)
Kinematic:	Not determined.	
· Solvent content: VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal	
Solids content: Other information	0.0% No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

US -

Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT · IMDG, IATA	not regulated UN3082
· UN proper shipping name · DOT · IMDG	not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin, Epoxy Resin), MARINE POLLUTANT

(Contd. on page 9)

BUILDING TRUST



Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

	(Contd. of pag
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (Epoxy phenol novolac resin)
Transport hazard class(es)	
DOT	
Class	not regulated
IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles 9
Packing group	
DOT	not regulated
IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: Epophenol novolac resin
Marine pollutant:	yes
	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Danger code (Kemler):	90
EMS Number:	F- A , S - F
Stowage Category	A
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN), 9, III

US



Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 9)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act): (Substances not listed)

All ingredients are listed.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 10)

· Hazard pictograms





GHS07

GHS09

· Signal word Warning

Hazard-determining components of labeling:

1,4-bis(2,3-epoxypropoxy)butane

Reaction Product of Bisphenol A and Epichlorohydrin

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 04/03/2019 / 1

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: EC440 Resin

(Contd. of page 11)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

* * Data compared to the previous version altered.