

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

*

Reviewed on 01/04/2020

Product identifi	er
Trade name: <u>E</u>	polam 2092 Hardener
Article number. Application of t	RZ30074-2 he substance / the mixture Epoxy curing agent
Sika Advanced I EHS Departmer Manufacturer/S	at Supplier: e: Sika Advanced Resins, US on Hwy
ehs-us@axson.c	om
During normal CHEMTREC 2 Hazard(s) id	4-hour Emergency: +1 (800) 424-9300
	f the substance or mixture
Classification o	
Classification o	f the substance or mixture
Classification of	f the substance or mixture 06 Skull and crossbones
Classification of GHSC Acute Tox. 3 Acute Tox. 2	f the substance or mixture 06 Skull and crossbones H311 Toxic in contact with skin.
Classification of GHSC Acute Tox. 3 Acute Tox. 2	f the substance or mixture 06 Skull and crossbones H311 Toxic in contact with skin. H330 Fatal if inhaled.
Classification of GHSC Acute Tox. 3 Acute Tox. 2 GHSC STOT RE 2	f the substance or mixture 06 Skull and crossbones H311 Toxic in contact with skin. H330 Fatal if inhaled. 08 Health hazard
Classification of GHSC Acute Tox. 3 Acute Tox. 2 GHSC STOT RE 2	f the substance or mixture 06 Skull and crossbones H311 Toxic in contact with skin. H330 Fatal if inhaled. 08 Health hazard H373 May cause damage to organs through prolonged or repeated exposure.
Classification of GHSU Acute Tox. 3 Acute Tox. 2 GHSU STOT RE 2 GHSU Skin Corr. 1A	f the substance or mixture 06 Skull and crossbones H311 Toxic in contact with skin. H330 Fatal if inhaled. 08 Health hazard H373 May cause damage to organs through prolonged or repeated exposure. 05 Corrosion
Classification of GHSC Acute Tox. 3 Acute Tox. 2 GHSC STOT RE 2 Skin Corr. 1A	f the substance or mixture D6 Skull and crossbones H311 Toxic in contact with skin. H330 Fatal if inhaled. D8 Health hazard H373 May cause damage to organs through prolonged or repeated exposure. D5 Corrosion H314 Causes severe skin burns and eye damage.



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener





Reviewed on 01/04/2020

BUILDING TRUST

Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Trade name: Epolam 2092 Hardener

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE1Fire = 1REACTIVITY0Reactivity = 0

• Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine) EINECS: 229-962-1 50-100%

4 First-aid measures

• Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:

Supply fresh air or oxygen; call for doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:
- Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 4)

(Contd. of page 2)



Page 4/12

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment:
- Mouth respiratory protective device.
- Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. • Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: All components have the value 0.28 mg/m^3 . · PAC-2: All components have the value 3.1 mg/m³. · PAC-3: All components have the value 19 mg/m^3 .

(Contd. on page 5)



Page 5/12

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

7 Handling and storage

· Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eves and skin.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)



Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

· Material of gloves

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and c	hemical properties	
General Information Appearance:		
Form:	Liquid	
Color:	Colorless	
Odor:	Amine-like	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	11	
Change in condition		
Melting point/Melting range:	-7 °C (-44.6 °F) 1,013 °C (33.813 °F)	
Boiling point/Boiling range:		
Flash point:	173 °C (343.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	275 °C (527 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.5 Vol %	
Upper:	2.8 Vol %	
Vapor pressure at 30 °C (86 °F):	0 hPa	
Density at 20 °C (68 °F):	0.94 g/cm³ (7.84 lbs/gal)	
Relative density	Not determined.	



Page 7/12

BUILDING TRUST

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

		(Contd. of page
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water at 20 °C (68 °F):	3.6 g/l	
Partition coefficient (n-octanol/wo	uter): Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	142 mPas	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

Oral	LD50	320-460 mg/kg (rat)
Dermal	LD50	200-400 mg/kg (rabbi

200-400 mg/kg (rabbit) LD50

Inhalative LC50/4 h 0.42 mg/l (rat) (Test Guideline 402)

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8) US



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

(Contd. of page 7)

Trade name: Epolam 2092 Hardener

Toxic Harmful Corrosive Very toxic Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

48 hr EC50 15.2 mg/l (daphnia)

96 hr LC50 45 mg/l (Fish)

• Persistence and degradability No further relevant information available.

- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

(Contd. on page 9)



Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

(Contd. of page 8)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, IMDG, IATA	UN2922
· UN proper shipping name	
·DOT	Corrosive liquids, toxic, n.o.s. (Cycloaliphatic Amine)
· IMDG, IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine)
• Transport hazard class(es)	
·DOT	
· Class	8 Corrosive substances
· Label	8, 6.1
· IMDG	
· Class	8 Corrosive substances
· Label	8/6.1
· IATA	
· Class	8 Corrosive substances
· Label	8 (6.1)



Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

	(Contd. of page
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Marine pollutant:	Yes (DOT)
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	886
EMS Number:	F-A,S-B
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
MARPOL73/78 and the IBC Code Transport/Additional information:	Not applicable.
-	
DOT Overstitu limitations	On nassanaay airoraft/rail: 0.5 I
Quantity limitations	On passenger aircraft/rail: 0.5 L On cargo aircraft only: 2.5 L
Remarks:	Special marking with the symbol (fish and tree).
	Special marking with the symbol (fish and tree).
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S (CYCLOALIPHATIC AMINE), 8 (6.1), II, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

(Contd. on page 11)

US



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

	(Contd. of page 10)
· Chemical regulated by TSCA 5(a)(2)rule:	
None of the ingredients is listed.	
· Hazardous Air Pollutants	
None of the ingredients is listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling:* 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

• Hazard statements Harmful if swallowed. Toxic in contact with skin. Fatal if inhaled. Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure.



Page 12/12

BUILDING TRUST

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2020

Reviewed on 01/04/2020

Trade name: Epolam 2092 Hardener

Contd. of page 11) Toxic to aquatic life with long lasting effects. • **Precautionary statements** Do not breathe dusts or mists. Wear protective gloves/protective clothing/eye protection/face protection. [In case of inadequate ventilation] wear respiratory protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment is urgent (see on this label). Take off immediately all contaminated clothing and wash it before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 01/04/2020 / 5

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 2: Acute toxicity - Category 2 Skin Corr. 1A: Skin corrosion/irritation – Category 1A STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 • * Data compared to the previous version altered.