



Page 1/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

1 Identification

- · Product identifier
- · Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)
- · Article number: 1822089-1
- · Application of the substance / the mixture Epoxy curing agent
- · Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Supplier's Name: Sika Advanced Resins, US

Headquarters:

30800 Stephenson Hwy Madison Heights, MI 48071

USA

advancedresins.ehs@us.sika.com

- · Information department: Product safety department
- · Emergency telephone number:

During normal opening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

H360 May damage fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)



Page 2/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 1)

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS05

GHS06

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:
- 2,2'-iminodiethylamine
- 3,6-diazaoctanethylenediamin

bisphenol A

Polyoxypropylenediamine

Teta, reaction products with propylene oxide

Polyoxylated Triethylenetetramine

· Hazard statements

Toxic if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause respiratory irritation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1Reactivity = 0

(Contd. on page 3)





Page 3/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous compone	· Dangerous components:		
CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin	20-50%	
CAS: 9046-10-0	Polyoxypropylenediamine	10-20%	
CAS: 26950-63-0	Teta, reaction products with propylene oxide Polyoxylated Triethylenetetramine	10-20%	
CAS: 111-40-0 EINECS: 203-865-4	2,2'-iminodiethylamine	≥10-<20%	
CAS: 80-05-7 EINECS: 201-245-8	bisphenol A	5-10%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Page 4/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
112-24-3	3,6-diazaoctanethylenediamin	3 ррт
9046-10-0	Polyoxypropylenediamine	4.8 mg/m³
111-40-0	2,2'-iminodiethylamine	3 ррт
80-05-7	bisphenol A	15 mg/m³
· PAC-2:		
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
9046-10-0	Polyoxypropylenediamine	53 mg/m³
	(C	ontd. on page 5

US-





Page 5/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

		(Contd. of page 4)
111-40-0	2,2'-iminodiethylamine	8.5 ppm
80-05-7	bisphenol A	110 mg/m³
· PAC-3:		
	3,6-diazaoctanethylenediamin	83 ppm
	Polyoxypropylenediamine	320 mg/m³
111-40-0	2,2'-iminodiethylamine	51 ppm
80-05-7	bisphenol A	650 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

112-24	l-3 3,6-diazaoctanethylenediamin
WEEL	Long-term value: 6 mg/m³, 1 ppm
10	Skin
	-0 2,2'-iminodiethylamine
REL	Long-term value: 4 mg/m³, 1 ppm Skin
TLV	Long-term value: 4.2 mg/m³, 1 ppm Skin

(Contd. on page 6)



Page 6/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 5)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

chemical mixture.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Color: According to product specification

· Odor: Characteristic

(Contd. on page 7)



Page 7/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

	(Contd. of	pag
· Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	207.1 °C (404.8 °F)	
Flash point:	103 °C (217.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	325 °C (617 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.7 Vol %	
Upper:	10 Vol %	
Vapor pressure at 20 °C (68 °F):	0.5 hPa (0.4 mm Hg)	
Density at 20 °C (68 °F):	1.01 g/cm³ (8.43 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	e r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	9.6 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- $\cdot \textit{Reactivity No further relevant information available}.$
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 8)



Page 8/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 7)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	· LD/LC50 values that are relevant for classification:			
Oral	LD50	2,880 mg/kg (rat)		
Dermal	LD50	2,980 mg/kg (rabbit)		
112-24	112-24-3 3,6-diazaoctanethylenediamin			
Oral	LD50	2,000 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		
9046-10	9046-10-0 Polyoxypropylenediamine			
Oral	LD50	2,855 mg/kg (rabbit)		
Dermal	LD50	2,980 mg/kg (rabbit)		
111-40-0	111-40-0 2,2'-iminodiethylamine			
Oral	LD50	1,553 mg/kg (rat)		
Dermal	LD50	1,045 mg/kg (rabbit)		
80-05-7	80-05-7 bisphenol A			
Oral	LD50	3,250 mg/kg (rat)		
Dermal	LD50	3,000 mg/kg (rabbit)		

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 9)





Page 9/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 8)

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

96 hr LC50 >220 mg/l (Fish)

9046-10-0 Polyoxypropylenediamine

48 hr EC50	80 mg/l (daphnia
48 hr EC50 96 hr LC50 72 or 96 hr ErC50	772 mg/l (Fish)
72 or 96 hr ErC50	15 mg/l (Algea)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)





Page 10/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 9)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· ON-Number · DOT, IMDG, IATA	UN2922
· UN proper shipping name · DOT	Corrosive liquids, toxic, n.o.s. (Triethylenetetram
· IMDG, IATA	Diethylenetriamine) CORROSIVE LIQUID, TOXIC, N.O (TRIETHYLENETETRAMINE, DIETHYLENETRIAMINE)
· Transport hazard class(es)	
\cdot DOT	
CORROSIVE TOXIC	
· Class · Label	8 Corrosive substances 8, 6.1
	0, 0.1
· IMDG	
· Class	8 Corrosive substances
· Label	8/6.1
· IATA	
· Class	8 Corrosive substances
· Label	8 (6.1)

(Contd. on page 11)



Page 11/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

	(Contd. of page 1
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler code):	86
· EMS Number:	F- A , S - B
· Segregation groups	Alkalis
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L
~ ,	On cargo aircraft only: 30 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (TRIETHYLENETETRAMINE, DIETHYLENETRIAMINE), (6.1), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-05-7 bisphenol A

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

(Contd. on page 12)



Page 12/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 11)

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

75-56-9 propylene oxide

· Chemicals known to cause reproductive toxicity for females:

80-05-7 bisphenol A

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS05

GHS06

GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

2,2'-iminodiethylamine

3,6-diazaoctanethylenediamin

bisphenol A

Polyoxypropylenediamine

Teta, reaction products with propylene oxide

Polyoxylated Triethylenetetramine

· Hazard statements

Toxic if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause respiratory irritation.

(Contd. on page 13)





Page 13/13

Safety Data Sheet acc. to OSHA HCS

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: SikaBiresin CH72-1 (MARINE 822 HARD)

(Contd. of page 12)

· Precautionary statements

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 07/27/2020 / 5
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 3: Acute toxicity - Category 3

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

 ${\it Skin Sens.} \ 1: {\it Skin sensitisation-Category} \ 1$

Repr. 1B: Reproductive toxicity – Category 1B

 $STOT\,SE\,3:\,Specific\,target\,organ\,toxicity\,(single\,exposure)-Category\,3$

* * Data compared to the previous version altered.

US