



Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

1 Identification

· Product identifier

· Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

· Article number: I025953-1

· Application of the substance / the mixture Epoxy resin

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Supplier's Name: Sika Advanced Resins, US

Headquarters:

30800 Stephenson Hwy Madison Heights, MI 48071

USA

advancedresins.ehs@us.sika.com

· Information department: Product safety department

· Emergency telephone number:

+1 (248) 588-2270 During normal opening times: CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling: bis[4-(2,3-epoxypropoxy)phenyl]propane Reaction Product of Bisphenol A and Epichlorohydrin

(Contd. on page 2)



Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 1)

1,4-bis(2,3-epoxypropoxy)butane oxirane, mono[(C12-14-alkyloxy)methyl] derivs Alkyl C12-C14 Glycidyl Ether

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 1

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)





Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 2)

· Dangerous components:		
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane	≥25-≤50%
CAS: 25068-38-6 NLP: 500-033-5	Reaction Product of Bisphenol A and Epichlorohydrin	20-50%
CAS: 2425-79-8 EINECS: 219-371-7	1,4-bis(2,3-epoxypropoxy)butane	≥5-<10%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Alkyl C12-C14 Glycidyl Ether	≥5-<10%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

-US





Page 4/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

DAC 1	······································	
· <i>PAC-1</i> :		
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	39 mg/m
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	90 mg/m ⁻
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	16 mg/m
PAC-2:		
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	430 mg/m
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	990 mg/m
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	170 mg/m
- PAC-3:		
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	2,600 mg/m
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	5,900 mg/m
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	220 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)



Page 5/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 4)

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

US



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

 $(Contd.\ of\ page\ 5)$

Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Translucent	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	266 °C (510.8 °F)	
Flash point:	112 °C (233.6 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.14 g/cm³ (9.51 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.1 %	
VOC content:	0.08 %	
	0.9 g/l / 0.01 lb/gal	
Solids content:	0.0 %	

(Contd. on page 7)



Sika®

Page 7/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 6)

· Other information

No further relevant information available.

*

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

*

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

*

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)





Page 8/11

Safety Data Sheet acc. to OSHA HCS

Reviewed on 05/11/2020 Printing date 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT · IMDG, IATA	not regulated UN3082
· UN proper shipping name	
$\cdot DOT$	not regulated
\cdot $IMDG$	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
	N.O.S. (Epoxy Resin), MARINE POLLUTANT
\cdot IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
	N.O.S. (Epoxy Resin)
· Transport hazard class(es)	

- $\cdot DOT$
- · Class not regulated
- · IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles

· Label

(Contd. on page 9)



Page 9/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

	(Contd. of page
Packing group	
DOT	not regulated
· IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: Epo:
	Resin
Marine pollutant:	Yes
1	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler co	
EMS Number:	F-A,S-F
Stowage Category	Т-A,5-Т А
Slowage Calegory	А
Transport in bulk according to Annex II of	of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
(- z)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IIN "Model Pegulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
UN ''Model Regulation'':	
	LIQUID, N.O.S. (EPOXY RESIN), 9, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

(Contd. on page 10)



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 9)

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

98-82-8 cumene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling:

bis[4-(2,3-epoxypropoxy)phenyl]propane Reaction Product of Bisphenol A and Epichlorohydrin 1,4-bis(2,3-epoxypropoxy)butane oxirane, mono[(C12-14-alkyloxy)methyl] derivs Alkyl C12-C14 Glycidyl Ether

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

(Contd. on page 11)

Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2020 Reviewed on 05/11/2020

Trade name: SikaBiresin CR86 (PROINFUSION RESIN)

(Contd. of page 10)

Wear protective gloves / eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 05/11/2020 / 8
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

* * Data compared to the previous version altered.

US