

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

1 Identification

- **Product identifier**
- **Trade name:** SCI75 Hardener
- **Article number:** I025471
- **Application of the substance / the mixture** Epoxy curing agent
- **Details of the supplier of the safety data sheet**
Sika Advanced Resins, US
EHS Department
- **Manufacturer/Supplier:**
Supplier's Name: Sika Advanced Resins, US
Headquarters:
30800 Stephenson Hwy
Madison Heights, MI 48071
USA

advancedresins.ehs@us.sika.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 1)

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

*Trimethylolpropane poly(oxypropylene)triamine
2-piperazin-1-ylethylamine*

- **Hazard statements**

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 1

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



*Health = *3*

Fire = 1

Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** *Not applicable.*

- **vPvB:** *Not applicable.*

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** *Mixture of the substances listed below with nonhazardous additions.*

- **Dangerous components:**

CAS: 39423-51-3	Trimethylolpropane poly(oxypropylene)triamine	10-20%
-----------------	---	--------

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 2)

CAS: 67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	5-10%
CAS: 140-31-8 EINECS: 205-411-0	2-piperazin-1-ylethylamine	5-10%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 3)

- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

39423-51-3	Trimethylolpropane poly(oxypropylene)triamine	30 mg/m ³
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	120 mg/m ³
140-31-8	2-piperazin-1-ylethylamine	6.4 mg/m ³

· **PAC-2:**

39423-51-3	Trimethylolpropane poly(oxypropylene)triamine	330 mg/m ³
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	1,300 mg/m ³
140-31-8	2-piperazin-1-ylethylamine	71 mg/m ³

· **PAC-3:**

39423-51-3	Trimethylolpropane poly(oxypropylene)triamine	2,000 mg/m ³
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	7,900 mg/m ³
140-31-8	2-piperazin-1-ylethylamine	420 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 4)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

US
(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Pasty
· Color:	White
· Odor:	Amine-like
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	220.4 °C (428.7 °F)

· **Flash point:** 102 °C (215.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 315 °C (599 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 6.8 hPa (5.1 mm Hg)

· **Density at 20 °C (68 °F):** 0.76 g/cm³ (6.34 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**

· Organic solvents:	0.4 %
· VOC content:	0.43 %
	3.3 g/l / 0.03 lb/gal

· **Solids content:** 38.7 %

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 6)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	220 mg/kg (rat)
Dermal	LD50	610 mg/kg (rabbit)

25322-69-4 Polypropylene glycol

Oral	LD50	541 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

39423-51-3 Trimethylolpropane poly(oxypropylene)triamine

Oral	LD50	<2,000 mg/kg (rat)
Dermal	LD50	>1,000 mg/kg (rat)

140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2,110 mg/kg (rat)
Dermal	LD50	866 mg/kg (rabbit)

38640-62-9 Diisopropyl naphthalene

Oral	LD50	>4,000 mg/kg (mouse)
Dermal	LD50	>4,000 mg/kg (rat)
Inhalative	LC50/6 h (dynamic)	>5.6 mg/l (rat) (Test Guideline 402)

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- Harmful
- Corrosive
- Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

39423-51-3 Trimethylolpropane poly(oxypropylene)triamine

48 hr EC50 (static)	13 mg/l (daphnia)
72 or 96 hr ErC50 (static)	4.4 mg/l (Algea)
NOEC (static)	1 mg/l (Algea)

140-31-8 2-piperazin-1-ylethylamine

48 hr EC50	58 mg/l (Invertabrates)
96 hr LC50	2,190 mg/l (Fish)
72 or 96 hr ErC50	1,000 mg/l (Algea)

38640-62-9 Diisopropyl naphthalene

48 hr EC50	0.16 mg/l (daphnia)
96 hr LC50	0.5 mg/l (Fish)
72 or 96 hr ErC50	0.15 mg/l (Algea)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 8)

*Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even extremely small quantities leak into the ground.*

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT

not regulated

· IMDG, IATA

UN3082

· UN proper shipping name

· DOT

not regulated

· IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated Triamine, PENTANES), MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated Triamine, PENTANES)

· Transport hazard class(es)

· DOT

· Class

not regulated

· IMDG, IATA



· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· Packing group

· DOT

not regulated

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 9)

· IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: Propoxylated Triamine
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user	Warning: Miscellaneous dangerous substances and articles
· Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PROPOXYLATED TRIAMINE, PENTANES), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

25322-69-4	Polypropylene glycol	ACTIVE
1317-65-3	Calcium Carbonate	ACTIVE
39423-51-3	Trimethylolpropane poly(oxypropylene)triamine	ACTIVE
	Triamine epoxy adduct	ACTIVE
67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	ACTIVE
140-31-8	2-piperazin-1-ylethylamine	ACTIVE

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 10)

38742-70-0	2-Propenoic acid, 2-methyl-, methyl ester, polymer with 2-methyl-2-propenenitrile and 2-propenenitrile	*
78-78-4	isopentane	ACTIVE
38640-62-9	Diisopropyl naphthalene	ACTIVE
1309-42-8	magnesium hydroxide	ACTIVE

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

1317-65-3	Calcium Carbonate
14808-60-7	Quartz (SiO ₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05 GHS07

· Signal word Danger

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2020

Reviewed on 06/05/2020

Trade name: SC175 Hardener

(Contd. of page 11)

- **Hazard-determining components of labeling:**
Trimethylolpropane poly(oxypropylene)triamine
2-piperazin-1-ylethylamine
- **Hazard statements**
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
- **Precautionary statements**
Do not breathe dusts or mists.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 06/05/2020 / 7
- **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
- *** Data compared to the previous version altered.**