

Page 1/12

٦

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

Product identifie	21
Trade name: <u>ES</u>	218 Resin
Article number: Application of th	1218088 <b>ne substance / the mixture</b> Epoxy resin
Sika Advanced R EHS Departmen Manufacturer/S	upplier: Sika Advanced Resins, US n Hwy
ehs-us@axson.co	om
Information dep Emergency telep	artment: Product safety department hone number:
During normal of	pening times: +1 (248) 588-2270 -hour Emergency: +1 (800) 424-9300
During normal of CHEMTREC 24	-hour Emergency: +1 (800) 424-9300
During normal c CHEMTREC 24 Hazard(s) ide	-hour Emergency: +1 (800) 424-9300 ntification
During normal of CHEMTREC 24 Hazard(s) ide Classification of	-hour Emergency: +1 (800) 424-9300 ntification The substance or mixture
During normal of CHEMTREC 24 Hazard(s) ide Classification of	-hour Emergency: +1 (800) 424-9300 ntification
During normal of CHEMTREC 24 Hazard(s) ide Classification of	-hour Emergency: +1 (800) 424-9300 ntification The substance or mixture
During normal of CHEMTREC 24 Hazard(s) ide Classification of Classification of GHS0 Repr. 2	-hour Emergency: +1 (800) 424-9300 ntification The substance or mixture 8 Health hazard
During normal of CHEMTREC 24 Hazard(s) ide Classification of Classification of GHS0 Repr. 2	-hour Emergency: +1 (800) 424-9300 ntification T the substance or mixture 8 Health hazard H361 Suspected of damaging fertility or the unborn child.
During normal of CHEMTREC 24 Hazard(s) ide Classification of Classification of GHS0 Repr. 2 GHS0	<ul> <li>hour Emergency: +1 (800) 424-9300</li> <li>ntification</li> <li>The substance or mixture</li> <li>8 Health hazard</li> <li>H361 Suspected of damaging fertility or the unborn child.</li> <li>5 Corrosion</li> </ul>
During normal of CHEMTREC 24 Hazard(s) ide Classification of GHS0 Repr. 2 Skin Corr. 1B Eye Dam. 1	<ul> <li>-hour Emergency: +1 (800) 424-9300</li> <li>ntification</li> <li>The substance or mixture</li> <li>8 Health hazard</li> <li>H361 Suspected of damaging fertility or the unborn child.</li> <li>5 Corrosion</li> <li>H314 Causes severe skin burns and eye damage.</li> </ul>
During normal of CHEMTREC 24 Hazard(s) ide Classification of GHS0 Repr. 2 CHEMTREC 24 GHS0 Skin Corr. 1B Eye Dam. 1 GHS0	<ul> <li><i>Intification</i></li> <li><i>Ithe substance or mixture</i></li> <li>8 Health hazard</li> <li>H361 Suspected of damaging fertility or the unborn child.</li> <li>5 Corrosion</li> <li>H314 Causes severe skin burns and eye damage.</li> <li>H318 Causes serious eye damage.</li> <li>9 Environment</li> </ul>
During normal of CHEMTREC 24 Hazard(s) ide Classification of GHS0 Repr. 2 Skin Corr. 1B Eye Dam. 1 Skin Corr. 1B	<ul> <li>-hour Emergency: +1 (800) 424-9300</li> <li>ntification</li> <li>The substance or mixture</li> <li>8 Health hazard</li> <li>H361 Suspected of damaging fertility or the unborn child.</li> <li>5 Corrosion</li> <li>H314 Causes severe skin burns and eye damage.</li> <li>H318 Causes serious eye damage.</li> <li>9 Environment</li> <li>2 H411 Toxic to aquatic life with long lasting effects.</li> </ul>



Page 2/12

## Safety Data Sheet acc. to OSHA HCS

#### Reviewed on 10/26/2019 Printing date 10/26/2019 Trade name: ES218 Resin (Contd. of page 1) Skin Sens. 1 H317 May cause an allergic skin reaction. H401 Toxic to aquatic life. Aquatic Acute 2 · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS05 GHS07 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labeling: Reaction Product of Bisphenol A and Epichlorohydrin 4-nonylphenol, branched 1,4-bis(2,3-epoxypropoxy)butane · Hazard statements Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Toxic to aquatic life. Toxic to aquatic life with long lasting effects. · Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray Do not breathe dusts or mists. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 1Reactivity = 0(Contd. on page 3)



Reviewed on 10/26/2019

BUILDING TRUST

Page 3/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Trade name: ES218 Resin

#### · HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE1Fire = 1REACTIVITY0Reactivity = 0

#### · Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

#### 3 Composition/information on ingredients

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5	Reaction Product of Bisphenol A and Epichlorohydrin	50-100%
CAS: 2425-79-8 EINECS: 219-371-7	1,4-bis(2,3-epoxypropoxy)butane	10-20%
CAS: 84852-15-3 EINECS: 284-325-5	4-nonylphenol, branched	5-10%

#### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

(Contd. of page 2)

US



Page 4/12

(Contd. of page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

Trade name: ES218 Resin

• Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

• Additional information

\*

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## 6 Accidental release measures

	ecautions, protective equipment and emergency procedures ratory protective device.	
	raiory protective device. tive equipment. Keep unprotected persons away.	
1	ntel precautions:	
	w product to reach sewage system or any water course.	
	ective authorities in case of seepage into water course or sewage system.	
	v to enter sewers/ surface or ground water.	
	d material for containment and cleaning up:	
	liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutrali		
	taminated material as waste according to item 13.	
	<i>juate ventilation.</i>	
· Reference to	o other sections	
See Section	7 for information on safe handling.	
See Section	8 for information on personal protection equipment.	
	13 for disposal information.	
• Protective A	lction Criteria for Chemicals	
• PAC-1:		
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	90 mg/m <sup>3</sup>
	1,4-bis(2,3-epoxypropoxy)butane	16 mg/m³
84852-15-3	4-nonylphenol, branched	3.9 mg/m <sup>3</sup>
• PAC-2:		
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	990 mg/m <sup>3</sup>
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	170 mg/m³
84852-15-3	4-nonylphenol, branched	43 mg/m <sup>3</sup>
· PAC-3:		
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	5,900 mg/m <sup>3</sup>
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	220 mg/m <sup>3</sup>
84852-15-3	4-nonylphenol, branched	260 mg/m <sup>3</sup>
	•	

(Contd. on page 5)



Page 5/12

#### Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

(Contd. of page 4)

Trade name: ES218 Resin

#### 7 Handling and storage

#### · Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.  $\tilde{\alpha}$ 

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

<sup>–</sup> US



Page 6/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

#### Trade name: ES218 Resin

(Contd. of page 5) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



\*

Tightly sealed goggles

Information on basic physical and	chemical properties	
General Information Appearance:		
Form:	Pasty	
Color:	White	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	266 °C (510.8 °F)	
Flash point:	112 °C (233.6 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.34 g/cm <sup>3</sup> (11.18 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	

US



Page 7/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

Trade name: ES218 Resin

		(Contd. of page 6
• Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	t <b>ter):</b> Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	28.2 %	
• Other information	No further relevant information available.	

#### **10 Stability and reactivity**

- · *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

#### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

(Contd. on page 8)



Page 8/12

3

2B

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

#### Trade name: ES218 Resin

(Contd. of page 7) Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

14807-96-6 Talc (Mg3H2(SiO3)4)

13463-67-7 titanium dioxide

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### **12** Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



# Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Trade name: ES218 Resin

• Uncleaned packagings: • Recommendation: Disposal must be made according to official regulations.

· UN-Number	
·DOT	not regulated
· IMDG, IATA	UN3082
· UN proper shipping name	As stated below:
·DOT	not regulated
·IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQU
- (	N.O.S. (Epoxy Resin), MARINE POLLUTANT
·IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQU
	N.O.S. (Epoxy Resin)
• Transport hazard class(es)	
·DOT	
· Class	not regulated
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group	
·DOT	not regulated
· IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
	Warning: Miscellaneous dangerous substances and articles
· Special precautions for user	
· EMS Number:	F- $A$ , $S$ - $F$
	F-A,S-F A
· EMS Number:	A

Reviewed on 10/26/2019

Page 9/12

(Contd. of page 8)



Page 10/12

(Contd. of page 9)

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

Trade name: ES218 Resin

• UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III

## **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

84852-15-3 4-nonylphenol, branched

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

• Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

· Listed in CWC Regulations

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 11)



Page 11/12

(Contd. of page 10)

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

Reviewed on 10/26/2019

Trade name: ES218 Resin

· Hazard pictograms



Hazard-determining components of labeling: Reaction Product of Bisphenol A and Epichlorohydrin 4-nonylphenol, branched 1,4-bis(2,3-epoxypropoxy)butane

#### · Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

• **Precautionary statements** Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label). Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Date of preparation / last revision 10/26/2019 / 6
 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

<sup>-</sup> U



#### Page 12/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2019

#### Trade name: ES218 Resin

(Contd. of page 11)

US

Reviewed on 10/26/2019