



Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

1 Identification

· Product identifier

· Trade name: SP707 Resin · Article number: 1229088-1

· Application of the substance / the mixture Epoxy resin

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Manufacturer:

Sika Advanced Resins

30800 Stephenson Hwy

Madison Heights

MI 48071

USA

· Information department: Product safety department

· Emergency telephone number:

During normalopening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

· Signal word Danger

(Contd. on page 2)



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 1)

· Hazard-determining components of labeling:

bis[4-(2,3-epoxypropoxy)phenyl]propane

N-methyl-2-pyrrolidone

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 0

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

US





Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous compon	ents:	
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane	≥25-≤50%
CAS: 17557-23-2 EINECS: 241-536-7	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	≥5-<10%
CAS: 67762-90-7	Silicones and siloxanes, dimethyl-, reaction products with silica	1-5%
CAS: 872-50-4 EINECS: 212-828-1	N-methyl-2-pyrrolidone	0.1-1%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

(Contd. on page 4)



Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 3)

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

1 Totelive Action	n Crueriu for Chemicus	
· PAC-1:		
1675-54-3 bis _[[4-(2,3-epoxypropoxy)phenyl]propane	39 mg/m³
67762-90-7 Sili	cones and siloxanes, dimethyl-, reaction products with silica	120 mg/m³
872-50-4 N-n	nethyl-2-pyrrolidone	30 ppm
· <i>PAC-2</i> :		
1675-54-3 bis _[[4-(2,3-epoxypropoxy)phenyl]propane	430 mg/m³
67762-90-7 Sili	cones and siloxanes, dimethyl-, reaction products with silica	$1,300 \text{ mg/m}^3$
872-50-4 N-n	nethyl-2-pyrrolidone	32 ppm
· PAC-3:		
1675-54-3 bis _[[4-(2,3-epoxypropoxy)phenyl]propane	$2,600 \text{ mg/m}^3$
67762-90-7 Sili	cones and siloxanes, dimethyl-, reaction products with silica	$7,900 \text{ mg/m}^3$
872-50-4 N-n	nethyl-2-pyrrolidone	190 ppm
		•

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

US





Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

872-50)-4 N-me	thyl-2-p	pyrrolidone
--------	----------	----------	-------------

TLV BEI

WEEL Long-term value: 10 ppm

Skin

· Ingredients with biological limit values:

872-50-4 N-methyl-2-pyrrolidone

BEI 100 mg/L

Medium: urine Time: end of shift

Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical propertie	9 Ph	ysical	and	chemi	cal p	rop	erti	es
-----------------------------------	------	--------	-----	-------	-------	-----	------	----

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pasty
Color: Grey
Odor: Amine-like

- Odor threshold: Not determined.
- · pH-value: Not determined.
- · Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: >200 °C (>392 °F)

- · Flash point: Not applicable.
- Flammability (solid, gaseous): Not applicable.
- Ignition temperature: 400 °C (752 °F)
- Decomposition temperature: Not determined.
- Auto igniting: Product is not selfigniting.
- Danger of explosion: Product does not present an explosion hazard.
- · Explosion limits:

Lower: Not determined. Upper: Not determined.

- · Vapor pressure: Not determined.
- Density at 20 °C (68 °F): 1.75 g/cm³ (14.6 lbs/gal)
- Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.
- · Solubility in / Miscibility with

Water: Fully miscible.

(Contd. on page 7)





Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

		(Contd. of page
Partition coefficient (n-octan	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.2 %	
VOC content:	0.20 %	
	3.6 g/l / 0.03 lb/gal	
Solids content:	39.3 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- $\cdot \textit{Reactivity} \ \textit{No further relevant information available}.$
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

Oral LD50 4,500 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC	(International	Agency f	for Research on	Cancer)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)



Sika[®]

Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

- 57	4 7	7		•	C	7 ·
	4 1	vmnc	$n \alpha v t$	8 6 / 6	forma	tian
	T 1	I WILLS	u u u u	ши		uvuu
			4			

· UN-Number · DOT · IMDG, IATA	not regulated UN3082
· UN proper shipping name · DOT · IMDG	not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
· IATA	N.O.S. (Epoxy Resin, DGEBA Monomer), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, DGEBA Monomer)

(Contd. on page 9)





Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

	(Contd. of page
Transport hazard class(es)	
DOT	
Class	not regulated
IMDG, IATA	
1 1 1 1 1 1 1 1 1 1	
Class	9 Miscellaneous dangerous substances and articles
Label	9
Packing group	
DOT	not regulated
IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: Epo
16.	phenol novolac resin
Marine pollutant:	Yes
Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
Special marking (IATA):	,
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler code)	
EMS Number:	F-A,S-F
Stowage Category	A
Transport in bulk according to Annex II of	M , 1: 11
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
<i>IMDG</i>	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (EPOXY RESIN, DGEBA MONOMER), 9, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)





Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 9)

Section 313 (Specific toxic chemical listings):	· Section	313	(Specific	toxic	chemical	listings):
---	-----------	-----	-----------	-------	----------	------------

7429-90-5 aluminum powder (stabilised)

872-50-4 N-methyl-2-pyrrolidone

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidone

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

· Signal word Danger

Hazard-determining components of labeling:

bis[4-(2,3-epoxypropoxy)phenyl]propane N-methyl-2-pyrrolidone

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 10)

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

· Hazard statements

Causes skin irritation.

Causes serious eve irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 11/10/2020 / 7
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

(Contd. on page 12)

Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 11/10/2020 Reviewed on 11/10/2020

Trade name: SP707 Resin

(Contd. of page 11)

BEI: Biological Exposure Limit
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category I
Repr. 1B: Reproductive toxicity – Category 1B

* Data compared to the previous version altered.