

Sika Sarnafil

World Class Roofing and Waterproofing

ROOFING TECHNICAL BULLETIN

#02-09

To: Authorized Roofing Applicators
Sika Sarnafil Sales Staff & Sales Representatives
Sika Sarnafil Regional Technical Staff
Sika Sarnafil Customer Service Staff
Sika Sarnafil Services Staff

From: Technical Service Department

Re: Sika Sarnafil Perimeter Warning Tape

Sika Sarnafil Perimeter Warning Tape is designed for use on all Sika Sarnafil PVC membranes as a reflective, highly visible product to draw attention to roof perimeters and potential hazardous areas.

Sika Sarnafil membrane where tape is to be applied must be cleaned to a “like new” condition. Failure to properly clean the membrane will result in less than satisfactory adhesion. The membrane should be cleaned as follows:

- 1) New Sika Sarnafil membrane: Remove loose dirt and dust by wiping clean with water. For areas where dirt is embedded, scrub the application area with a commercial cleaner such as Simple Green, 409 or other similar all purpose cleaner using a Scotch Brite scrubbing pad or similar product. Wash away residual cleaning material with clean water.
- 2) Weathered Sika Sarnafil membrane: For older membranes or areas where there is excessive dirt buildup, use the above cleaning procedure followed by cleaning with a natural fiber rag wet with MEK. Wipe away all residual cleaning solution and remaining dirt until membrane has a “like new” appearance.

After Sika Sarnafil membrane is clean and dry, apply tape to membrane taking care to avoid trapping air and creating blisters as tape is smoothed over with hand pressure. If a chalk line is used, be sure to keep chalk dust clear of application area.

Do not apply Perimeter Warning Tape to Sika Sarnafil membranes when the temperature is below 40 degrees Fahrenheit.

Perimeter Warning Tape may be slippery when wet.



Sika Sarnafil, A Division of Sika Corporation, 100 Dan Road, Canton, MA 02021
Tel. 800-451-2504, Fax: 781-828-5365, www.sikacorp.com

Sarnafil®