



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

SECTION 1. IDENTIFICATION

Product name : SikaBiresin® G439 (formerly EC-439) Part A

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion : Sub-category 1C

Serious eye damage : Category 1

Skin sensitization : Category 1

Germ cell mutagenicity : Category 2

Reproductive toxicity : Category 1B

Other hazards

GHS label elements

Hazard pictograms : 

Signal Word : Danger



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

- Hazard Statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H360 May damage fertility or the unborn child.
- Supplemental Hazard Statements : Corrosive to the respiratory tract.
- Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing mist or vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
- Response:**
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
- Storage:**
P405 Store locked up.
- Disposal:**
P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.
None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS No./Unique ID	Classification	Concentration (% w/w)
---------------	-------------------	----------------	-----------------------



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

bisphenol-F-(epichlorhydrin) epoxy resin	28064-14-4	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 65 - <= 85
Trimethylolpropane triglycidylether	30499-70-8	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Muta. 2; H341 Repr. 1B; H360	>= 5 - <= 10
1,4-bis(2,3-epoxypropoxy)butane	2425-79-8	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 5 - <= 10
bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 0.5 - <= 1.5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms : Health injuries may be delayed.



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

and effects, both acute and delayed

corrosive effects
sensitizing effects
toxic effects for reproduction
Allergic reactions
Dermatitis
May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of causing genetic defects.
May damage fertility or the unborn child.
Causes severe burns.
Corrosive to the respiratory tract.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

- Advice on safe handling** : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Pregnant women or women of child-bearing age should not be exposed to this product.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage** : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid** : Explosives
Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids
Spontaneously Combustible Substances

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

	imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: amber
Odor	: characteristic
Odor Threshold	: No data available
pH	: Not applicable
Melting point/ range / Freezing point	: No data available
Boiling point/boiling range	: > 392 °F / > 200 °C
Flash point	: 201 °F / 94 °C (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.1 hpa
Relative vapor density	:	No data available
Density	:	1.18 g/cm ³ (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

bisphenol-F-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Trimethylolpropane triglycidylether:

Acute oral toxicity : LD50 Oral (Rat): 3,398 mg/kg

1,4-bis(2,3-epoxypropoxy)butane:

Acute oral toxicity : LD50 Oral (Rat): 1,163 mg/kg

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Not classified due to lack of data.

IARC Not applicable

OSHA Not applicable

NTP Not applicable



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Corrosive to the respiratory tract.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Trimethylolpropane triglycidylether:

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 9 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): 3.7 mg/l
Exposure time: 48 d

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

May be harmful to the environment if released in large quantities.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 1760
- Proper shipping name : Corrosive liquid, n.o.s.
(Trimethylolpropane triglycidylether)
- Class : 8
- Packing group : III
- Labels : Corrosive
- Packing instruction (cargo aircraft) : 856
- Packing instruction (passenger aircraft) : 852
- Environmentally hazardous : yes

IMDG-Code

- UN number : UN 1760
- Proper shipping name : CORROSIVE LIQUID, N.O.S.
(Trimethylolpropane triglycidylether, epoxy resin)
- Class : 8
- Packing group : III
- Labels : 8
- EmS Code : F-A, S-B
- Marine pollutant : yes

Domestic regulation

49 CFR Road

- UN/ID/NA number : UN 1760
- Proper shipping name : Corrosive liquids, n.o.s.
(Trimethylolpropane triglycidylether)
- Class : 8

Safety Data Sheet
SikaBiresin® G439 (formerly EC-439) Part A



Revision Date 03/24/2025

Print Date 03/24/2025

Packing group : III
Labels : CORROSIVE
ERG Code : 154
Marine pollutant : yes

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)

DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Germ cell mutagenicity
Reproductive toxicity
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).




SikaBiresin® G439 (formerly EC-439) Part A

Revision Date 03/24/2025

Print Date 03/24/2025

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Oxirane, (chloromethyl)- Epichlorohydrin, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/24/2025

100000035706
US / Z8