

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

SECTION 1. IDENTIFICATION

Product name : SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US

Product code : 00000000050001958

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : floor coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure

Specific target organ toxicity : Category 1 (Lungs)
- repeated exposure (Inhalation)

Specific target organ toxicity : Category 2 (Kidney, Immune system)
- repeated exposure (Inhalation)

GHS label elements

Hazard pictograms :

Signal Word : Danger

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Hazard Statements : H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H350 May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : modified cement mortar

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Components

Chemical name	CAS-No.	Concentration (% w/w)
crystalline silica	14808-60-7	>= 70 - < 90
Cement, portland, chemicals	65997-15-1	>= 10 - < 20
Calcium dihydroxide	1305-62-0	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety.
Remove contaminated clothing.
- If inhaled : After inhalation of dust.
Keep patient calm, remove to fresh air.
If difficulties occur:
Seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water
and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15
to 20 minutes. Remove contact lenses, if present, after first 5
minutes, then continue rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,
seek medical attention.
Do not induce vomiting unless told to by a poison control cen-
ter or doctor.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated
exposure if inhaled.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
Product itself is non-combustible. Only the packaging materi-
als can catch fire. The extinguishing agents normally used are
sufficient.

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0	Revision Date: 02/08/2021	SDS Number: 960000009321	Date of last issue: - Date of first issue: 02/08/2021
----------------	------------------------------	-----------------------------	--

- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : Product is not combustible or explosive. Exposure to decomposition products may be a hazard to health.
- Hazardous combustion products : harmful vapours
- Further information : Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and chemical-protective clothing.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid dust formation. Do not inhale dusts. Use personal protective equipment. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice.
- Environmental precautions : Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal. Avoid dust formation. Rinse with plenty of water. Keep in suitable, closed containers for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : No special precautions necessary.
- Advice on safe handling : Avoid dust formation. Do NOT breathe dust because it is hazardous to respiratory system. Avoid contact with skin and eyes. Breathing must be protected when large quantities are decanted without local exhaust ventilation. The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore.

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Pour downwind and allow as little free fall as possible while emptying bags into equipment.

Further information on storage conditions : Containers should be stored tightly sealed in a dry place.

Materials to avoid : Keep away from water.
Segregate from metals.
Segregate from acids and bases.
Segregate from oxidants.
Segregate from foods and animal feeds.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
crystalline silica	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m ³	ACGIHTLV
		REL value (Respirable dust)	0.05 mg/m ³	NIOSH
		TWA value	0.05 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
Cement, portland, chemicals	65997-15-1	TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
		TWA value (Respirable fraction)	1 mg/m ³	ACGIHTLV
		REL value	10 mg/m ³	NIOSH

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
 Date of first issue: 02/08/2021

		(Total)		
		REL value (Respirable)	5 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	50 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Dust)	50 Million particles per cubic foot	OSHA Z-3
Calcium dihydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0

Engineering measures : Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection : Wear the following respiratory protection if exposure limits may be exceeded:
 Wear a NIOSH-certified (or equivalent) particulate respirator.

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Avoid contact with the skin, eyes and clothing.
Avoid inhalation of dusts.
In order to prevent contamination while handling, closed working clothes and working gloves should be used.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : granules-powder mixture

Color : white to grey-brown

Odor : faint, earthy

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : Not applicable

Melting point : No data available

Boiling point/boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Self-ignition : not self-igniting

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Upper explosion limit / Upper flammability limit : As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Lower explosion limit / Lower flammability limit : As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : No data available

Bulk density : 1,900 kg/m³ (68 °F / 20 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : Not applicable

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Molecular weight : No data available

Dust explosion class : none

Metal corrosion rate : Not corrosive to metals.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0	Revision Date: 02/08/2021	SDS Number: 960000009321	Date of last issue: - Date of first issue: 02/08/2021
----------------	------------------------------	-----------------------------	--

scribed/indicated.

Possibility of hazardous reactions : Strong bases are formed on the addition of water. The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : Avoid dust formation.
Avoid humidity.

Incompatible materials : Strong bases
Strong acids

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory tract irritation.

STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0	Revision Date: 02/08/2021	SDS Number: 960000009321	Date of last issue: - Date of first issue: 02/08/2021
----------------	------------------------------	-----------------------------	--

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Product:

Skin contact : Remarks: In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable for inorganic substances.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Product:

Distribution among environmental compartments : Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected. The substance will not evaporate into the atmosphere from the water surface.

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Completely emptied packagings can be given for recycling. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

crystalline silica	14808-60-7
Cement, portland, chemicals	65997-15-1
Calcium dihydroxide	1305-62-0

New Jersey Right To Know

crystalline silica	14808-60-7
Cement, portland, chemicals	65997-15-1

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version 1.0 Revision Date: 02/08/2021 SDS Number: 960000009321 Date of last issue: -
Date of first issue: 02/08/2021

Calcium dihydroxide 1305-62-0

California Prop. 65

WARNING: This product can expose you to chemicals including crystalline silica, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

- TSCA : All substances listed as active on the TSCA inventory
DSL : All components of this product are on the Canadian DSL


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/08/2021	960000009321	Date of first issue: 02/08/2021

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit

29 CFR 1910.1000 (Table Z-3) / TWA value : Time Weighted Average (TWA):

29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level

29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):

ACGIH / TWA : 8-hour, time-weighted average

ACGIHTLV / TWA value : Time Weighted Average (TWA):

NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund

SAFETY DATA SHEET

SikaUcrete HF60RT Part 3 US Formerly Ucrete PT3 HF60RT US



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/08/2021	960000009321	Date of first issue: 02/08/2021

Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/08/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN