

Sikadur® Aggregates Selection Guide

Selected Quartz Sand Gradings for Special Flooring Application

Name	Description / Uses	Grading Mesh No.	Bulk Density	Packaging
Sikadur® 504	Slurry aggregates for Sikafloor® products, such as <ul style="list-style-type: none">• Sikafloor®- Epoxy• Sikafloor®- Polyurethane Formerly known as F- 62	50 – 200 (0.03 – 0.3mm)	1.50kg/L	50lb/bag
SAP Code:	402716			
Sikadur® 506	Aggregate composition for Troweled Epoxy and resurfacing mortars <ul style="list-style-type: none">• Used with Sikafloor®- 160 Resin Formerly known as F- 70	16 – 140 (0.1 – 1.2mm)	1.75kg/L	50lb/bag
SAP Code:	402717			
Sikadur® 506 ER	Aggregate composition for Troweled Epoxy and resurfacing mortars <ul style="list-style-type: none">• Used with Sikafloor®- 160 Resin Formerly known as EpoRok (identical gradation - different bag size)	16 – 140 (0.1 – 1.2mm)	1.75kg/L	50lb/bag
SAP Code:	465673			
Sikadur® 506 RC	Aggregate composition for Troweled Epoxy and resurfacing mortars <ul style="list-style-type: none">• Used with Sikafloor®- 160 Resin Contains 30% Recycled Material	16 – 140 (0.1 – 1.2mm)	1.75kg/L	50lb/bag
SAP Code:	465672			

Industrial Flooring

Name	Description / Uses	Grading Mesh No.	Bulk Density	Packaging
Sikadur® 507	Fine Broadcasting aggregates for Sikafloor® products, such as: <ul style="list-style-type: none"> • Sikafloor®- Epoxy • Sikafloor®- Polyurethane • Sikafloor®- PurCem 	40 – 70 (0.21 – 0.42mm)	1.60kg/L	50lb/bag
SAP Code:	465671			
Sikadur® 508	Medium Broadcasting aggregates for Sikafloor® products, such as: <ul style="list-style-type: none"> • Sikafloor®- Epoxy • Sikafloor®- Polyurethane • Sikafloor®- PurCem 	35 – 50 (0.29 – 0.50mm)	1.60kg/L	50lb/bag
SAP Code:	465670			
Sikadur® 509	Coarse Broadcasting aggregates for Sikafloor® products, such as: <ul style="list-style-type: none"> • Sikafloor®- Epoxy • Sikafloor®- Polyurethane • Sikafloor®- PurCem • Sikafloor®- MMA 	20 – 40 (0.42 – 0.84mm)	1.60kg/L	50lb/bag
SAP Code:	469609			
Sika Wear Aggregate:	Wear aggregates for Sikafloor® products, such as: <ul style="list-style-type: none"> • Sikafloor®- 315 	240 (0.054mm)	1.90kg/L	7lb/can
SAP Code:	178274			

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <http://usa.sika.com> or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BELIEABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Visit our website at <http://usa.sika.com>

1-800-933-SIKA NATIONWIDE

Regional Information and Sales Centers. For the location of your nearest Sika sales office, contact your regional center.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225

Sika Canada Inc.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

