



SikaTile®-815 Secure Grout

HIGH PERFORMANCE, RAPID-SETTING, POLYMER MODIFIED, DUSTLESS GROUT

- Polymer modified for hard, durable, high performing results
- Stain-resistant, color consistent, and efflorescence free
- Dustless formula – provides approximately 80% less dust than ordinary grouts
- Promotes cleaner working conditions by minimizing dust
- Creamier and easier to spread
- Uses less water for consistent hydration and quicker drying
- For grout joints from 1/16" to 1/2" (1.5 to 13 mm)
- **Colors:** 18 colors - see back for details
- **Packaging:** 10 lb. bags, 3 bags per case

Standards

- Exceeds ANSI A118.7

Attributes Include:



BUILDING TRUST



SikaTile®-815 Secure Grout

HIGH PERFORMANCE, RAPID-SETTING, POLYMER MODIFIED, DUSTLESS GROUT

WHERE TO USE

- For interior and exterior applications in both residential and commercial applications in dry or wet conditions.
- For floors, walls, countertops, and submerged conditions.
- For joint widths from 1/16" (1.5 mm) to 1/2" (13 mm).
- For application in submerged conditions (swimming pools, spas, water features, and fountains), once fully cured (after 21 days).

SUITABLE TILE TYPES:

- Brick and thin brick
- Cement-based precast terrazzo
- Impervious porcelain and glass tile
- Natural stone tile, granite and slate
- Vitreous, semi-vitreous or non-vitreous tile:
 - Ceramic, mosaic, quarry, cement body tile

COLORS AVAILABLE

00010 Bright White



00150 Santa Fe



00011 Snow White



00175 Dark Chocolate



00012 Navajo White



00191 Terracotta



00018 Cream



00030 Silver



00021 Canvas



00034 River Rock



00032 Light Taupe



00035 Natural Gray



00025 Tumbleweed



00038 Gray



00153 Buckskin



00162 True Taupe



00071 Sandstone



00525 Black Sapphire



FEATURES AND BENEFITS

- Polymer modified for hard, durable, high performing results
- Stain-resistant, color consistent, and efflorescence free
- For 1/16" (1.5 mm) to 1/2" (13 mm) grout joints
- Easy mixing – just add water, no additives required
- Rapid-Setting
- For interior and exterior floors, walls, and countertops
- Dustless formula – provides approximately 80% less dust than ordinary grouts
- Promotes cleaner working conditions by minimizing dust
- Creamier and easier to spread
- Uses less water for consistent hydration and quicker drying
- Mold and mildew resistant

NOTE: Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.

APPROXIMATE COVERAGE

SikaTile®-815 Secure Grout - Coverage in sqft. (m ²) per 10 lb. Bag (4.53 kg)*					
Tile Size	Grout Joint Width				
	1/16" (1.5 mm)	1/8" (3 mm)	1/4" (6 mm)	3/8" (10 mm)	1/2" (13 mm)
1" x 4" x 1/4" (25 x 25 x 6 mm)	42 (3.9)	23 (2.1)	14 (1.3)	10 (1.0)	9 (0.8)
2" x 2" x 1/4" (50 x 50 x 6 mm)	81 (7.5)	42 (3.9)	23 (2.1)	17 (1.6)	14 (1.3)
4" x 4" x 3/8" (100 x 100 x 10 mm)	105 (9.8)	54 (5.0)	28 (2.6)	20 (1.9)	16 (1.5)
6" x 6" x 3/8" (150 x 150 x 10 mm)	156 (14.5)	79 (7.3)	41 (3.8)	28 (2.6)	22 (2.0)
8" x 8" x 3/8" (200 x 200 x 10 mm)	207 (19.2)	105 (9.8)	54 (5.0)	37 (3.4)	28 (2.6)
12" x 12" x 3/8" (300 x 300 x 10 mm)	310 (28.8)	156 (14.5)	80 (7.4)	54 (5.0)	41 (3.8)
18" x 18" x 3/8" (150 x 610 x 10 mm)	464 (43.1)	233 (21.6)	119 (11.1)	80 (7.4)	61 (5.7)
24" x 24" x 3/8" (610 x 610 x 10 mm)	618 (57.4)	310 (28.8)	158 (14.7)	106 (9.8)	80 (7.4)
6" x 24" x 3/8" (150 x 610 x 10 mm)	249 (23.1)	126 (11.7)	65 (6.0)	44 (4.1)	34 (3.2)
12" x 24" x 3/8" (300 x 610 x 10 mm)	413 (38.4)	208 (19.3)	106 (9.8)	72 (6.7)	54 (5.0)

* Coverage shown is for estimating purposes only. Actual coverage may vary due to installation techniques and actual tile types and sizes used on the job.

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.SikaTile.com

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

BUILDING TRUST

