

SikaTile® No-Slake Product Range

NO MORE WAIT! SIKATILE'S NEW, NO-SLAKE TECHNOLOGY PROVIDES A UNIFORM MIX TO ELIMINATE SLAKING OR WAIT TIME. JUST MIX, TROWEL AND INSTALL.





BUILDING TRUST

SikaTile[®] No-Slake Product Range

NO WAIT. JUST MIX, TROWEL AND INSTALL



SikaTile®-300 Set

- Standard Grade Non-Modified Thin Set Mortar
- For use with ceramic tile and dimensionally stable natural stone
- Can be used over plywood substrates when mixed with Sika Latex R

Specifications: ANSI: A118.1 when mixed with water (A118.4 and A118.11 when mixed with Sika® Latex R)

Packaging: 50 lb. bags Colors: Gray and White



SikaTile®-350 Flex Set

- Superior Grade Polymer Modified Thin Set Mortar
- Ideal for Exterior Vertical Installations
- For Glass, Porcelain, Ceramic Tile and Natural Stone
- Adheres to Non-Absorptive Surface

Premium Grade, Rapid Setting LHT Mortar

Specifications: ANSI: A118.4F, A118.11F

High Performance Flexible LHT Mortar

porcelain tile panels

Packaging: 50 lb. bags

Colors: White

ISO: 13007 - C2FP1

SikaTile®-475 LHT Premium Set

Specifications: ANSI: A118.15ET, A118.4ET, A118.11

ISO: 13007 - C2TES1P1

For use with large ceramic, porcelain, gauged

porcelain, marble, granite, and natural stone

Flexible adhesive, suitable for high traffic areas

Superior transfer promotes full coverage for gauged

Non-sag and slip resistance for large and heavy tile

Ideal for time critical residential and commercial

Allows for grouting in 3 hours and open for traffic

Specifications: ANSI: A118.15E, A118.4E, A118.11 ISO: 13007 - C2EP1

Packaging: 50 lb. bags Colors: Gray and White

applications

in 4 hours

Packaging: 50 lb. bags

Colors: Gray and White

C î 🖉 📓

SikaTile[®]-400 LHT Pro Set Professional Grade LHT Mortar

- For use with large and heavy tile and natural stone Non-slumping formula eliminates tile lipage
- May be applied up to 3/4" thick on
- horizontal applications

Specifications: ANSI: A118.4

ISO: 13007 - C1

Packaging: 50 lb. bags Colors: Gray and White

SikaTile®-450 LHT Secure Set

Premium Grade I HT Mortar

- Non-sag and slip resistance for large and heavy tile May be applied up to 3/4" thick on horizontal applications
- Flowable properties reduce the need for back-buttering

Specifications: ANSI: A118.4E, A118.11 ISO: 13007 - C2EP1

Packaging: 50 lb. bags Colors: Gray and White



-

(*) in 🗾 🖪

SikaTile®-500 LHT Lite

Superior Grade Lightweight Flexible LHT Mortar

- Non-sag and slip resistance for LHTs
- Non-slumping formula eliminates tile lipage May be applied up to 3/4" (19 mm) thick on
- horizontal applications
- 30 lb. bag provides same coverage as a typical 50 lb. bag of mortar

Specifications: ANSI: A118.15*, A118.4, A118.11 Packaging: 30 lb. bags Colors: Gray and White

SikaTile®-800 Unsanded Grout

Premium, Polymer Modified Portland Cement Unsanded Grout

- Polymer modified for hard, durable, professional results
- Stain resistant and color consistent
- For 1/16" (1.5 mm) to 1/8" (3 mm) grout joints
- Easy mixing just add water, no additives required Specifications: ANSI: A118.6

Packaging: 10 lb. box Colors: 18 Colors



Contact Sika: Phone 800.933.SIKA(7452) Website: www.SikaTile.com

Sika Corporation


201 Polito Avenue Lyndhurst, NJ 07071 Phone: 201-933-8800 Fax: 201-933-6225











Premium, Polymer Modified Portland Cement Sanded Grout

- Polymer modified for hard, durable, professional results
- Stain resistant and color consistent
- For 1/8" (3 mm) to 1/2" (13 mm) grout joints
- Easy mixing just add water, no additives required

Specifications: ANSI: A118.6

Packaging: 25 lb. bags Colors: 18 Colors

SikaTile®-815 Secure Grout

High Performance, Rapid-Setting, Polymer Modified Grout

- Polymer modified for hard, durable, high performing results
- Stain resistant, color consistent and efflorescence free
- For 1/16" (1.5 mm) to 1/2" (13 mm) grout joints
- Easy mixing just add water

BUILDING TRUST

Specifications: ANSI: A118.7

Packaging: 10 lb. bag Colors: 18 Colors





